

SAFETY DATA SHEET

Version 6.1
Revision Date 05/28/2017
Print Date 06/29/2019

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : 2-Mercaptoethanol

Product Number : M6250

Brand : Aldrich

CAS-No. : 60-24-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 Spruce Street
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 4), H227

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 2), H310

Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Skin sensitisation (Category 1), H317

Specific target organ toxicity - repeated exposure, Oral (Category 2), Liver, Heart, H373

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H227

Combustible liquid.

H301 + H331	Toxic if swallowed or if inhaled
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs (/*_ORG_REP_ORAL*/) through prolonged or repeated exposure if swallowed.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P350 + P310	IF ON SKIN: Gently wash with plenty of soap and water. Immediately call a POISON CENTER or doctor/ physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P314	Get medical advice/ attention if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Stench.

Stench., Rapidly absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms	:	Thioethylene glycol 2-Hydroxyethylmercaptan BME β-Mercaptoethanol
Formula	:	C ₂ H ₆ OS
Molecular weight	:	78.13 g/mol
CAS-No.	:	60-24-2
EC-No.	:	200-464-6

Hazardous components

Component	Classification	Concentration
-----------	----------------	---------------

2-Mercaptoethanol		
	Flam. Liq. 4; Acute Tox. 3; Acute Tox. 2; Skin Irrit. 2; Eye Dam. 1; Skin Sens. 1; STOT RE 2; Aquatic Acute 1; Aquatic Chronic 1; H227, H301 + H331, H310, H315, H317, H318, H373, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides, Sulphur oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
2-Mercaptoethanol	60-24-2	TWA	0.200000 ppm	USA. Workplace Environmental Exposure Levels (WEEL)
	Remarks	Skin		

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 30 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN 14387) respirator cartridges as a backup to enginee protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid Colour: colourlessyellow
b) Odour	Stench.
c) Odour Threshold	No data available
d) pH	4.5 - 6 at 500 g/l at 20 °C (68 °F)
e) Melting point/freezing point	< -49.99 °C (< -57.98 °F)
f) Initial boiling point and boiling range	157 °C (315 °F) - lit.
g) Flash point	74 °C (165 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 18 %(V) Lower explosion limit: 2.3 %(V)
k) Vapour pressure	0.76 hPa at 20 °C (68 °F) 4.67 hPa at 40 °C(104 °F)
l) Vapour density	2.70 - (Air = 1.0)
m) Relative density	1.114 g/cm3 at 25 °C (77 °F)
n) Water solubility	soluble
o) Partition coefficient: n-octanol/water	log Pow: -0.326log Pow: -0.056 at 25 °C (77 °F)
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

Relative vapour density	2.70 - (Air = 1.0)
-------------------------	--------------------

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Metals, Oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sulphur oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 98 - 162 mg/kg(2-Mercaptoethanol)

(OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 2 mg/l(2-Mercaptoethanol)

LC50 Inhalation - Rat - 4 h - 625 ppm(2-Mercaptoethanol)

LD50 Dermal - Rabbit - 112 mg/kg(2-Mercaptoethanol)

No data available(2-Mercaptoethanol)

Skin corrosion/irritation

Skin - Rabbit(2-Mercaptoethanol)

Result: Irritating to skin.

(Draize Test)

Serious eye damage/eye irritation

Eyes - Rabbit(2-Mercaptoethanol)

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Maximisation Test - Guinea pig(2-Mercaptoethanol)

May cause sensitisation by skin contact.

(OECD Test Guideline 406)

Germ cell mutagenicity

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available(2-Mercaptoethanol)

No data available(2-Mercaptoethanol)

Specific target organ toxicity - single exposure

No data available(2-Mercaptoethanol)

Specific target organ toxicity - repeated exposure

Ingestion - May cause damage to organs through prolonged or repeated exposure. - Liver, Heart

Aspiration hazard

No data available(2-Mercaptoethanol)

Additional Information

RTECS: KL5600000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Weakness, Unconsciousness, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema(2-Mercaptoethanol)

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(2-Mercaptoethanol)

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxicity to fish	LC50 - Leuciscus idus (Golden orfe) - 46 - 100 mg/l - 96.0 h(2-Mercaptoethanol)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia (water flea) - 0.89 mg/l - 48 h(2-Mercaptoethanol) (OECD Test Guideline 202)
Toxicity to algae	EC50 - Desmodesmus subspicatus (green algae) - 12 mg/l - 72 h(2-Mercaptoethanol)
Toxicity to bacteria	LC50 - Bacteria - 125 mg/l - 17 h(2-Mercaptoethanol)

12.2 Persistence and degradability

Biodegradability Result: < 30.0 % - Not readily biodegradable.
Result: 6 % - Not readily biodegradable.
aerobic - Exposure time 28 d(2-Mercaptoethanol)
Result: < 10 % - Not readily biodegradable.

Biochemical Oxygen Demand (BOD) 105 mg/g(2-Mercaptoethanol)

Chemical Oxygen Demand (COD) 1.894 mg/g(2-Mercaptoethanol)

12.3 Bioaccumulative potential

Does not accumulate in organisms.

12.4 Mobility in soil

No data available(2-Mercaptoethanol)

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 2966 Class: 6.1 Packing group: II
Proper shipping name: Thioglycol
Poison Inhalation Hazard: No

IMDG

UN number: 2966 Class: 6.1 Packing group: II EMS-No: F-A, S-A
Proper shipping name: THIOGLYCOL
Marine pollutant : yes

IATA

UN number: 2966 Class: 6.1 Packing group: II
Proper shipping name: Thioglycol

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
2-Mercaptoethanol	60-24-2	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
2-Mercaptoethanol	60-24-2	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
2-Mercaptoethanol	60-24-2	1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H227	Combustible liquid.
H301	Toxic if swallowed.

H301 + H331	Toxic if swallowed or if inhaled
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H373	May cause damage to organs (/\$/*_ORG_REP_ORAL\$/) through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

HMIS Rating

Health hazard:	4
Chronic Health Hazard:	*
Flammability:	2
Physical Hazard	0

NFPA Rating

Health hazard:	3
Fire Hazard:	2
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
 Product Safety – Americas Region
 1-800-521-8956
 Version: 6.1

Revision Date: 05/28/2017

Print Date: 06/29/2019