

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Product code : 00000000004045672

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Corrosion inhibitors

#### 1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.  
rue Jules Bordet - Parc Industriel - Zone C  
B-7180 Seneffe

Telephone : English Tel: +49 611237507  
Deutsch Tel: +49 611237500  
Français Tel: +32 64511149  
Italiano Tel: +32 64511170  
Español Tel: +32 64511163

E-mail address of person  
responsible for the SDS : sdseu@dowcorning.com

#### 1.4 Emergency telephone number

**Dow Corning (Barry U.K. 24h) Tél: +44 1446732350**  
**Dow Corning (Wiesbaden 24h) Tél: +49 61122158**  
**Dow Corning (Seneffe 24h) Tel: +32 64 888240**

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Chronic aquatic toxicity, Category 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves.

#### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Butane  
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics  
Naphtha (petroleum), hydrodesulfurized heavy  
Calcium salts of petroleum sulfonate

### 2.3 Other hazards

|| May displace oxygen and cause rapid suffocation.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Hydrocarbon aerosol propellant

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version  
5.0

Revision Date:  
06.09.2017

SDS Number:  
812589-00011

Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned  01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1 265-185-4 649-330-00-2	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
Calcium salts of petroleum sulfonate	68783-96-0 272-213-9	Skin Sens. 1B; H317	>= 1 - < 10
(Z)-N-9-Octadecenylpropane-1,3-diamine	7173-62-8 230-528-9	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.1 - < 0.25

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: Flush eyes with water as a precaution.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

If swallowed : Get medical attention if irritation develops and persists.  
: If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
May cause drowsiness or dizziness.  
Causes damage to organs through prolonged or repeated exposure.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Metal oxides  
Sulphur oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

#### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.  
Use only in an area equipped with explosion proof exhaust

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

---

ventilation.

- Advice on safe handling : Do not spray on an open flame or other ignition source.
- Do not get on skin or clothing.  
Do not breathe vapours or spray mist.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
- Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

### 7.3 Specific end use(s)

- Specific use(s) : For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version  
5.0

Revision Date:  
06.09.2017

SDS Number:  
812589-00011

Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium salts of petroleum sulfonate	Workers	Inhalation	Long-term systemic effects	11.75 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	3.33 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	1.03 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2.9 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1.667 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0.513 mg/kg bw/day
(Z)-N-9-Octadecenylpropane-1,3-diamine	Workers	Inhalation	Long-term systemic effects	0.8333 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	0.035 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	0.01 mg/kg bw/day

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium salts of petroleum sulfonate	Fresh water	1 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	226000000 mg/kg
	Marine sediment	226000000 mg/kg
	Soil	271000000 mg/kg
	Oral (Secondary Poisoning)	16.67 mg/kg food
(Z)-N-9-Octadecenylpropane-1,3-diamine	Fresh water	0.010 mg/l
	Marine water	0.001 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

	Intermittent use/release	0.0029 mg/l
	Sewage treatment plant	0.251 mg/l
	Fresh water sediment	0.22 mg/kg
	Marine sediment	0.022 mg/kg
	Soil	10 mg/kg

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.  
Use only in an area equipped with explosion proof exhaust ventilation.  
Use with local exhaust ventilation.

#### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Hand protection  
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

---

Appearance : Aerosol containing a dissolved gas

Colour : white, translucent

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0.87

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Molecular weight : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 4,951 mg/m3 Exposure time: 4 h Test atmosphere: vapour

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version  
5.0

Revision Date:  
06.09.2017

SDS Number:  
812589-00011

Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Naphtha (petroleum), hydrodesulfurized heavy:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 13.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Calcium salts of petroleum sulfonate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Acute oral toxicity : LD50 (Rat): 500 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species: Rabbit  
Result: Mild skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version  
5.0

Revision Date:  
06.09.2017

SDS Number:  
812589-00011

Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Assessment: Repeated exposure may cause skin dryness or cracking.

### **Naphtha (petroleum), hydrodesulfurized heavy:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
Remarks: Based on data from similar materials

Assessment: Repeated exposure may cause skin dryness or cracking.

### **Calcium salts of petroleum sulfonate:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation  
Remarks: Based on data from similar materials

### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: Corrosive after 3 minutes to 1 hour of exposure

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: No eye irritation  
Remarks: Based on data from similar materials

### **Naphtha (petroleum), hydrodesulfurized heavy:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: No eye irritation  
Remarks: Based on data from similar materials

### **Calcium salts of petroleum sulfonate:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials

### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Result: Irreversible effects on the eye  
Remarks: Based on skin corrosivity.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Result: negative  
Remarks: Based on data from similar materials

##### Naphtha (petroleum), hydrodesulfurized heavy:

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative  
Remarks: Based on data from similar materials

##### Calcium salts of petroleum sulfonate:

Test Type: Local lymph node assay (LLNA)  
Exposure routes: Skin contact  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: positive  
Remarks: Based on data from similar materials

Assessment: Probability or evidence of low to moderate skin sensitisation rate in humans

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Naphtha (petroleum), hydrodesulfurized heavy:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Inhalation  
Result: negative  
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Calcium salts of petroleum sulfonate:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 105 weeks  
Result: negative  
Remarks: Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

### **Naphtha (petroleum), hydrodesulfurized heavy:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 13 weeks  
Result: negative  
Remarks: Based on data from similar materials

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Naphtha (petroleum), hydrodesulfurized heavy:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

#### **Calcium salts of petroleum sulfonate:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative  
Remarks: Based on data from similar materials

#### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

---

### Components:

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Assessment: May cause drowsiness or dizziness.

#### **Naphtha (petroleum), hydrodesulfurized heavy:**

Assessment: May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

### Components:

#### **Naphtha (petroleum), hydrodesulfurized heavy:**

Target Organs: Central nervous system

Assessment: Causes damage to organs through prolonged or repeated exposure.

#### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Exposure routes: Ingestion

Assessment: Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

#### **Repeated dose toxicity**

### Components:

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species: Rat

NOAEL: 10,186 mg/m<sup>3</sup>

Application Route: inhalation (vapour)

Exposure time: 13 Weeks

#### **Naphtha (petroleum), hydrodesulfurized heavy:**

Species: Rat

NOAEL: 2.34 mg/l

LOAEL: 4.67 mg/l

Application Route: inhalation (vapour)

Exposure time: 6 Months

Method: OECD Test Guideline 413

Remarks: Based on data from similar materials

#### **Calcium salts of petroleum sulfonate:**

Species: Rat

NOAEL: 1,000 mg/kg

Application Route: Ingestion

Exposure time: 28 Days

Method: OECD Test Guideline 407

Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Species: Rat  
NOAEL: > 1,000 mg/kg  
Application Route: Skin contact  
Exposure time: 28 Days  
Method: OECD Test Guideline 410

### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Species: Rat  
NOAEL: 0.4 mg/kg  
Application Route: Ingestion  
Exposure time: 90 Days  
Method: OECD Test Guideline 408

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Naphtha (petroleum), hydrodesulfurized heavy:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### **Experience with human exposure**

### **Components:**

#### **Naphtha (petroleum), hydrodesulfurized heavy:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Dizziness, Headache, Neurological disorders

## SECTION 12: Ecological information

### 12.1 Toxicity

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Toxicity to algae : Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

: EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **Naphtha (petroleum), hydrodesulfurized heavy:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 10 - 30 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 10 - 22 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 4.6 - 10 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0.097 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Remarks: Based on data from similar materials

### **Calcium salts of petroleum sulfonate:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

Toxicity to fish	:	LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to algae	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC50 : > 10,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 0.08 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.013 - 0.025 mg/l Exposure time: 48 h
Toxicity to algae	:	ErC50 (Desmodesmus subspicatus (green algae)): 0.507 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  EC10 (Desmodesmus subspicatus (green algae)): 0.188 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	:	10
Toxicity to microorganisms	:	EC50 : 66 mg/l Exposure time: 3 h Method: OECD Test Guideline 209
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 0.1 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

### 12.2 Persistence and degradability

#### Components:

##### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 89 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Naphtha (petroleum), hydrodesulfurized heavy:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 74.7 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Calcium salts of petroleum sulfonate:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 9.1 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

##### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 62 %  
Exposure time: 28 d  
Remarks: Based on data from similar materials

### 12.3 Bioaccumulative potential

#### Components:

##### **Naphtha (petroleum), hydrodesulfurized heavy:**

Partition coefficient: n-octanol/water : log Pow: > 4  
Remarks: Based on data from similar materials

##### **(Z)-N-9-Octadecenylpropane-1,3-diamine:**

Bioaccumulation : Species: Fish  
Bioconcentration factor (BCF): > 500  
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 0.03

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

## SECTION 14: Transport information

### 14.1 UN number

- ADN : UN 1950  
ADR : UN 1950  
RID : UN 1950  
IMDG : UN 1950  
IATA : UN 1950

### 14.2 UN proper shipping name

- ADN : AEROSOLS  
ADR : AEROSOLS  
RID : AEROSOLS  
IMDG : AEROSOLS  
((Z)-N-9-Octadecenylpropane-1,3-diamine, Naphtha (petroleum), hydrotreated light)
- IATA : Aerosols, flammable

### 14.3 Transport hazard class(es)

- ADN : 2

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

**ADR** : 2  
**RID** : 2  
**IMDG** : 2.1  
**IATA** : 2.1

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : yes

**ADR**  
Environmentally hazardous : yes

**RID**  
Environmentally hazardous : yes

**IMDG**  
Marine pollutant : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version 5.0      Revision Date: 06.09.2017      SDS Number: 812589-00011      Date of last issue: 02.05.2017  
Date of first issue: 21.11.2014

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### The components of this product are reported in the following inventories:

- NZIoC : All ingredients listed or exempt.
- REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
- AICS : All ingredients listed or exempt.
- IECSC : All ingredients listed or exempt.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- PICCS : Consult your local Dow Corning office.
- TCSI : All ingredients listed or exempt.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

### Full text of H-Statements

- H226 : Flammable liquid and vapour.
- H302 : Harmful if swallowed.
- H304 : May be fatal if swallowed and enters airways.
- H314 : Causes severe skin burns and eye damage.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.
- H336 : May cause drowsiness or dizziness.
- H372 : Causes damage to organs through prolonged or repeated exposure.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.
- H411 : Toxic to aquatic life with long lasting effects.
- H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Aquatic Acute : Acute aquatic toxicity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Sens. 1	H317
STOT SE 3	H336

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## MOLYKOTE(R) METAL PROTECTOR PLUS COATING SPRAY

Version	Revision Date:	SDS Number:	Date of last issue: 02.05.2017
5.0	06.09.2017	812589-00011	Date of first issue: 21.11.2014

---

STOT RE 1	H372	Calculation method
Aquatic Chronic 2	H411	Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN