

SAFETY DATA SHEET

Version 6.6 Revision Date 10/01/2021 Print Date 01/15/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

| Product name | [:] 1,4-Dioxane |
|-------------------------|--------------------------|
| Product Number Brand | : 360481 : SIGALD |
| Index-No. | : 603-024-00-5 |
| CAS-No. | : 123-91-1 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

| Company | : Sigma-Aldrich Inc. 3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES |
|-----------|---|
| Telephone | : +1 314 771-5765 |
| Fax | : +1 800 325-5052 |

1.4 Emergency telephone

| Emergency Phone # | : 800-424-9300 CHEMTREC (USA) +1-703- |
|-------------------|---------------------------------------|
| | 527-3887 CHEMTREC (International) 24 |
| | Hours/day; 7 Days/week |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 Carcinogenicity (Category 2), H351 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

SIGALD - 360481

Page 1 of 11



| Hazard statement(s) | |
|----------------------------|---|
| H225 | Highly flammable liquid and vapor. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| | |
| Precautionary statement(s) | |
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. |
| P264 | Wash skin thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. |
| P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. |
| | Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P337 + P313 | If eye irritation persists: Get medical advice/ attention. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant |
| | foam to extinguish. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |
| | pland |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

Repeated exposure may cause skin dryness or cracking. May form explosive peroxides.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms

: Dioxane Diethylene oxide

| Formula | : C ₄ H ₈ O ₂ |
|------------------|--|
| Molecular weight | : 88.11 g/mol |
| CAS-No. | : 123-91-1 |
| EC-No. | : 204-661-8 |
| SIGALD - 360481 | |

Page 2 of 11



Index-No.

| Component | Classification | Concentration |
|-------------|--|---------------|
| 1,4-Dioxane | | |
| | Flam. Liq. 2; Eye Irrit. 2A; Carc. 2; STOT SE 3; H225, H319, H351, H335 Concentration limits: >= 20 %: STOT SE 3, H335; | <= 100 % |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Pay attention to flashback.

SIGALD - 360481

Page 3 of 11



Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

- Chemizorb®). Dispose of properly. Clean up affected area.
- **6.4 Reference to other sections** For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Test for peroxide formation periodically and before distillation.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

SIGALD - 360481

Page 4 of 11



7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis |
|-------------|----------|-----------------------------------|-------------------------------------|--|
| 1,4-Dioxane | 123-91-1 | TWA | 20 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Remarks | humans | animal carcinoge cutaneous absor | en with unknown relevance to ption |
| | | TWA | 25 ppm 90 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | Skin notati | on | |
| | | TWA | 100 ppm 360 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | | Skin desigr | nation | |
| | | С | 1 ppm 3.6 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| | | Potential Occupational Carcinogen | | inogen |
| | | PEL | 0.28 ppm 1 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| | | Skin | | |

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|------------------------------|-------------|
| Soil | 0.153 mg/kg |
| Sea water | 0.67 mg/l |
| Fresh water | 10 mg/l |
| Fresh water sediment | 37 mg/kg |
| Sewage treatment plant | 2700 mg/l |
| Aquatic intermittent release | 10 mg/l |

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

SIGALD - 360481

Page 5 of 11



Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 120 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| a) | Appearance | Form: liquid Color: colorless |
|----|---|---|
| b) | Odor | No data available |
| c) | Odor Threshold | No data available |
| d) | рН | 6.0 - 8 at 500 g/l at 20 °C (68 °F) |
| e) | Melting point/freezing point | Melting point/range: 10 - 12 °C (50 - 54 °F) - lit. |
| f) | Initial boiling point and boiling range | 100 - 102 °C 212 - 216 °F - lit. |
| g) | Flash point | 11 °C (52 °F) - closed cup |
| h) | Evaporation rate | No data available |
| i) | Flammability (solid, gas) | No data available |
| j) | Upper/lower | Upper explosion limit: 22 %(V) |

SIGALD - 360481

Page 6 of 11





| | flammability or explosive limits | Lower explosion limit: 2 %(V) |
|--------------------------|---|---|
| k) | Vapor pressure | 36 hPa at 20 °C (68 °F) 53 hPa at 25.20 °C(77.36 °F) |
| I) | Vapor density | 3.04 - (Air = 1.0) |
| m) | Density | 1.034 g/cm3 at 25 °C (77 °F) - lit. |
| | Relative density | 1.03 at 20 °C (68 °F) |
| n) | Water solubility | 1,000 g/l at 20 °C (68 °F) - completely miscible |
| o) | Partition coefficient: n-octanol/water | log Pow: -0.42 - Bioaccumulation is not expected. |
| p) | Autoignition temperature | 190.55 °C (374.99 °F) |
| q) | Decomposition temperature | No data available |
| r) | Viscosity | 1.27 mm2/s at 20 °C (68 °F) - OECD Test Guideline 114 - 0.93 mm2/s at 40 °C (104 °F) - OECD Test Guideline 114 - |
| s) | Explosive properties | No data available |
| t) | Oxidizing properties | none |
| Other safety information | | |
| | Surface tension | 36.9 mN/m at 25 °C (77 °F) |

3.04 - (Air = 1.0)

SECTION 10: Stability and reactivity

Relative vapor

10.1 Reactivity

9.2

Formation of peroxides possible. Vapors may form explosive mixture with air.

10.2 Chemical stability

density

The product is chemically stable under standard ambient conditions (room temperature) . Stable under recommended storage conditions. Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Warming. Moisture.

10.5 Incompatible materials

various plastics, copper compounds

SIGALD - 360481

Page 7 of 11



10.6 Hazardous decomposition products

Peroxides

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 5,150 mg/kg (OECD Test Guideline 401) Inhalation: No data available Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, Lung edema LD50 Dermal - Rabbit - 7,378 mg/kg Remarks: (RTECS) No data available

Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation - 20 h Remarks: (IUCLID)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation (OECD Test Guideline 405) (Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Maximization Test - Guinea pig Result: negative (Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Result: negative Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Result: negative Remarks: (ECHA)

Test Type: dominant lethal test Species: Mouse

Application Route: Intraperitoneal injection

SIGALD - 360481

Page 8 of 11



Result: negative Remarks: (ECHA)

Carcinogenicity

Suspected of causing cancer.

- IARC: 2B Group 2B: Possibly carcinogenic to humans (1,4-Dioxane)
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male - Oral - 716 Days - NOAEL (No observed adverse effect level) - 9.6 mg/kg Remarks: (ECHA)

RTECS: JG8225000

Nausea, Vomiting, Weakness, Dizziness, Vertigo, Headache, Sweating, loss of appetite, Kidney injury may occur., Liver injury may occur.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

The substance has delayed effects.

After absorption:

Headache Dizziness Nausea Vomiting

Absorption can result in damage to:

Liver Kidney

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Liver - Irregularities - Based on Human Evidence

SIGALD - 360481

Page 9 of 11



SECTION 12: Ecological information

12.1 Toxicity

| Toxicity to daphnia | semi-static test EC50 - Daphnia magna (Water flea) - > 1,000 mg/l |
|---------------------|---|
| and other aquatic | - 48 h |
| invertebrates | (OECD Test Guideline 202) |
| Toxicity to algae | static test ErC50 - Pseudokirchneriella subcapitata (green algae) - > 1,000 mg/l - 72 h (OECD Test Guideline 201) |

12.2 Persistence and degradability

aerobic - Exposure time 29 d Result: < 10 % - Not readily biodegradable. (OECD Test Guideline 301F)

12.3 Bioaccumulative potential

Biodegradability

Bioaccumulation Cyprinus carpio (Carp) - 10 mg/l(1,4-Dioxane)

Bioconcentration factor (BCF): 0.3 - 0.7 (OECD Test Guideline 305C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Forms toxic mixtures in water, dilution measures notwithstanding. Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1165 Class: 3 Proper shipping name: Dioxane Reportable Quantity (RQ): 100 lbs Poison Inhalation Hazard: No Packing group: II

IMDG

SIGALD - 360481

Page 10 of 11



UN number: 1165 Class: 3 Proper shipping name: DIOXANE

ΙΑΤΑ

UN number: 1165 Class: 3 Proper shipping name: Dioxane Packing group: II

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

| | CAS-No. | Revision Date |
|-------------|----------|---------------|
| 1,4-Dioxane | 123-91-1 | 2007-03-01 |

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.6

Revision Date: 10/01/2021

Print Date: 01/15/2022

SIGALD - 360481

Page 11 of 11



