

Safety Data Sheet

Carbon Dioxide

WestAir Gases & Equipment Inc 2506 Market St San Diego, CA 92102 619-239-7571 http://westairgases.com

Section 1: Product and Company Identification

WestAir Gases & Equipment Inc 2506 Market St San Diego, CA 92102 619-239-7571 http://westairgases.com

Product Code: Carbon Dioxide

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:

Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

CAS # 124-38-9

Chemical Substance	Chemical Family	Trade Names
CARBON DIOXIDE, GAS	oxides of carbon	CARBONIC ACID GAS; CARBONIC ANHYDRIDE; CARBON DIOXIDE; CARBON OXIDE; UN 1013; CO2

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Do not induce vomiting.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Non-flammable	Non-flammable	Any appropriate escape-type, self-contained breathing apparatus.
		Non-flammable

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do	Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of	Stop leak if possible without personal risk.
not touch spilled material.	water supplies and sewers.	•

Methods for Cleanup	Other Information
Stop leak, evacuate, remove source of ignition.	None

Section 7: Handling and Storage

Handling	Storage
Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from	Store and handle in accordance with all current
incompatible substances.	regulations and standards

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

CARBON DIOXIDE, GAS: CARBON DIOXIDE: 5000 ppm (9000 mg/m3) OSHA TWA 10000 ppm (18000 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 30000 ppm (54000 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 5000 ppm ACGIH TWA 30000 ppm ACGIH STEL 5000 ppm (9000 mg/m3) NIOSH recommended TWA 10 hour(s) 30000 ppm (54000 mg/m3) NIOSH recommended STEL

Engineering Controls

Handle only in fully enclosed systems.

Eye Protection	Skin Protection	Respiratory Protection
For the gas: Eye protection not required, but recommended. For the liquid:	For the gas: Protective clothing is not	Any appropriate escape-
Wear splash resistant safety goggles. Contact lenses should not be worn.	required. For the liquid: Wear	type, self-contained
Provide an emergency eye wash fountain and quick drench shower in the	appropriate protective, cold insulating	breathing apparatus.
immediate work area.	clothing.	

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Gas	Colorless	Colorless	N/A	Gas	Odorless	Acid taste

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Not flammable	Not available	N/A	Nonflammable	Nonflammable	Nonflammable

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosity
Not available	-71 F (-57 C) @ 4000 mmHg	43700 mmHg @ 21 C	1.5 (Air=1)	1.522 @ 21 C	Soluble	3.7 (saturated aqueous solution) @ 101.3 kPa (carbonic acid)	Not available	Not applicable	0.01657 cP @ 0 C

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
44.01	C-O2	0.114	Not available	Not applicable	Not applicable	Soluble: Alcohol, acetone, hydrocarbons, organic solvents

Section 10: Stability and Reactivity

Stability	Conditions to Avoid	Incompatible Materials
Stable at normal temperatures	Stable at normal temperatures	Combustible materials, oxidizing materials, metal salts, reducing agents,
and pressure.	and pressure.	metal carbide, metals, bases

Hazardous Decomposition Products	Possibility of Hazardous Reactions	
Carbon monoxide	Will not polymerize.	

Section 11: Toxicology Information

Acute Effects

Oral LD50	Dermal LD50	Inhalation
Not	Not	Ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual
established	established	disturbances, suffocation, convulsions, coma

Eye Irritation	Skin Irritation	Sensitization
Irritation, frostbite, blurred vision	Liquid: blisters, frostbite	Difficulty breathing

Chronic Effects

Carcinogenicity Mutagenicity		Reproductive Effects	Developmental Effects	
	Not available	Not established	Available.	No data

Section 12: Ecological Information

Fate and Transport

i ato ana manopon			
Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
			LITALIOULIEUR

Fish toxicity: 150000 ug/L 48 day(s)
(Mortality) Brown trout (Salmo trutta)
Invertibrate toxicity: Not available
Algal toxicity: Not available
Phyto toxicity: Not available
Other toxicity: Not available

Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Carbon dioxide	UN1013	2.2	Not applicable	2.2	75 kg or L	150kg	None

Canadian Transportation of Dangerous Goods

Shipping Name	UN N	lumber	Class	Packing Group / Risk Group
Carbon dioxide	UN10)13	2.2	Not applicable

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40
Not regulated.	Not regulated.	Not regulated.

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	No	No	Yes

SARA 372.65

Not regulated.

OSHA Process Safety

Not regulated.

State Regulations

CA Proposition 65
Not regulated.

Canadian Regulations

WHMIS Classification

National Inventory Status

	2	,	
US Inventory (TSCA)		TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
	Listed on inventory.	Not listed.	Listed on inventory.

Section 16: Other Information

NFPA Rating

HEALTH=2 FIRE=0 REACTIVITY=0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard