

# SAFETY DATA SHEET

Version 8.11  
Revision Date 03/02/2024  
Print Date 06/15/2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifiers

Product name : Ethyl Alcohol 200 Proof GR ACS  
Product Number : EX0276  
Brand : Millipore  
Index-No. : 603-002-00-5  
CAS-No. : 64-17-5

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis  
Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

### 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES  
Telephone : +1 314 771-5765  
Fax : +1 800 325-5052

### 1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225  
Eye irritation (Category 2A), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Millipore - EX0276

Page 1 of 12

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H319

Causes serious eye irritation.

Precautionary Statements

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313

If eye irritation persists: Get medical advice/ attention.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P235

Store in a well-ventilated place. Keep cool.

P501

Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula	:	C <sub>2</sub> H <sub>6</sub> O
Molecular weight	:	46.07 g/mol
CAS-No.	:	64-17-5
EC-No.	:	200-578-6
Index-No.	:	603-002-00-5

Component	Classification	Concentration
<b>ethanol</b>		
	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

### 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		PEL	1,000 ppm 1,900 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

## 8.2 Exposure controls

### Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

#### Body Protection

Flame retardant antistatic protective clothing.

### Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- |   |   |
|---|---|
| a) Appearance                                   | Form: liquid<br>Color: colorless                                    |
| b) Odor   | alcohol-like  |
| c) Odor Threshold                               | 0.1 ppm   |
| d) pH   | 7.0 at 10 g/l at 20 °C (68 °F)                                      |
| e) Melting point/freezing point                 | Melting point/freezing point: -114.0 °C (-173.2 °F) at 1,013.25 hPa |
| f) Initial boiling point and boiling range      | 78.29 °C 172.92 °F at 1,013 hPa                                     |
| g) Flash point                                  | 13 °C (55 °F) - closed cup  |
| h) Evaporation rate                             | No data available   |
| i) Flammability (solid, gas)                    | No data available   |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 27.7 %(V)<br>Lower explosion limit: 3.1 %(V) |
| k) Vapor pressure                               | 57.26 hPa at 19.6 °C (67.3 °F)                                      |
| l) Vapor density                                | 1.6   |
| m) Density                                      | 0.79 g/cm <sup>3</sup> at 20 °C (68 °F)                             |
| Relative density                                | No data available   |
| n) Water solubility                             | 1,000 g/l at 20 °C (68 °F) - completely miscible                    |
| o) Partition coefficient: n-octanol/water       | log Pow: -0.35 at 24 °C (75 °F) - Bioaccumulation is not expected.  |
| p) Autoignition temperature                     | 363 - 425 °C (685 - 797 °F) at 1,013 hPa                            |
| q) Decomposition                                | Distillable in an undecomposed state at normal pressure.            |

Millipore - EX0276

Page 6 of 12

- temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties none

## 9.2 Other safety information

Conductivity	< 1 $\mu$ S/cm
Surface tension	22.31 mN/m at 20 °C (68 °F) - similar to water
Relative vapor density	1.6

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide  
 perchlorates  
 perchloric acid  
 Nitric acid  
 mercury(II) nitrate  
 permanganic acid  
 Nitriles  
 peroxi compounds  
 Strong oxidizing agents  
 nitrosyl compounds  
 Peroxides  
 sodium  
 Potassium  
 halogen oxides  
 calcium hypochlorite  
 nitrogen dioxide  
 metallic oxides  
 uranium hexafluoride  
 iodides  
 Chlorine  
 Alkali metals  
 Alkaline earth metals  
 alkali oxides  
 Ethylene oxide  
 silver  
 with  
 Nitric acid

Millipore - EX0276

Page 7 of 12

silver compounds  
with  
Ammonia  
potassium permanganate  
with  
conc. sulfuric acid  
Risk of ignition or formation of inflammable gases or vapours with:  
halogen-halogen compounds  
chromium(VI) oxide  
chromyl chloride  
Fluorine  
hydrides  
Oxides of phosphorus  
platinum  
Nitric acid  
with  
potassium permanganate

#### **10.4 Conditions to avoid**

Warming.  
Warming.

#### **10.5 Incompatible materials**

No data available

#### **10.6 Hazardous decomposition products**

In the event of fire: see section 5

---

### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

##### **Acute toxicity**

LD50 Oral - Rat - male and female - 10,470 mg/kg  
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l - vapor

(OECD Test Guideline 403)

Dermal: No data available

##### **Skin corrosion/irritation**

Skin - Rabbit

Result: No skin irritation - 24 h

(OECD Test Guideline 404)

##### **Serious eye damage/eye irritation**

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

##### **Respiratory or skin sensitization**

Maximization Test - Guinea pig



Result: negative  
(OECD Test Guideline 406)  
Remarks: (in analogy to similar products)  
The value is given in analogy to the following substances: Methanol

### **Germ cell mutagenicity**

Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
Test Type: In vitro mammalian cell gene mutation test  
Test system: mouse lymphoma cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

Test Type: dominant lethal test  
Species: Mouse

Application Route: Oral  
Method: OECD Test Guideline 478  
Result: Positive results were obtained in some in vivo tests.

### **Carcinogenicity**

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.  
OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

No data available

### **Specific target organ toxicity - single exposure**

No data available

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

## **11.2 Additional Information**

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) - 1,730 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,200 mg/kg

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 15,300 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h Remarks: (ECHA)
Toxicity to algae	static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	semi-static test NOEC - Danio rerio (zebra fish) - 250 mg/l - 120 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	semi-static test NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d Remarks: (ECHA)

### 12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 15 d Result: ca.95 % - Readily biodegradable. (OECD Test Guideline 301E)
Biochemical Oxygen Demand (BOD)	930 - 1,670 mg/g Remarks: (Lit.)
Theoretical oxygen demand	2,100 mg/g Remarks: (Lit.)

### 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

No interference with wastewater treatment plants are to be expected when used properly.

Millipore - EX0276

Page 10 of 12

Discharge into the environment must be avoided.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

---

## SECTION 14: Transport information

### DOT (US)

UN number: 1170 Class: 3 Packing group: II  
Proper shipping name: Ethanol  
Reportable Quantity (RQ):  
Poison Inhalation Hazard: No

### IMDG

UN number: 1170 Class: 3 Packing group: II EMS-No: F-E, S-D  
Proper shipping name: ETHANOL

### IATA

UN number: 1170 Class: 3 Packing group: II  
Proper shipping name: Ethanol

---

## SECTION 15: Regulatory information

### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Massachusetts Right To Know Components

	CAS-No.	Revision Date
ethanol	64-17-5	

### Pennsylvania Right To Know Components

	CAS-No.	Revision Date
ethanol	64-17-5	

Millipore - EX0276

Page 11 of 12

**California Prop. 65 Components**

, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov.ethanol](http://www.P65Warnings.ca.gov.ethanol)

CAS-No.  
64-17-5

Revision Date

---

**SECTION 16: Other information****Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 8.11

Revision Date: 03/02/2024

Print Date: 06/15/2024