



Black Nickel Oxide

Product Information

Black Nickel Oxide

This MSDS includes both Grade A and Grade F Black Nickel Oxide

Distributed by: Vale Inco Limited 200 Bay St., Royal Bank Plaza Suite 1600, South Tower, PO B Toronto, ON Canada, M5J 2K2 msds@valeinco.com	ox 70		
Imported by:			
In North & South America:	In Europe, Middle East, Africa,	<u>In Japan:</u>	
	India, & Pakistan:		
Vale Inco America Inc.		Vale Inco Japan Limited	
Park 80 West, Plaza Two	Vale Inco Europe Limited	Atago Green Hills,	
Saddle Brook, NJ 07663	1st Floor, Gordon House,	MORI Tower 25F	
USA	10, Greencoat Place	5-1 Atago 2-chome, Minatoku,	
	London SW1P 1PH	Tokvo 105-6225, Japan	
	England		
In China	I <u>n Asia (Except China, Japan, Ind</u> New Zealand:	lia, & Pakistan), Australia, and	
Vale Inco China			
Room 2501 Aurora Place	Vale Inco Pacific Limited		
99 Fu Cheng Road	15/F Wilson House 19-27 Wyndham Street		
Pudong, Shanghai	Central, Hong Kong		

Hazards Identification

GHS:

200120 P.R. China

Health	Environmental	Physical
Skin Sensitization – Category 1	Aquatic Toxicity – Chronic 4	
Carcinogenicity – Category 1A		
STOT * Repeated Exposure – Category 1		

* - Single Organ Target Toxicity

Symbols: Exclamation mark, Health Hazard







Signal Word: Danger

Hazard Statements: May cause cancer by inhalation May cause allergic skin reaction Causes damage to lungs through prolonged or repeated inhalation exposure May cause long lasting harmful effects to aquatic life

Precautionary Statements: Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust or fume. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and protective clothing. Do not eat, drink or smoke when using this product. Avoid release to the environment.

Response:

If exposed or concerned; get medical advice/attention If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment; see first aid section

Storage: Store locked up

Disposal:

Dispose of contents/container in accordance to local/regional/national/international regulations

Composition

Substance

Mixture

Typical Analysis:

Ni	Cu	Fe	S	0
76.6%	<0.0005%	0.009%	0.0002%	22.0%





Hazardous	Typical Composition	C.A.S.	EINECS/
Ingredients	(%)	Number	EC Label No.
Nickel Oxide	99.5%	1313-99-1	215-215-7
Nickel Hydroxide	0.5%	12054-48-7	235-008-5

First Aid Measures

Ingestion	Large quantities of water should be drunk. Seek medical attention.
Inhalation	Remove from exposure. Seek medical attention.
Skin	Wash thoroughly with water. For rashes seek medical advice. Show label if possible
Eyes	Irrigate eyeball thoroughly with water for at least 10 minutes. If discomfort persists seek medical attention.
Wounds	Cleanse thoroughly to remove any nickel oxide particles.

Fire Fighting Measures

Suitable extinguishing media:	Any, type to be selected according to materials stored in the immediate neighborhood.
Special risks:	Non flammable. Extinguish surrounding fires with appropriate methods.
Special protective equipment for fire fighting:	None needed. Wear protective equipment if required for other materials within the immediate vicinity.

Accidental Release Measures

Person related precautionary measures:	Wear appropriate nationally approved respirators if collection and disposal of spills is likely to cause the concentration limits of airborne nickel to exceed the locally prescribed exposure limits.
Environmental Protection measures:	No specific measures needed.
Procedures for cleaning/absorption:	Collect spills by wet sweeping or vacuuming with the vacuum exhaust passing through a high efficiency particulate arresting (HEPA) filter if exhaust is discharged into the work place. Replace in original container. Nickel-containing material is normally collected to recover nickel values.



MATERIAL SAFETY DATA SHEET

Handling and Storage

Handling:

Prevent the generation of inhalable dusts e.g. by the use of suitable ventilation. Do not inhale dust. Wear appropriate nationally approved respirators if handling is likely to cause the concentration limits of airborne nickel to exceed the locally prescribed exposure limits. Wear suitable protective clothing and gloves. As packed, nickel oxide may constitute a manual handling risk.

Storage: Keep in the container supplied, and keep container closed when not in use. Local regulations should be followed regarding the storage of this product.

Exposure Controls / Personal Protection

Nickel Oxide – CAS 1313-99-1			
	Exposure Limit (mg/m3)	Year	
ACGIH TLV-TWA ⁽¹⁾	0.2 * ‡ as Ni	2008	
UK WEL ⁽²⁾	0.5 as Ni	2006	
Japan	1 as Ni	1968	
Korea	0.1 as Ni	2006	
China	1 as Ni	2007	

* Inhalable fraction

‡ Insoluble inorganic fraction

Nickel Hydroxide – CAS 12054-48-7			
	Exposure Limit (mg/m3)	Year	
ACGIH TLV-TWA ⁽¹⁾	0.2 * ‡ as Ni	2008	
UK WEL ⁽²⁾	0.5 as Ni	2006	
Japan	1 as Ni	1968	
Korea	0.1 as Ni	2006	
China	1 as Ni	2007	

* Inhalable fraction

‡ Insoluble inorganic fraction

Occupational exposure controls:

a. Respiratory protection:

Do not inhale dust. Ventilation is normally required when handling or using this product to keep airborne nickel oxide below the nationally authorized limits. If ventilation alone cannot control exposure, use respirators nationally approved for the purpose.





- b. Eye protection: Avoid repeated eye contact. Wear goggles or face shield.
- *c. Hand & Skin Protection:* Avoid repeated skin contact. Wear suitable protective clothing and gloves, which should be selected specifically for the working place, depending on concentration and quantity of the hazardous material (overalls and leather/rubber gloves). Wash skin thoroughly after handling and before eating, drinking or smoking. Change contaminated clothing frequently. Launder clothing and gloves as needed. Use of skin-protective barrier cream advised.

Physical and Chemical Properties

Black odourless powder.

Ingredient	Mol. Wt.
Nickel Oxide	74.71

рН	Not Applicable (N/A)
Boiling point/ boiling range	N/A
Melting Point	1984°C
Flash Point	N/A
Evaporation rate	N/A
Flammability	N/A
Explosive properties	Not explosive
Vapour pressure	N/A
Vapour density	N/A
Tap density	2.0 g/cm3
Solubility cold water	N/A
Solubility hot water	N/A
Partition coefficient	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Oxidizing properties	Not oxidizing
Viscosity	N/A
Particle size	8 micrometers (8 μm)
Magnetic Properties	Paramagmetic

Stability and Reactivity

Conditions to be avoided:No hazardous exothermic reaction.Substances to be avoided:None.

Hazardous decomposition
products:No information available.



MATERIAL SAFETY DATA SHEET

Toxicological Information

As a mixture the toxicological properties of this product are unknown. The toxicology of the reported ingredients are summarized below.

Nickel Oxide

Inhalation:

Evidence for the association of nickel compound exposures and cancer risk comes mainly from workers in now obsolete nickel refining operations. The studies of nickel workers suggest that respiratory cancer risks are primarily related to exposure to relatively insoluble forms of nickel notably sulphidic and oxidic nickel at concentrations greater than 10mg/m3. Toxic respiratory effects in animals may be caused by reduced particle clearance capacity.

The International Agency for Research on Cancer (IARC) in 1990 and the U.S. Tenth Report on Carcinogens in 2002 concluded there was sufficient evidence that nickel compounds are carcinogenic to humans. The Report of the International Committee on Nickel Carcinogenesis in Man reported that workers who have been primarily exposed to nickel oxide showed some evidence of increased lung cancer.

The European Union Commission in 1991 classified nickel oxide and work involving exposure to dusts, fumes and sprays produced during the roasting and electro refining of nickel-copper mattes as carcinogenic processes. ACGIH has re-evaluated the data regarding the carcinogenicity of nickel and nickel compounds and has classified nickel oxide as a confirmed human carcinogen, Class A1.

There is some evidence that the inhalation of nickel oxide has resulted in an increased incidence of malignant lung tumors in rats. Inhalation of nickel oxide at concentrations 50 times the TLV, produced pneumoconiosis in hamsters. Repeated intratracheal instillation of nickel oxide produced an increased incidence of malignant lung tumors in rats.

- Wounds: Nickel oxide has caused tumors at the site of injection in rodents.
- Ingestion: The U.S. National Institute for Occupational Safety and Health (NIOSH) concluded there is no evidence that nickel and its inorganic compounds are carcinogenic when ingested.
- Conditions: Prolonged and intimate skin contact can cause an allergic skin rash in previously sensitized individuals.

Reproductive

Preexisting

Toxicity: There is no evidence of mutagenesis. Animal experiments indicate that soluble nickel ingestion causes adverse effects on fetal development at a threshold oral exposure of 2.2 mg/Ni/kg/day by pregnant rats. Data are insufficient to determine if this effect occurs in humans and no regulatory agency has classified soluble forms of nickel as reproductive risks for humans.

Nickel Hydroxide

No information currently available.





Ecological Information

Ecotoxic effects:

Aquatic Toxicity – Chronic category 4

Further Ecological Data: Due to poor solubility of the product, no harmful effects on aquatic organisms are to be expected when handled and used with due care and attention.

Disposal Considerations

Nickel-containing material is normally collected to recover nickel values. Should disposal be deemed necessary, follow local regulations.

Transport Information

International Maritime Dangerous Goods Code	Not regulated.
International Civil Aviation Organization Technical Instructions for the Carriage of Dangerous Goods by Air	Not regulated.
U.S. Dept. of Transportation Regulations	Not regulated.
Canadian Transportation of Dangerous Goods Act	Not regulated.
European Agreement Concerning the International Carriage of Dangerous Goods by Road	Not regulated.

Regulatory Information

Other Information

Note:

Vale Inco believes that the information in this Material Safety Data Sheet is accurate. However, Vale Inco makes no express or implied warranty as to the accuracy of such information and expressly disclaims any liability resulting from reliance on such information.

1. Threshold Limit Values of the American Conference of Governmental Industrial Hygienists. 2009.

2. Maximum Exposure Limit of the Health and Safety Executive in the U.K. in EH40/00.

Safety Data Sheet prepared by:

Vale Inco Limited 200 Bay St., Royal Bank Plaza Suite 1600, South Tower, PO Box 70 Toronto, ON Canada, M5J 2K2 Product Stewardship (416) 361-7801 msds@valeinco.com

SDS available online at www.valeinco.com