

# SAFETY DATA SHEET

Creation Date 24-Mar-2014 Revision Date 14-Feb-2020 Revision Number 2

# 1. Identification

Product Name p-Xylene

Cat No. : A10534

**CAS-No** 106-42-3

Synonyms 1,4-Dimethylbenzene

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

### Company

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

## **Emergency Telephone Number**

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

# 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Target Organs - Central nervous system (CNS), Respiratory system.

Aspiration Toxicity

Category 1

#### Label Elements

# Signal Word

Danger

# **Hazard Statements**

Flammable liquid and vapor

p-Xylene Revision Date 14-Feb-2020

May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause respiratory irritation Harmful in contact with skin or if inhaled



### **Precautionary Statements**

#### Prevention

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

Call a POISON CENTER or doctor/physician if you feel unwell

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

#### **Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

# Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposa

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
p-Xylene	106-42-3	>95

p-Xylene Revision Date 14-Feb-2020

# 4. First-aid measures

**Eye Contact**Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Inhalation** Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. Risk of serious damage to the lungs (by

aspiration).

Ingestion Aspiration hazard. Do NOT induce vomiting. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Most important symptoms and

effects

Difficulty in breathing. . Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

Notes to Physician

# 5. Fire-fighting measures

Suitable Extinguishing Media CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point 25 °C / 77 °F

Method - No information available

Autoignition Temperature 465 °C / 869 °F

**Explosion Limits** 

**Upper** 7.0 vol % **Lower** 1.1 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### **Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

# **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrocarbons. Aldehydes.

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA** 

HealthFlammabilityInstabilityPhysical hazards330N/A

# 6. Accidental release measures

precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

Revision Date 14-Feb-2020 p-Xylene

**Environmental Precautions** 

Avoid release to the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system. Collect spillage.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

# Handling and storage

Handling

Use only under a chemical fume hood. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only

non-sparking tools.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
p-Xylene	TWA: 100 ppm		IDLH: 900 ppm	TWA: 100 ppm
	STEL: 150 ppm		TWA: 100 ppm	STEL: 150 ppm
			TWA: 435 mg/m <sup>3</sup>	
			STEL: 150 ppm	
			STEL: 655 mg/m <sup>3</sup>	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures** Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined

areas.

**Personal Protective Equipment** 

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection** 

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection** 

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures** 

# 9. Physical and chemical properties

**Physical State** Liquid **Appearance** Colorless Odor aromatic

**Odor Threshold** No information available

Not applicable pН 13 °C / 55.4 °F Melting Point/Range

Revision Date 14-Feb-2020

p-Xylene

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper Lower
 7.0 vol %

 Lower
 1.1 vol %

 Vapor Pressure
 8 mbar @ 20 °C

 Vapor Density
 3.7 (Air = 1.0)

Specific Gravity 0.866

SolubilityNo information availablePartition coefficient; n-octanol/waterNo data availableAutoignition Temperature465 °C / 869 °FDecomposition TemperatureNo information availableViscosity0.648 mPa.s (20°C)

Molecular FormulaC8 H10Molecular Weight106.17

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrocarbons, Aldehydes

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

# 11. Toxicological information

### **Acute Toxicity**

# Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
p-Xylene	LD50 = 4029 mg/kg (Rat)	Not listed	LC50 = 4740 ppm (Rat) 4 h LC50 = 4550 ppm (Rat) 4 h

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

ĺ	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
	p-Xylene	106-42-3	Not listed				

Mutagenic Effects No information available

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Revision Date 14-Feb-2020 p-Xylene

**Developmental Effects** Developmental effects have occurred in experimental animals.

Teratogenic effects have occurred in experimental animals. **Teratogenicity** 

STOT - single exposure Central nervous system (CNS) Respiratory system

STOT - repeated exposure None known

**Aspiration hazard** Category 1

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

**Endocrine Disruptor Information** No information available

Other Adverse Effects See actual entry in RTECS for complete information.

# 12. Ecological information

### **Ecotoxicity**

Do not empty into drains. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
p-Xylene	EC50: = 3.2 mg/L, 72h static	LC50: = 2.6 mg/L, 96h	EC50 = 5.7 mg/L 30 min	EC50: 3.55 - 6.31 mg/L, 48h
	(Pseudokirchneriella	(Oncorhynchus mykiss)		Static (Daphnia magna)
	subcapitata)	LC50: 7.2 - 9.9 mg/L, 96h		
	EC50: = 105.1 mg/L, 3h	static (Pimephales		
	(Chlorella vulgaris)	promelas)		
		LC50: = 8.8 mg/L, 96h		
		semi-static (Poecilia		
		reticulata)		
		LC50: = 2.6 mg/L, 96h static		
		(Oncorhynchus mykiss)		

Persistence and Degradability Insoluble in water Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** . Is not likely mobile in the environment due its low water solubility. Will likely be mobile in

the environment due to its volatility.

Component	log Pow
p-Xylene	3.15

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

UN1307 **UN-No XYLENES Proper Shipping Name Hazard Class** 3

Ш

**Packing Group** 

TDG

UN-No UN1307 **Proper Shipping Name XYLENES** 

**Hazard Class Packing Group** Ш

Revision Date 14-Feb-2020 p-Xylene

IATA

UN1307 **UN-No Proper Shipping Name XYLENES** 

**Hazard Class Packing Group** Ш

IMDG/IMO

**UN-No** UN1307 **XYLENES Proper Shipping Name** 

**Hazard Class** Ш **Packing Group** 

# 15. Regulatory information

### **United States of America Inventory**

Component	CAS-No	TSCA	TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory Flags
p-Xylene	106-42-3	X	ACTIVE	-

#### Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
p-Xylene	106-42-3	Х	-	203-396-5	Х	X	Х	Χ	KE-35430

# U.S. Federal Regulations

### **SARA 313**

	Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Г	p-Xylene	106-42-3	>95	1.0

#### SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

OVA (Cicali Water Act)				
Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
p-Xvlene	X	=	-	-

### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
p-Xylene	X		-

**OSHA** - Occupational Safety and

Health Administration

Not applicable

**CERCLA** 

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
p-Xylene	100 lb	-

**California Proposition 65** This product does not contain any Proposition 65 chemicals.

p-Xylene Revision Date 14-Feb-2020

#### U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
p-Xylene	Х	Х	X	Х	-

**U.S. Department of Transportation** 

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Moderate risk, Grade 2

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

 Creation Date
 24-Mar-2014

 Revision Date
 14-Feb-2020

 Print Date
 14-Feb-2020

**Revision Summary** SDS authoring systems update, replaces ChemGes SDS No. 106-42-3.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**