SAFETY DATA SHEET



NALCO 41 CORROSION INHIBITOR

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	NALCO 41 CORROSION INHIBITOR	
Other means of identification	:	Not applicable.	
Recommended use	:	CORROSION INHIBITOR	
Restrictions on use	:	Refer to available product literature or ask your local Sales Representative for restrictions on use and dose limits.	
Company	:	Nalco Company 1601 W. Diehl Road Naperville, Illinois 60563-1198 USA TEL: (630)305-1000	
Emergency telephone number	:	(800) 424-9300 (24 Hours) CHEMTREC	
Issuing date	:	04/23/2014	

Section: 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids Skin irritation Serious eye damage/eye irritation Specific target organ toxicity -		Category 3 Category 2 Category 1 Category 3 (Central Nervous System)
single exposure Aspiration hazard		Category 1
GHS Label element		
Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness.
Precautionary Statements	:	Prevention: Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after
		1/10

handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. **Response:** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

: None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Concentration: (%)
Severely Hydrotreated Heavy Naphthenic	64742-52-5	60 - 100
Distillate Butanol	71-36-3	5 - 10
Benzenesulfonic acid, C10-14-alkyl derivatives, sodium salts	69669-44-9	1 - 5

|--|

In case of eye contact	lea	nse immediately with plenty of water, also under the eyelids, for at ast 15 minutes. Remove contact lenses, if present and easy to do. ontinue rinsing. Get medical attention immediately.	
In case of skin contact	Us	ash off immediately with plenty of water for at least 15 minutes. The a mild soap if available. Get medical attention if irritation velops and persists.	
If swallowed	un	NOT induce vomiting. Never give anything by mouth to an conscious person. Aspiration hazard if swallowed - can enter ngs and cause damage. Get medical attention immediately.	
If inhaled		emove to fresh air. Treat symptomatically. Get medical attention if mptoms occur.	
Protection of first-aiders	no	event of emergency assess the danger before taking action. Do t put yourself at risk of injury. If in doubt, contact emergency sponders.Use personal protective equipment as required.	
Notes to physician	: Tre	eat symptomatically.	
See toxicological information (Section 11)			

Section: 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting.	:	Fire Hazard Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Hazardous combustion products	:	Carbon oxides
Special protective equipment for firefighters	:	Use personal protective equipment
Specific extinguishing methods	:	Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.
Section: 6. ACCIDENTAL RE	LE	ASE MEASURES
Section: 6. ACCIDENTAL RE Personal precautions, protective equipment and emergency procedures	: :	ASE MEASURES Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Personal precautions, protective equipment and	:	Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and
Personal precautions, protective equipment and emergency procedures	:	Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice on safe handling	Avoid contact with skin and eyes. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from fire, sparks and heated surfaces. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Use only with adequate ventilation.
Conditions for safe storage	Keep away from heat and sources of ignition. Keep in a cool, well- ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Packaging material : Suitable material: Keep in properly labelled containers.

Unsuitable material: not determined

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Severely Hydrotreated Heavy Naphthenic Distillate	64742-52-5	TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		STEL (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA Z1
Butanol	71-36-3	TWA	20 ppm	ACGIH
		Ceiling	50 ppm 150 mg/m3	NIOSH REL
		TWA	100 ppm 300 mg/m3	OSHA Z1

Engineering measures :	Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.	
Personal protective equipment		
Eye protection :	Safety goggles Face-shield	
Hand protection :	Wear the following personal protective equipment: Standard glove type. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.	
Skin protection :	Wear suitable protective clothing.	
Respiratory protection :	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.	
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.	

HUMAN EXPOSURE CHARACTERIZATION :

Based on our recommended product application and personal protective equipment, the potential human exposure is: Moderate

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	: Liquid		
Colour	: Blue		
Odour	: Hydrocarbon		

Flash point	:	49 °C
рН	:	9.5 - 12, 50 %
Odour Threshold	:	no data available
Melting point/freezing point	:	-15 °C ASTM D-97
Initial boiling point and boiling range	:	no data available
Evaporation rate	:	no data available
Flammability (solid, gas)	:	no data available
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	no data available
Relative vapour density	:	no data available
Relative density	:	0.91 (15.6 °C) ASTM D-1298
Density	:	0.91 g/cm3
Water solubility	:	insoluble
Solubility in other solvents	:	no data available
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	no data available
Thermal decomposition	:	Carbon oxides
Viscosity, dynamic	:	no data available
Viscosity, kinematic	:	no data available
VOC	:	84.8 %

Section: 10. STABILITY AND REACTIVITY

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Contact with strong oxidizers (e.g. chlorine, peroxides, chromates, nitric acid, perchlorate, concentrated oxygen, permanganate) may generate heat, fires, explosions and/or toxic vapors.
Hazardous decomposition products	:	If heated above flashpoint and/or sprayed, formation of combustible mixtures with air is possible. Oxides of carbon Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation, Eye contact, Skin contact
exposure		

Potential Health Effects

Eyes	: Causes serious eye damage.
Skin	: Causes skin irritation.
Ingestion	: May be fatal if swallowed and enters airways.
Inhalation	: Inhalation may cause central nervous system effects.
Chronic Exposure	: Health injuries are not known or expected under normal use.
Experience with human expe	osure
Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Irritation
Ingestion	: Vomiting
Inhalation	: Dizziness, Drowsiness
Toxicity	
Product	
Acute oral toxicity	: Acute toxicity estimate : 2,997 mg/kg
Acute inhalation toxicity	: no data available
Acute dermal toxicity	: no data available
Skin corrosion/irritation	: no data available
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available

STOT - single exposure	: no data available
STOT - repeated exposure	: no data available

Aspiration toxicity : no data available

HUMAN HAZARD CHARACTERIZATION

Based on our hazard characterization, the potential human hazard is: Moderate

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects	: This product has no known ecotoxicological effects	•
<u>Product</u>		
Toxicity to fish	: LC50 Rainbow Trout: 3.85 mg/l Exposure time: 96 hrs Test substance: Product	
Toxicity to daphnia and other aquatic invertebrates.	: LC50 Ceriodaphnia dubia: 2.18 mg/l Exposure time: 48 hrs Test substance: Product	
Toxicity to algae	: no data available	

Persistence and degradability

Chemical Oxygen Demand (COD): 2,900,000 mg/l

Mobility

The environmental fate was estimated using a level III fugacity model embedded in the EPI (estimation program interface) Suite TM, provided by the US EPA. The model assumes a steady state condition between the total input and output. The level III model does not require equilibrium between the defined media. The information provided is intended to give the user a general estimate of the environmental fate of this product under the defined conditions of the models. If released into the environment this material is expected to distribute to the air, water and soil/sediment in the approximate respective percentages;

Air	:	<5%
Water	:	30 - 50%
Soil	:	30 - 50%

The portion in water is expected to be soluble or dispersible.

Bioaccumulative potential

This preparation or material is not expected to bioaccumulate.

Other information

no data available

ENVIRONMENTAL HAZARD AND EXPOSURE CHARACTERIZATION Based on our hazard characterization, the potential environmental hazard is: Moderate

Based on our recommended product application and the product's characteristics, the potential environmental exposure is: Moderate

Section: 13. DISPOSAL CONSIDERATIONS

If this product becomes a waste, it could meet the criteria of a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Before disposal, it should be determined if the waste meets the criteria of a hazardous waste.

Hazardous Waste:	D001	
Disposal methods	Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of compliance with local regulations. Dispose of wastes approved waste disposal facility.	
Disposal considerations	Dispose of as unused product. Empty containers sho taken to an approved waste handling site for recyclin disposal. Do not re-use empty containers.	

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

Proper shipping name Technical name(s) UN/ID No. Transport hazard class(es) Packing group	:	FLAMMABLE LIQUID, N.O.S. N-BUTANOL UN 1993 3 III
Air transport (IATA)		
Proper shipping name Technical name(s) UN/ID No. Transport hazard class(es) Packing group	:	FLAMMABLE LIQUID, N.O.S. N-BUTANOL UN 1993 3 III
Sea Transport (IMDG/IMO)		
Proper shipping name Technical name(s) UN/ID No. Transport hazard class(es) Packing group	:	FLAMMABLE LIQUID, N.O.S. N-BUTANOL UN 1993 3 III

Section: 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ
			(lbs)
Butanol	71-36-3	5000	83500

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	Acute Health Hazard Fire Hazard	
SARA 302 :	SARA 302: No chemicals ir requirements of SARA Title	the reporting
SARA 313 :	The following components by SARA Title III, Section 3 Butanol	ls established 5.988 %

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

INTERNATIONAL CHEMICAL CONTROL LAWS :

TOXIC SUBSTANCES CONTROL ACT (TSCA)

The substances in this preparation are included on or exempted from the TSCA 8(b) Inventory (40 CFR 710)


CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA)

The substance(s) in this preparation are included in or exempted from the Domestic Substance List (DSL).

EUROPE

The substances in this preparation have been reviewed for compliance with the EINECS or ELINCS inventories.

Section: 16. OTHER INFORMATION



Due to our commitment to Product Stewardship, we have evaluated the human and environmental hazards and exposures of this product. Based on our recommended use of this product, we have characterized the product's general risk. This information should provide assistance for your own risk management practices. We have evaluated our product's risk as follows:

* The human risk is: Moderate

* The environmental risk is: Moderate

Any use inconsistent with our recommendations may affect the risk characterization. Our sales representative will assist you to determine if your product application is consistent with our recommendations. Together we can implement an appropriate risk management process.

Revision Date	:	04/23/2014
Version Number	:	1.0
Prepared By	:	Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

For additional copies of an MSDS visit www.nalco.com and request access.