

SAFETY DATA SHEET

Version 1.0 Revision Date 11/06/2019 Print Date 11/13/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Anthracene

Product Number : 48567
Brand : Supelco
CAS-No. : 120-12-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 Spruce Street ST. LOUIS MO 63103

UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Carcinogenicity (Category 1A), H350 Short-term (acute) aquatic hazard (Category 1), H400 Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H350 May cause cancer.

H410 Very toxic to aquatic life with long lasting effects.

Supelco - 48567 Page 1 of 10



Precautionary statement(s) P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P391 Collect spillage. P405 Store locked up.

Dispose of contents/ container to an approved waste disposal

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

plant.

Photosensitizer., Lachrymator.

SECTION 3: Composition/information on ingredients

3.1 Substances

P501

Formula : $C_{14}H_{10}$ Molecular weight : 178.23 g/mol CAS-No. : 120-12-7 EC-No. : 204-371-1

Component	Classification	Concentration
Anthracene		
	Carc. 1A; Aquatic Acute 1;	<= 100 %
	Aquatic Chronic 1; H350,	
	H400, H410	
	M-Factor - Aquatic Acute:	
	1,000	
	M-Factor - Aquatic	
	Chronic: 1,000	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

Supelco - 48567

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.



Page 2 of 10

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Supelco - 48567 Page 3 of 10

Store at room temperature.

Storage class (TRGS 510): 11: Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components with workplace control parameters							
Component	CAS-No.	Value	Control	Basis			
·			parameters				
Anthracene	120-12-7	TWA	0.2 mg/m3	USA. Occupational Exposure			
				Limits (OSHA) - Table Z-1			
				Limits for Air Contaminants			
	Remarks	1910.1002 As used in §1910.1000 (Table Z-1), coal tar pitch volatiles					
		include the fused polycyclic hydrocarbons which volatilize					
		from the distillation residues of coal, petroleum (excluding					
		asphalt), wood, and other organic matter. Asphalt (CAS					
		8052-42-4, and CAS 64742-93-4) is not covered under the					
		'coal tar pitch volatiles' standard					
		OSHA specifically regulated carcinogen					
		TWA	0.1 mg/m3	USA. NIOSH Recommended			
				Exposure Limits			
		Potential Occupational Carcinogen					
		NIOSH considers coal tar, coal tar pitch, and creosote to be					
		coal tar products.					
		cyclohexane-extractable fraction					
		See Appendix C					
		See Appendix A					
		PEL	California permissible exposure				
				limits for chemical			
				contaminants (Title 8, Article			
				107)			
		Coal tar pitch volatiles (benzene or cyclohexane-soluble					
		fraction) in	clude fused poly	cyclic hydrocarbons (some of			
				ns) which volatilize from the			
		distillation	residues of coal,	petroleum (excluding asphalt),			
		wood, and other organic matter. Asphalt (CAS 8052-42-4,					
				t covered under the 'coal tar			
		pitch volatiles' standard.					
		PEL	0.2 mg/m3	California permissible exposure			
				limits for chemical			
				contaminants (Title 8, Article			
				107)			
		Coal tar pitch volatiles (benzene or cyclohexane-soluble					
		fraction) include fused polycyclic hydrocarbons (some of					
		which are known carcinogens) which volatilize from the					
		distillation residues of coal, petroleum (excluding asphalt),					
		wood, and other organic matter. Asphalt (CAS 8052-42-4,					

Supelco - 48567 Page 4 of 10



and CAS 64742-93-4) is not covered under the 'coal tar
pitch volatiles' standard.

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Anthracene	120-12-7	1- Hydroxypyr ene	2.5 µg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			
		3- hydroxyben zo(a)pyrene		Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift at end of workweek			

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Chloroprene

Minimum layer thickness: 0.6 mm Break through time: 480 min

Material tested: Camapren® (KCL 722 / Aldrich Z677493, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 30 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective

Supelco - 48567 Page 5 of 10



equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: crystalline

Colour: beige

b) Odourc) Odour Thresholdd) pHNo data availableNo data available

e) Melting point/range: 210 - 215 °C (410 - 419 °F) - lit.

point/freezing point

f) Initial boiling point 340 °C 644 °F - lit. and boiling range

g) Flash point 121.0 °C (249.8 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower Lower explosion limit: 0.6 %(V) flammability or

k) Vapour pressure 1.3 hPa at 145.0 °C (293.0 °F)

I) Vapour density No data availablem) Relative density No data availablen) Water solubility No data available

o) Partition coefficient: log Pow: 4.65 at ca.20 °C (ca.68 °F)

n-octanol/water

explosive limits

p) Auto-ignition 540.0 °C (1004.0 °F)

temperature

q) Decomposition No data available

temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

Supelco - 48567 Page 6 of 10

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents, Hypochlorites

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Inhalation: No data available Dermal: No data available

LD50 Intraperitoneal - Mouse - 430 mg/kg

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory or skin sensitisation

Causes photosensitivity. Exposure to light can result in allergic reactions resulting in dermatologic lesions, which can vary from sunburnlike responses to edematous, vesiculated lesions, or bullae

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Supelco - 48567 Page 7 of 10

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Possible tumor promoter., Headache, Nausea, Weakness

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Blood -

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 0.001 mg/l - 96.0 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 0.10 mg/l - 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Indication of bioaccumulation.

Bioaccumulation Pimephales promelas (fathead minnow) - 42 d

- 0.01191 mg/l(Anthracene)

Bioconcentration factor (BCF): 649

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Supelco - 48567 Page 8 of 10

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 3077 Class: 9 Packing group: III

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Anthracene)

Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Anthracene)

Marine pollutant : yes

IATA

UN number: 3077 Class: 9 Packing group: III

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Anthracene)

Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids

or > 5kg for solids.

SECTION 15: Regulatory information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Anthracene CAS-No. Revision Date 120-12-7 2007-07-01

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Anthracene CAS-No. Revision Date 120-12-7 2007-07-01

Supelco - 48567 Page 9 of 10

SECTION 16: Other information

Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 1.0 Revision Date: 11/06/2019 Print Date: 11/13/2019

Supelco - 48567 Page 10 of 10

