

Revised: March 8, 2013

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: DuPont[™] Teflon[®] Multi-Use Dry, Wax Lubricant - Aerosol

Product Use: Lubricant.

Manufacturer/Supplier: Finish Line Technologies

50 Wireless Blvd Hauppauge, NY

11788

Phone Number: 631-666-7300

Emergency Phone: PROSAR: 1-800-217-5157

CHEMTREC: 1-800-424-9300

Date of Preparation: October 28, 2011

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER

EXTREMELY FLAMMABLE. HARMFUL BY INHALATION. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation: Harmful by inhalation. May cause respiratory tract irritation. Intentional

misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. This product may be aspirated into the lungs and cause

chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Abdominal pain. Headache. CNS depression. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.



Santian 2	COMPOSITION	INFORMATION	ON INGREDIENTS
Section 5:	・しいいというロコいは	INCURINALION	JN INGREIJENIS

Ingredient	CAS#	Wt. %
Naphtha (petroleum), hydrotreated light	64742-49-0	60 - 100
Propane	74-98-6	5 - 10
Butane	106-97-8	5 - 10
Fatty acids, tall-oil, compounds with 4,5-dihydro-2-nortall-oil alkyl-1H-		
imidazole-1-ethanol	68132-48-9	1 - 5
Fatty acids, tall-oil, polymers with adipic acid and trimethylolpropane	100930-27-6	0.5 - 1.5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	0.1 - 1
Paraffin waxes (petroleum), clay-treated	64742-43-4	3 - 7

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of soap and water.

Remove contaminated clothing and shoes. Wash clothing before reuse. Call a

physician if irritation develops and persists.

Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion: DO NOT induce vomiting. If victim is conscious and alert, give 2 cupfuls of

water. Never give anything by mouth to an unconscious person. Seek medical

attention or call poison control.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Extremely flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon, noxious fumes.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.



Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container. Provide ventilation.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Launder contaminated clothing before reuse. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49 °C / 120 °F. Store away from light.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

	Exposure Limits	
Ingredient	OSHA-PEL	ACGIH-TLV
Naphtha (petroleum), hydrotreated light	Not available.	Not available.
Propane	1000 ppm	1000 ppm
Butane	Not available.	800 ppm
Fatty acids, tall-oil, compounds with 4,5-dihydro-2-nortall-oil		
alkyl-1H-imidazole-1-ethanol	Not available.	Not available.
Fatty acids, tall-oil, polymers with adipic acid and trimethylolpropane	Not available.	Not available.
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m³ (mist)	5 mg/m³ (mist)
Paraffin waxes (petroleum), clay-treated	Not available.	Not available.

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory

equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Translucent.

Color: White.

Odour: Light petroleum odor.

Odour Threshold: Not applicable.

Physical State: Gas/Pressurized Liquid.

pH: Not available.

Viscosity: < 10 cSt @ 40 °C (104 °F)

Freezing Point: Not available. **Boiling Point:** Not available. **Flash Point:** Not available. **Evaporation Rate:** Not applicable. **Lower Flammability Limit:** Not applicable. **Upper Flammability Limit:** Not applicable. **Vapor Pressure:** Not applicable. Not available. Vapor Density: **Specific Gravity:** Not available. Solubility in Water: Insoluble. **Coefficient of Water/Oil Distribution:** Not available. **Auto-ignition Temperature:** Not available.

Percent Volatile, wt. %: 85
VOC content, wt. %: 85

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: None known.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon,

noxious fumes.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC ₅₀
Naphtha (petroleum), hydrotreated light	>5000mg/kg, rat	73680 ppm 4hr, rat
Propane	Not available.	658 mg/L 4hr, rat
Butane	Not available.	658 mg/L 4hr, rat
Fatty acids, tall-oil, compounds with 4,5-dihydro-2-		
nortall-oil alkyl-1H-imidazole-1-ethanol	Not available.	Not available.
Fatty acids, tall-oil, polymers with adipic acid and		
trimethylolpropane	Not available.	Not available.
Distillates (petroleum), hydrotreated heavy naphthenic	>5000 mg/kg, rat	2.18 mg/L 4hr, rat
Paraffin waxes (petroleum), clay-treated	10000 mg/kg, rat	Not available.

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking

and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, edema, drying,

defatting and cracking of the skin.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation: Harmful by inhalation. May cause respiratory tract irritation. This product may be

aspirated into the lungs and cause chemical pneumonitis. Vapours may cause

drowsiness and dizziness.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS/OSHA criteria. **Carcinogenicity:** Not hazardous by WHMIS/OSHA criteria.

Ingredient Chemical Listed as Carcinogen or Potential

Carcinogen *

Naphtha (petroleum), hydrotreated light Not listed.
Propane Not listed.
Butane Not listed.

Fatty acids, tall-oil, compounds with 4,5-dihydro-2-nortall-oil alkyl-

1H-imidazole-1-ethanol

Fatty acids, tall-oil, polymers with adipic acid and trimethylolpropane Not listed.

Distillates (petroleum), hydrotreated heavy naphthenic

Paraffin waxes (petroleum), clay-treated

Not listed. Not listed.

Not listed.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria. **Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

^{*} See Section 15 for more information.



Section 14: TRANSPORTATION INFORMATION

DOT Classification

UN1950; AEROSOLS, Flammable; Class 2.1 ORM-D (≤ 1L)

TDG Classification

UN1950; AEROSOLS, Flammable; Class 2.1

Limited Quantity (≤ 1L)

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section	Section		
	302 (EHS)	304 EHS	CERCLA	Section
	TPQ (lbs.)	RQ (lbs.)	RQ (lbs.)	313
Naphtha (petroleum), hydrotreated light	Not listed.	Not listed.	Not listed.	Not listed.
Propane	Not listed.	Not listed.	Not listed.	Not listed.
Butane	Not listed.	Not listed.	Not listed.	Not listed.
Fatty acids, tall-oil, compounds with 4,5-dihydro-2-				
nortall-oil alkyl-1H-imidazole-1-ethanol	Not listed.	Not listed.	Not listed.	Not listed.
Fatty acids, tall-oil, polymers with adipic acid				
and trimethylolpropane	Not listed.	Not listed.	Not listed.	Not listed.
Distillates (petroleum), hydrotreated heavy				
naphthenic	Not listed.	Not listed.	Not listed.	Not listed.
Paraffin waxes (petroleum), clay-treated	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Naphtha (petroleum), hydrotreated light	DSL	Yes.
Propane	DSL	Yes.
Butane	DSL	Yes.
Fatty acids, tall-oil, compounds with 4,5-dihydro-2-nortall-oil alkyl-1H-		
imidazole-1-ethanol	DSL	Yes.
Fatty acids, tall-oil, polymers with adipic acid and trimethylolpropane	DSL	Yes.
Distillates (petroleum), hydrotreated heavy naphthenic	DSL	Yes.
Paraffin waxes (petroleum), clay-treated	DSL	Yes.

HMIS - Hazardous Materials Identification System

Health - 1 Flammability - 3 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 1 Fire - 3 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class A - Compressed Gas Class B5 - Flammable Aerosol Class D1B - Toxic Material Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:









SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen. A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: October 28, 2014

Version #: 2.0

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com