

SAFETY DATA SHEET

Creation Date 16-Jan-2015

Revision Date 24-Dec-2021

Revision Number 5

1. Identification

1,2-Diaminoethane; 1,2-Ethanediamine; Dimethylenediamine

Product Name

Ethylenediamine

E479-4; E479-500; S80006

CAS No Synonyms

Recommended Use Laboratory chemicals. Uses advised against Food, drug, pesticide or biocidal product use.

107-15-3

Details of the supplier of the safety data sheet

Company Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 3	
Acute oral toxicity	Category 4	
Acute dermal toxicity	Category 4	
Skin Corrosion/Irritation	Category 1 B	
Serious Eye Damage/Eye Irritation	Category 1	
Respiratory Sensitization	Category 1	
Skin Sensitization	Category 1	
Specific target organ toxicity (single exposure)	Category 3	
Target Organs - Respiratory system.		

Label Elements

Signal Word Danger

Hazard Statements

Flammable liquid and vapor Causes severe skin burns and eye damage May cause respiratory irritation May cause an allergic skin reaction May cause allergy or asthma symptoms or breathing difficulties if inhaled Harmful if swallowed or in contact with skin



Precautionary Statements Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapors/spray In case of inadequate ventilation wear respiratory protection Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool **Response**

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Ingestion

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

erte tte	Component	CAS No	Weight %
----------	-----------	--------	----------

Ethylene diamine		107-15-3 > 98		
4. First-aid measures				
General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minute Immediate medical attention is required.		under the eyelids, for at least 15 minutes.	
Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and gloves, including the inside, before re-use. Cal immediately.				
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not u mouth-to-mouth method if victim ingested or inhaled the substance; give artificial result the aid of a pocket mask equipped with a one-way valve or other proper respirated medical device. Call a physician immediately.		inhaled the substance; give artificial respiration a one-way valve or other proper respiratory	
Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anythir unconscious person. Call a physician immediately.				
Most important symptoms and effects	symptoms or overexposure corrosive ma of stomach o damage to th include rash, lightheadedn	breathing difficulties if inhaled. e may be headache, dizziness, t terial. Use of gastric lavage or e r esophagus should be investiga e delicate tissue and danger of itching, swelling, trouble breath ess, chest pain, muscle pain or	Ity in breathing. May cause allergy or asthma May cause allergic skin reaction. Symptoms tiredness, nausea and vomiting: Product is a emesis is contraindicated. Possible perforation ated: Ingestion causes severe swelling, sever perforation: Symptoms of allergic reaction ma ing, tingling of the hands and feet, dizziness, flushing	
Notes to Physician	Treat sympto	matically		

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	34 °C / 93.2 °F
Method -	No information available
Autoignition Temperature	385 °C / 725 °F
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	14.2 vol % 2.6 vol % It No information available No information available

Specific Hazards Arising from the Chemical Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx). Ammonia. Hydrogen cyanide (hydrocyanic acid). **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u>	Health 3	Flammability 2	Instability 0	Physical hazards N/A
		6. Accidental rel	ease measures	
Personal	Precautions	personnel to safe areas. Ke sources of ignition. Take pr	uipment as required. Ensure ac eep people away from and upw ecautionary measures against	ind of spill/leak. Remove all static discharges.
Environm	nental Precautions		the environment. See Section to surface water or sanitary sev	5
Methods Up	for Containment and Cl	ean Soak up with inert absorber Remove all sources of ignit	nt material. Keep in suitable, clo ion. Use spark-proof tools and	
		7. Handling a	and storage	
HandlingWear personal protective equipment/face protection. Do not get in eyes, on skin, or clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray ingest. If swallowed then seek immediate medical assistance. Keep away from op flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.				eathe mist/vapors/spray. Do not nce. Keep away from open
Storage.				lated place. Keep away from a. Incompatible Materials. Acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethylene diamine	TWA: 10 ppm	(Vacated) TWA: 10 ppm	IDLH: 1000 ppm	TWA: 10 ppm
	Skin	(Vacated) TWA: 25 mg/m ³	TWA: 10 ppm	STEL: 3 mg/m ³
		TWA: 10 ppm	TWA: 25 mg/m ³	_
		TWA: 25 mg/m ³		

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. F	Physical and chemical properties
Physical State	Liquid
Appearance	Clear, Viscous
Odor	Ammonia-like
Odor Threshold	No information available
рН	11.9 (25 %)
Melting Point/Range	8.5 °C / 47.3 °F
Boiling Point/Range	118 °C / 244.4 °F @ 760 mmHg
Flash Point	34 °C / 93.2 °F
Evaporation Rate	0.91 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	14.2 vol %
Lower	2.6 vol %
Vapor Pressure	12 mmHg @ 25 °C
Vapor Density	2.07 (Air = 1.0)
Specific Gravity	.8980
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	385 °C / 725 °F
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C2H8N2
Molecular Weight	60.1
VOC Content(%)	98
	10. Stability and reactivity

Reactive Hazard None known, based on information available				
Stability Stable under normal conditions.				
Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.				
Incompatible Materials Acids, Acid anhydrides, Acid chlorides, Oxidizing agent				
Hazardous Decomposition Products Nitrogen oxides (NOx), Ammonia, Hydrogen cyanide (hydrocyanic acid)				
Hazardous Polymerization Hazardous polymerization does not occur.				
Hazardous Reactions	None under normal processing.			

11. Toxicological information

Acute Toxicity

Product Information

Component Information						
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation			
Ethylene diamine 637 mg/kg (Rat) LD50 = 560 mg/kg (Rabbit) 14.7 mg/L/4h (F 866 mg/kg (Rat) 866 mg/kg (Rat) 14.7 mg/L/4h (F						
Toxicologically Synergistic No information available Products Delayed and immediate effects as well as chronic effects from short and long-term exposure						
belayed and mimediate enects as well as throme enects from short and long-term exposure						
Irritation Causes burns by all exposure routes						

Sensitization		May cause sensitization by skin contact							
Carcinogenicity		The table below indicates whether each agency has listed any ingredient as a carcinogen.							
Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico			
Ethylene diamine	107-15-3	Not listed	Not listed	Not listed	Not listed	Not listed			
Mutagenic Effects		No information ava	ailable						
Reproductive Effec	ts	No information ava	ailable.						
Developmental Effe	ects	No information ava	ailable.						
Teratogenicity		No information available.							
STOT - single exposure STOT - repeated exposure		Respiratory system None known							
Aspiration hazard		No information available							
Symptoms / effects,both acute and delayed		d Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing							
Endocrine Disruptor Information		No information available							
Other Adverse Effects		The toxicological properties have not been fully investigated.							

12. Ecological information

Ecotoxicity

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethylene diamine	EC50: = 645 mg/L, 72h (Pseudokirchneriella subcapitata) EC50: = 151 mg/L, 96h (Pseudokirchneriella subcapitata)	LC50: 191 - 254 mg/L, 96h flow-through (Pimephales promelas) LC50: 98.6 - 131.6 mg/L, 96h static (Pimephales promelas) LC50: 180 - 560 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 115.7 mg/L, 96h semi-static (Pimephales promelas)	EC50 = 29 mg/L 17 h	EC50: = 17 mg/L, 48h (Daphnia magna)

Persistence and Degradability

Persistence is unlikely

Bioaccumulation/Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Ethylene diamine	-1.221

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a

hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

	14. Transport information
DOT	
UN-No	UN1604
Proper Shipping Name	ETHYLENEDIAMINE
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	II
TDG	
UN-No	UN1604
Proper Shipping Name	ETHYLENEDIAMINE
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	II
IATA_	
UN-No	UN1604
Proper Shipping Name	ETHYLENEDIAMINE
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1604
Proper Shipping Name	ETHYLENEDIAMINE
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	
	15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethylene diamine	107-15-3	Х	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710) X - Listed '-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethylene diamine	107-15-3	Х	-	203-468-6	Х	Х	Х	Х	Х	KE-13141

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Ethylene diamine	X	5000 lb	-	-

Not applicable

OSHA - Occupational Safety and Not applicable Health Administration

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethylene diamine	5000 lb	5000 lb

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethylene diamine	Х	Х	Х	-	Х

U.S. Department of Transportation

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product contains the following DHS chemicals: **Legend** - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Ethylene diamine	Release STQs - 20000lb

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High
			Concern (SVHC)
Ethylene diamine	-	Use restricted. See item 75.	SVHC Candidate list - 203-468-6 -
-		(see link for restriction details)	Respiratory sensitising properties
			(Article 57(f) - human health)

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

https://echa.europa.eu/authorisation-list

https://echa.europa.eu/substances-restricted-under-reach

https://echa.europa.eu/candidate-list-table

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethylene diamine	107-15-3	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

	Qualifying Quantities Qualifying Quantities				
		for Major Accident	for Safety Report		
		Notification	Requirements		
Ethylene diamine	107-15-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information		
Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com	
Creation Date Revision Date Print Date Revision Summary	16-Jan-2015 24-Dec-2021 24-Dec-2021 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).	

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS