



1. Product and Company Identification

Product Code:	FB08
Product Name:	Fryer Boil Out
Company Name:	DISCO, Inc.
	1895 Brannan Road
	McDonough, GA 30253
Web site address: Emergency Contact:	www.discoinc.com
Information:	www.chemtelinc.com

Phone Number: (800) 548-5150

(800) 255-3924 (813) 248-0573

2. Hazards Identification

Serious Eye Damage/Eye Irritation, Category 2A Skin Corrosion/Irritation, Category 1A



GHS Signal Word:	Danger
GHS Hazard Phrases:	H319 - Causes serious eye irritation.
	H314 - Causes severe skin burns and eye damage.
GHS Precaution Phrases:	P264 - Wash hands thoroughly after handling.
	P280 - Wear eye and face protection when handling. Wear protective gloves.
	P260 - Do not breathe dust, fumes, mist or spray.
GHS Response Phrases:	P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+313 - If eye irritation persists, get medical advice/attention.
	P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
	P363 - Wash contaminated clothing before reuse.
	P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P310 - Immediately call a doctor or Poison Control Center.
	P321 - Specific treatment see appropriate section on the product label.
GHS Storage and Disposal	P405 - Store locked up.
Phrases:	P501 - Unused product is not a RCRA Hazardous waste. However, contaminated
	product and wastes may be RCRA hazardous. Users are advised to determine the
	appropriate disposal method based on local, state and federal regulations and comply with those regulations.
Hazard Rating System:	HEALTH 2
	FLAMMABILITY 0
	REACTIVITY 2 Health
	PPE D COR
HMIS:	NFPA: V Special Hazard

Potential Health Effects (Acute and Chronic):	Prolonged or repeated skin contact may cause dermatitis.
Inhalation:	Harmful if inhaled. May cause respiratory tract irritation. Irritation may lead to chemical pneumonitis and pulmonary edema. Causes severe irritation of upper respiratory tract with coughing, burns, breathing difficulty, and possible coma. Causes chemical burns to the respiratory tract. Skin: May be harmful if absorbed through skin.
Skin Contact:	Causes skin irritation. Causes skin burns. May cause deep, penetrating ulcers of the skin. May cause skin rash (in milder cases), and cold and clammy skin with cyanosis or pale color.
Eye Contact:	Causes eye burns. May cause chemical conjunctivitis and corneal damage.
Ingestion:	May be harmful if swallowed. May cause severe and permanent damage to the digestive tract. Causes gastrointestinal tract burns. Causes severe pain, nausea, vomiting, diarrhea, and shock. May cause corrosion and permanent tissue destruction of the esophagus and digestive tract. May cause systemic effects.
3	. Composition/Information on Ingredients

CAS # Hazard	lous Components (Chemical Name)	Concentration
--------------	---------------------------------	---------------

1310-73-2 Sodium hydroxide {Caustic soda; Lye solution} <25.0 %

	4. First Aid Measures
Emergency and First Aid Procedures:	
In Case of Inhalation:	Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Get medical aid.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse. Wash off with soap and plenty of water.
In Case of Eye Contact:	In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes. Get medical aid immediately.
In Case of Ingestion:	Get medical aid immediately. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person.

	5. Fire Fightin	g Measures	
Flash Pt:			
Explosive Limits:	LEL:	UEL:	
Autoignition Pt:			
Suitable Extinguishing Medi		use agent most appropriate to extinguish s iners. Use water spray, dry chemical, carbo	-
Fire Fighting Instructions:	MSHA/NIOSH (approved or ec keep fire-exposed containers of Contact with moisture or water	ained breathing apparatus in pressure-dem uivalent), and full protective gear. Use wate ool. Use water with caution and in flooding may generate sufficient heat to ignite nea may evolve flammable hydrogen gas. Wea nting if necessary.	er spray to amounts. rby combustible
Flammable Properties and Hazards:			SDS #9565

	6. Accidental Release Measures
Steps To Be Taken In Case Material Is Released Or Spilled:	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container. (See Exposure Controls, Personal Protection section). Provide ventilation. Do not let this chemical enter the environment. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Do not get water on spilled substances or inside containers. Environmental precautions. Do not let product enter drains. Methods for cleaning up. Sweep up and shovel. Keep in suitable, closed containers fordisposal.
	7. Handling and Storage
Precautions To Be Taken in Handling:	Minimize dust generation and accumulation. Do not get in eyes, on skin, or on clothing. Do not ingest or inhale. Wash thoroughly after handling. Do not allow water to get into the container because of violent reaction. Keep container tightly closed. Avoid ingestion and inhalation. Discard contaminated shoes. Use only with adequate ventilation. Normal measures for preventive fire protection.
Precautions To Be Taken in Storing:	Store in a cool, dry place. Store in a tightly closed container. Keep away from acids. Store in a cool, dry, well-ventilated area away from incompatible substances. Corrosives area. Store protected from moisture.

	8	. Exposure Co	ontrols/Perso	onal Protection	
CAS #	Partial Chemical	Name	OSHA TWA	ACGIH TWA	Other Limits
1310-73-2	Sodium hydroxide solution}	{Caustic soda; Lye	PEL: 2 mg/m3	CEIL: 2 mg/m3	
Respiratory E (Specify Type		requirements or Eur conditions warrant r of dusts are desired	ropean Standard E respirator use. is no l, use type N95 (U sted and approved	meets OSHA's 29 CFR 1910. N 149 must be followed wher ot required. Where protection S) or type P1 (EN 143) dust m under appropriate governme	never workplace from nuisance levels nasks. Use respirators
Eye Protectio	on:	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Wear chemical splash goggles. Safety glasses.			
Protective Glo	oves:	Wear appropriate protective gloves to prevent skin exposure. For prolonged or repeated contact use protective gloves.			
Other Protect	ive Clothing:	Wear a chemical apron.			
Engineering (Ventilation et		Facilities storing or a safety shower.	utilizing this materi	al should be equipped with ar	n eyewash facility and
Work/Hygieni Practices:	c/Maintenance	General industrial hygiene practice.			

	9. Physical and Ch	emical Prop	erties		
Physical States:	[]Gas []Liquid [X] Solid			
Appearance and Odor:	Granular, white to off-white po mild odor.	wder			
Melting Point:					
Boiling Point:					
Autoignition Pt: Flash Pt:					
Explosive Limits:	LEL:	UEL:			
Specific Gravity (Water = 1):		UEL.			
Vapor Pressure (vs. Air or					
mm Hg):					
Vapor Density (vs. Air = 1):					
Evaporation Rate:					
Solubility in Water:	-20%				
pH:	> 12.5 @ 1%				
Percent Volatile:					
	10. Stability an	d Reactivity	/		
Stability:	Unstable [] Stable [X]				
Conditions To Avoid - Instability:	Exposure to moist air or water.				
Incompatibility - Materials To Avoid:	Acids, Hydrogen peroxide, Alu halogens.	minum, Zinc, gela	atin, leather, fla	ammable liqu	uids, organic
Hazardous Decomposition Or	r Carbon monoxide, Carbon dio	kide, Toxic fumes	of sodium oxid	de, Carbon c	oxides.
Byproducts:					
Possibility of Hazardous Reactions:	Will occur [] Will not occ	ur [X]			
Conditions To Avoid -					
Hazardous Reactions:					
	11. Toxicologica	al Informatic	n		
Toxicological Information:					
Carcinogenicity/Other	CAS# 1310-73-2: Not				
Information:	listed by ACGIH, IARC, NTP, o	or CA Prop 65.			
CAS # Hazardous Com	ponents (Chemical Name)	NTP	IARC	ACGIH	OSHA
1310-73-2 Sodium hydroxide	e {Caustic soda; Lye solution}	n.a.	n.a.	n.a.	n.a.
	12. Ecological	Information			
General Ecological Information:	Environmental: Not regulated.				
	13. Disposal Co	nsideration	S		
Waste Disposal Method:	Chemical waste generators mu as a hazardous waste. US EPA in 40 CFR Parts 261. Additiona hazardous waste regulations to Observe all federal, state, and	A guidelines for th ally, waste genera o ensure complete	e classificatior ators must con and accurate	n determinati sult state an classificatio	ion are listed d local

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name:	Corrosive solid,	basic, inorganic, n.o.s.	
DOT Hazard Class:	8	CORROSIVE	
UN/NA Number:	UN3262	Packing Group:	Π



15. Regulatory Information

EPA SARA (S	uperfund Amendi	ments and Reauthorization Act	of 1986) Lists		1 40 19	
		nponents (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)	
1310-73-2	Sodium hydroxid	de {Caustic soda; Lye solution}	No	Yes 1000 LB	No	
CAS # Hazardous Components (Chemical Name)		Other US EPA or	State Lists			
1310-73-2 Sodium hydroxide {Caustic soda; Lye solution}			CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No			
		16. Other I	nformation			
Revision Date: 06/09/2016						
Preparer Name: Regulatory Affairs						
Additional In	formation Abou	t				
This Product: The informat		The information contained in	this Material Safe	ty Data Sheet is pro	ovided pursuant to	
Company Policy or		current OSHA regulations to convey information concerning the hazardous nature of the				
Disclaimer:		named product. The informa available at the time of prepa exposure situations expected present greater or lesser haz the control of the manufactur on the product label be read	aration and in light d from the intended card exposure und rer. Therefore it is i	of the most reason d use of this produc er other circumstan mperative that all c	able foreseeable et. The material(s) may lices that are beyond	