# **SAFETY DATA SHEET**



Date of issue/Date of revision 4 May 2025

Version 4.03

### **Section 1. Identification**

Product name : 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR

SEMI-GLOSS NEUTRAL BASE

Product code : 00441676

Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against :

: Not applicable.

Manufacturer : The Pittsburgh Paints Co.

400 Bertha Lamme Drive, Cranberry Township, PA 16066

**Emergency telephone** 

number

: 7-833-477-1553 (U.S. and Canada)

SETIQ Interior de la República: 800-00-214-00 (México)

Technical Phone Number : 1-800-441-9695 (U.S. and México)

1-800-387-2253 (Canada)

## Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 32.5%

(oral), 32.5% (dermal), 32.5% (inhalation)

**GHS** label elements

Signal word : No signal word.

**Hazard statements**: No known significant effects or critical hazards.

**Precautionary statements** 

Prevention: Not applicable.Response: Not applicable.Storage: Not applicable.

United States Page: 1/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

### Section 2. Hazards identification

Disposal : Not applicable.

Supplemental label elements

: Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.

**Hazards not otherwise** 

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

**Product name** 

: 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

| Ingredient name                        | %           | CAS number |
|--|-------------|------------|
| 1-(2-butoxy-1-methylethoxy)propan-2-ol | ≥1.0 - ≤5.0 | 29911-28-2 |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label. Keep

person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

United States Page: 2/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

### Section 4. First aid measures

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

United States Page: 3/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

### Section 6. Accidental release measures

### Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures Special precautions

- : Put on appropriate personal protective equipment (see Section 8).
- : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, : including any incompatibilities

: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits

| Ingredient name |  | Ехр  | Exposure limits                    |  |  |
|-----------------|--|------|------------------------------------|--|--|
| 1-(2-b          | 1-(2-butoxy-1-methylethoxy)propan-2-ol                             |      | e.                                 |  |  |
|                 | Key to abbreviations   |      |                                    |  |  |
| Α               | = Acceptable Maximum Peak  | S    | = Potential skin absorption        |  |  |
| ACGIH           | = American Conference of Governmental Industrial Hygienists.       | SR   | = Respiratory sensitization        |  |  |
| С               | = Ceiling Limit  | SS   | = Skin sensitization               |  |  |
| F               | = Fume   | STEL | = Short term Exposure limit values |  |  |
| IPEL            | = Internal Permissible Exposure Limit                              | TD   | = Total dust                       |  |  |
| OSHA            | Occupational Safety and Health Administration.                     | TLV  | = Threshold Limit Value            |  |  |
| R               | = Respirable   | TWA  | = Time Weighted Average            |  |  |
| Z               | = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances |      | S S                                |  |  |

#### Consult local authorities for acceptable exposure limits.

United States Page: 4/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-**GLOSS NEUTRAL BASE** 

### Section 8. Exposure controls/personal protection

procedures

Recommended monitoring: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Safety glasses with side shields.

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid.

Color : Not available. : Characteristic. Odor **Odor threshold** Not available. : Not available. pН **Melting point** : Not available. : >37.78°C (>100°F) **Boiling point** 

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

**Auto-ignition temperature** : Not available.

> **United States** Page: 5/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

### Section 9. Physical and chemical properties

**Decomposition temperature** : Not available.

Flammability : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Evaporation rate : Not available.

Vapor pressure : Not available.

Vapor density : Not available.

Relative density : 1.05 Density (lbs / gal) : 8.76

Solubility(ies) Media Result

Partition coefficient: n-

octanol/water

: Not applicable.

cold water

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Soluble

% Solid. (w/w) : 38.044

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** 

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials:

carbon oxides

United States Page: 6/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

# **Section 11. Toxicological information**

### **Information on toxicological effects**

#### **Acute toxicity**

| Product/ingredient name                 | Result                          | Species | Dose                     | Exposure |
|---|---------------------------------|---------|--------------------------|----------|
| 1-(2-butoxy-1-methylethoxy) propan-2-ol | LC50 Inhalation Dusts and mists | Rat     | 5.4 mg/l                 | 4 hours  |
|   | LD50 Dermal<br>LD50 Oral        |         | >2000 mg/kg<br>4.05 g/kg | -        |

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which may cause damage to the following organs: liver, upper

respiratory tract.

**Aspiration hazard** 

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.

United States Page: 7/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

### **Section 11. Toxicological information**

**Ingestion**: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary**: There are no data available on the mixture itself. Contains isothiazolinones. May cause

allergic reaction. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of

exposure and eye contact.

**Short term exposure** 

Potential immediate : There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

**Potential immediate**: There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

| Product/ingredient name  | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | (gases) | (vapors) | Inhalation<br>(dusts and<br>mists) (mg/<br>l) |
|--|------------------|-------------------|---------|----------|---|
| 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE 1-(2-butoxy-1-methylethoxy)propan-2-ol | 194212.6         | 119884.3          | N/A     | N/A      | N/A   |
|  | 4050             | 2500              | N/A     | N/A      | 5.4   |

United States Page: 8/11

**Product code 00441676** 

Date of issue 4 May 2025

Version 4.03

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

# **Section 12. Ecological information**

#### **Toxicity**

| Product/ingredient name                 | Result              | Species | Exposure |
|---|---------------------|---------|----------|
| 1-(2-butoxy-1-methylethoxy) propan-2-ol | Acute LC50 841 mg/l | Fish    | 96 hours |

### Persistence and degradability

| Product/ingredient name                    | Test              | Result     |                | Dose |         | Inoculum   |
|--|-------------------|------------|----------------|------|---------|------------|
| 1-(2-butoxy-1-methylethoxy) propan-2-ol    | OECD 302B         | 96 % - Rea | dily - 28 days | -    |         | -          |
| Product/ingredient name                    | Aquatic half-life |            | Photolysis     |      | Biodegi | radability |
| 1-(2-butoxy-1-methylethoxy)<br>propan-2-ol | -                 |            | -              |      | Readily |            |

#### **Bioaccumulative potential**

| Product/ingredient name LogPo                 | Pow | BCF | Potential |
|---|-----|-----|-----------|
| 1-(2-butoxy-1-methylethoxy) 1.523 propan-2-ol | 3   | -   | Low       |

#### **Mobility in soil**

Soil/Water partition coefficient

: Not available.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

United States Page: 9/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

# 14. Transport information

|                              | DOT             | IMDG            | IATA            |
|------------------------------|-----------------|-----------------|-----------------|
| UN number                    | Not regulated.  | Not regulated.  | Not regulated.  |
| UN proper shipping name      | -               | -               | -               |
| Transport hazard class (es)  | -               | -               | -               |
| Packing group                | -               | -               | -               |
| <b>Environmental hazards</b> | No.             | No.             | No.             |
| Marine pollutant substances  | Not applicable. | Not applicable. | Not applicable. |

#### **Additional information**

DOT : None identified.IMDG : None identified.IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# Section 15. Regulatory information

#### **United States**

United States inventory (TSCA 8b): All components are active or exempted.

TSCA 5(a)2 - Proposed significant new use rules:

3(2H)-Isothiazolone, 2-methyl- Listed P-96-1250

**SARA 302/304** 

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

**SARA 311/312** 

Classification : Not applicable.

Composition/information on ingredients

| Name                                    | %           | Classification               |
|---|-------------|------------------------------|
| 1-(2-butoxy-1-methylethoxy) propan-2-ol | ≥1.0 - ≤5.0 | EYE IRRITATION - Category 2A |

United States Page: 10/11

Product name 39-4200 PITTSBURGH PAINTS AND STAINS FAST DRY INTERIOR/EXTERIOR SEMI-GLOSS NEUTRAL BASE

# **Section 15. Regulatory information**

### Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

: EHS

Date of previous issue : 2/19/2025

Organization that prepared

**Key to abbreviations** 

the SDS

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

### ▼ Indicates information that has changed from previously issued version.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 11/11