

# SAFETY DATA SHEET

Version 6.8 Revision Date 03/02/2024 Print Date 07/13/2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifiers

Product name : Formalin solution, neutral buffered, 10%

Product Number : HT501128 Brand : Sigma

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

#### 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 4), H227 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332 Skin sensitization (Category 1), H317 Germ cell mutagenicity (Category 2), H341

Sigma - HT501128

Page 1 of 16



Carcinogenicity (Category 1B), H350 Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal Word	Danger
-------------	--------

Hazard Statements

H227 Combustible liquid.

H302 + H332 Harmful if swallowed or if inhaled.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H350 May cause cancer. H402 Harmful to aquatic life.

**Precautionary Statements** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smokina.

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the

workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel

unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

Sigma - HT501128

Page 2 of 16



# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Component		Classification	Concentration
formaldehyde			
CAS-No. EC-No. Index-No. Registration number	50-00-0 200-001-8 605-001-00-5 01-2119488953-20- XXXX	Flam. Liq. 4; Acute Tox. 3; Acute Tox. 2; Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; Skin Sens. 1; Muta. 2; Carc. 1B; STOT SE 3; Aquatic Acute 2; H227, H301, H330, H311, H314, H318, H317, H341, H350, H335, H401 Concentration limits: >= 25 %: Skin Corr. 1B, H314; 5 - < 25 %: Eye Irrit. 2, H319; >= 5 %: STOT SE 3, H335; >= 0.2 %: Skin Sens. 1, H317; 5 - < 25 %: Skin Irrit. 2, H315; >= 25 %: Skin Corr. 1B, H314; 5 - < 25 %: Skin Irrit. 2, H315; > < 25 %: Skin Irrit. 2, H315; 5 - < 25 %: Eye Irrit. 2, H319; >= 5 %: STOT SE 3, H335; >= 0.2 %: Skin Sens. 1, H317;	>= 1 - < 5 %
Methanol			
CAS-No. EC-No. Index-No. Registration number	67-56-1 200-659-6 603-001-00-X 01-2119433307-44- XXXX	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	>= 1 - < 3 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first-aid measures

## **General advice**

Show this material safety data sheet to the doctor in attendance.

# If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

Sigma - HT501128

Page 3 of 16



#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed No data available

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

# 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Not combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Ambient fire may liberate hazardous vapours.

## 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

## **5.4** Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Sigma - HT501128

Page 4 of 16



## 6.2 Environmental precautions

Do not let product enter drains.

# 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

## 6.4 Reference to other sections

For disposal see section 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

# Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

# Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

# **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

# Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

#### Storage class

Storage class (TRGS 510): 6.1C: Combustible, acute toxic Cat.3 / toxic compounds or compounds which causing chronic effects

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Ingredients with workplace control parameters

Tilgi calcillo With	woi kpiace	control par	anneters	
Component	CAS-No.	Value	Control parameters	Basis
formaldehyde	50-00-0	TWA	0.1 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	, ,	nsitization sensitization human carcinog	en

Sigma - HT501128



Page 5 of 16

		STEL	0.3 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Dermal Se	ensitization	•		
			y sensitization			
		Confirmed human carcinogen				
		TWA	TWA 0.016 ppm USA. NIOSH Recomme Exposure Limits			
		Potential Occupational Carcinogen				
		С	0.1 ppm	USA. NIOSH Recommended Exposure Limits		
		Potential C	Occupational Car	rcinogen		
		PEL	0.75 ppm	OSHA Specifically Regulated Chemicals/Carcinogens		
		OSHA spec	cifically regulate	ed carcinogen		
		STEL	2 ppm	OSHA Specifically Regulated Chemicals/Carcinogens		
		OSHA spec	cifically regulate	ed carcinogen		
		PEL	0.75 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		STEL	2 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		TWA	0.016 ppm	USA. NIOSH Recommended Exposure Limits		
		Potential C	Occupational Ca			
		С	0.1 ppm	USA. NIOSH Recommended Exposure Limits		
		Potential C	Occupational Ca	rcinogen		
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Danger of	cutaneous abso	orption		
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Danger of	cutaneous abso			
		ST	250 ppm 325 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential f	or dermal absor			
		TWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential f	or dermal absor			

Sigma - HT501128 Page 6 of 16



TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		·

**Biological occupational exposure limits** 

biological occupational exposure inints					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (	(As soon as	possible after ex	oosure ceases)

# 8.2 Exposure controls

# **Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

## Personal protective equipment

# Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm



Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

protective clothing

# Respiratory protection

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented. required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

# **Control of environmental exposure**

Do not let product enter drains.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor No data available

c) Odor Threshold No data availabled) pH 6.5 - 7.5 at 10%

e) Melting No data available point/freezing point

f) Initial boiling point 100 °C 212 °F at 1,013 hPa

and boiling range

g) Flash point
h) Evaporation rate
i) Flammability (solid, No data available)

gas)

j) Upper/lower Upper explosion limit: 70 %(V) flammability or

explosive limits Lower explosion limit: 7 %(V)

Sigma - HT501128

Millipore SigMa k) Vapor pressure 53 hPa at 39 °C (102 °F)

I) Vapor density No data available

m) Density 1.080 g/cm3

Relative density No data available

n) Water solubility completely misciblesoluble

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition Not applicable

temperature

q) Decomposition No data available

temperature

r) Viscosity No data available

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

# 9.2 Other safety information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

## 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

# 10.3 Possibility of hazardous reactions

Violent reactions possible with:

The generally known reaction partners of water.

## 10.4 Conditions to avoid

Strong heating.

# 10.5 Incompatible materials

Strong bases, Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Amines, Strong acids, Acid chlorides, Acid anhydrides, Reducing agents, Peroxides, Isocyanates, Phenol, Aniline

## 10.6 Hazardous decomposition products

In the event of fire: see section 5



#### **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Mixture**

# **Acute toxicity**

Oral: No data available

Inhalation: No data available
Dermal: No data available

Skin corrosion/irritation

No data available

# Serious eye damage/eye irritation

No data available

# Respiratory or skin sensitization

Mixture may cause an allergic skin reaction.

# Germ cell mutagenicity

Evidence of genetic defects.

# Carcinogenicity

Possible carcinogen.

IARC: 1 - Group 1: Carcinogenic to humans (formaldehyde)

NTP: Known - Known to be human carcinogen (formaldehyde)

OSHA: OSHA specifically regulated carcinogen (formaldehyde)

# Reproductive toxicity

No data available

## Specific target organ toxicity - single exposure

No data available

# Specific target organ toxicity - repeated exposure

No data available

# **Aspiration hazard**

No data available

## 11.2 Additional Information

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, May cause convulsions. Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

Sigma - HT501128

Page 10 of 16



# **Components**

# formaldehyde

# **Acute toxicity**

LD50 Oral - Rat - 100 mg/kg

Remarks: (Lit.)

Acute toxicity estimate Inhalation - 4 h - 0.51 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Inhalation: Corrosive to respiratory system.

LD50 Dermal - Rabbit - 270 mg/kg

Remarks: (RTECS)

# Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 20 h (OECD Test Guideline 404)

# Serious eye damage/eye irritation

Remarks: Causes serious eye damage.

# Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: positive

(OECD Test Guideline 406)

# Germ cell mutagenicity

Suspected of causing genetic defects.

# Carcinogenicity

Presumed to have carcinogenic potential for humans

## Reproductive toxicity

No data available

## Specific target organ toxicity - single exposure

May cause respiratory irritation.

## Specific target organ toxicity - repeated exposure

# **Aspiration hazard**

No data available

#### **Methanol**

# **Acute toxicity**

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Symptoms: Nausea, Vomiting



Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

# Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

# Serious eye damage/eye irritation

Eves - Rabbit

Result: No eye irritation

Remarks: (ECHA)

# Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

# **Germ cell mutagenicity**

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

#### Carcinogenicity

Did not show carcinogenic effects in animal experiments.

## Reproductive toxicity

Based on available data the classification criteria are not met.

# Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - Nausea, Vomiting

Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

# Specific target organ toxicity - repeated exposure

No data available

#### **Aspiration hazard**

No data available

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Mixture**

No data available

# 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

# 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

No data available

# **Components**

# formaldehyde

Toxicity to fish static test LC50 - Morone saxatilis - 6.7 mg/l - 96 h

Remarks: (ECHA)

Toxicity to daphnia

and other aquatic invertebrates

static test EC50 - Daphnia pulex (Water flea) - 5.8 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) -

4.89 mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - 19 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to daphnia

semi-static test NOEC - Daphnia magna (Water flea) - >= 6.4 mg/l - 21 d

and other aquatic

invertebrates (Chronic (OECD Test Guideline 211)

toxicity)

#### Methanol

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) -

15,400.0 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

semi-static test EC50 - Daphnia magna (Water flea) - 18,260

and other aquatic mg/l - 96 h

Sigma - HT501128

**AilliPDR**@

Page 13 of 16

invertebrates (OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green

algae) - ca. 22,000.0 mg/l - 96 h

(OECD Test Guideline 201)

Toxicity to bacteria  $\,$  static test IC50 - activated sludge -  $> 1,000 \,$  mg/l  $\,$  - 3 h

(OECD Test Guideline 209)

Toxicity to NOEC - Oryzias latipes (Orange-red killifish) - 7,900 mg/l - 200

fish(Chronic toxicity) h

Remarks: (External MSDS)

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

# **SECTION 14: Transport information**

DOT (US)

NA-Number: 1993 Class: NONE Packing group: III

Proper shipping name: Combustible liquid, n.o.s. (formaldehyde, Methanol)

Reportable Quantity (RQ): 2500 lbs

Poison Inhalation Hazard: No

**IMDG** 

Not dangerous goods

**IATA** 

Not dangerous goods

# **SECTION 15: Regulatory information**

# **SARA 302 Components**

formaldehyde CAS-No. Revision Date 50-00-0 2008-11-03

Sigma - HT501128 Page 14 of 16

Millipore Sigma

## **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

formaldehyde	CAS-No. 50-00-0	Revision Date 2008-11-03
Methanol	67-56-1	2007-07-01

# SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

## **Massachusetts Right To Know Components**

water	CAS-No. 7732-18-5	Revision Date
formaldehyde	50-00-0	2008-11-03
Methanol	67-56-1	2007-07-01
Pennsylvania Right To Know Components formaldehyde	CAS-No. 50-00-0	Revision Date 2008-11-03
Methanol	67-56-1	2007-07-01
disodium hydrogen orthophosphate	7558-79-4	1993-04-24
California Prop. 65 Components , which is/are known to the State of California to cause cancer, andformaldehyde	CAS-No. 50-00-0	Revision Date 2007-09-28
, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to	CAS-No. 67-56-1	Revision Date 2012-03-16

## SECTION 16: Other information

www.P65Warnings.ca.gov.Methanol

## **Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact

Sigma - HT501128 Page 15 of 16



with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.8 Revision Date: 03/02/2024 Print Date: 07/13/2024

