

# SAFETY DATA SHEET

Version 1.0 Revision Date 11/06/2019 Print Date 11/21/2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifiers**

Product name	: Ergosterol		
Product Number	: 47130-U		
Brand	: Supelco		
Index-No.	: 602-006-00-4		

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

### **1.3** Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765
Fax	: +1 800 325-5052

### **1.4 Emergency telephone number**

Emergency Phone # : +1-703-527-3887

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure (Category 1), Liver, Kidney, H372 Short-term (acute) aquatic hazard (Category 3), H402 Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram

Supelco - 47130-U







Signal word	Danger
Hazard statement(s) H302 H315 H319 H331 H336 H351 H361 H372	Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statement(s) P201 P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P260 P264 P270 P271 P273 P280	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face
P301 + P312 + P330	protection. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P302 + P352 P304 + P340 + P311	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 P332 + P313 P337 + P313 P362 P403 + P233 P405 P501	IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **SECTION 3: Composition/information on ingredients**

3.2	<b>Mixtures</b> Synonyms	:	Provitamin D2 3β-Hydroxy-5,7,22-ergostatriene 5,7,22-Ergostatrien-3β-ol
	Formula Molecular weight		C <sub>28</sub> H <sub>44</sub> O 396.65 g/mol

Supelco - 47130-U

Page 2 of 11



Component		Classification	Concentration
Chloroform			
CAS-No. EC-No. Index-No. Registration number	67-66-3 200-663-8 602-006-00-4 01-2119486657-20- XXXX	Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; Repr. 2; STOT SE 3; STOT RE 1; Aquatic Acute 3; Aquatic Chronic 3; H302, H331, H315, H319, H351, H361, H336, H372, H402, H412 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %
Ergosterol			
CAS-No. EC-No.	57-87-4 200-352-7	Aquatic Chronic 4; H413	>= 1 - < 5 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# SECTION 4: First aid measures

# 4.1 Description of first aid measures

### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

Supelco - 47130-U



### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

# **Suitable extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- **5.2** Special hazards arising from the substance or mixture Carbon oxides, Hydrogen chloride gas
- **5.3 Advice for firefighters** Wear self-contained breathing apparatus for firefighting if necessary.
- **5.4 Further information** No data available

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.
- **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
- **6.3 Methods and materials for containment and cleaning up** Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.
- **6.4** Reference to other sections For disposal see section 13.

### SECTION 7: Handling and storage

### **7.1 Precautions for safe handling** Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

**7.2** Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C Storage class (TRGS 510): 6.1C: Combustible, acute toxic Cat.3 / toxic compounds or compounds which causing chronic effects

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Supelco - 47130-U

Page 4 of 11



# SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components with workplace control parameters						
Component	CAS-No.	Value	Control parameters	Basis		
Chloroform	67-66-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Central Nervous System impairment Liver damage Embryo/fetal damage Confirmed animal carcinogen with unknown relevance to humans				
		ST	2 ppm 9.78 mg/m3	USA. NIOSH Recommended Exposure Limits		
		Potential Occupational Carcinogen See Appendix A				
		С	50 ppm 240 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants		
		The value in mg/m3 is approximate. Ceiling limit is to be determined from breathing-zone air samples.				
		PEL	2 ppm 9.78 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		

### **Components with workplace control parameters**

### 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole

Supelco - 47130-U

Page 5 of 11



means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless			
b)	Odour	No data available			
c)	Odour Threshold	No data available			
d)	рН	No data available			
e)	Melting point/freezing point	Melting point/range: 156 - 158 °C (313 - 316 °F) - lit.			
f)	Initial boiling point and boiling range	61 °C 142 °F at 1013 hPa			
g)	Flash point	()No data available			
h)	Evaporation rate	11.6			
i)	Flammability (solid, gas)	No data available			
j)	Upper/lower flammability or explosive limits	No data available			
k)	Vapour pressure	213 hPa at 25 °C (77 °F)			
I)	Vapour density	No data available			
m)	Relative density	1.490 g/cm3			
n)	Water solubility	No data available			
o)	Partition coefficient: n-octanol/water	log Pow: 1.97			
p)	Auto-ignition temperature	No data available			
q)	Decomposition temperature	No data available			
r)	Viscosity	No data available			
s)	Explosive properties	No data available			
t)	Oxidizing properties	No data available			
Other safety information					
	Curfo co toncion	27.1  mN/m at 20.0.9C (69.0.9C)			

Surface tension

27.1 mN/m at 20.0 °C (68.0 °F)

Supelco - 47130-U

9.2

Page 6 of 11



### **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No data available
- **10.2 Chemical stability** Stable under recommended storage conditions.
- 10.3 Possibility of hazardous reactions No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** Strong bases, Strong oxidizing agents, acids, Lithium, Sodium/sodium oxides, Magnesium
- 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

# SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50 Oral - Rat - male - 908 mg/kg (OECD Test Guideline 401) LOEC Inhalation - Rat - male - 6 h - 500 ppm Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Dermal: No data available No data available

### Skin corrosion/irritation

Skin - Rabbit Result: Irritating to skin. - 24 h Remarks: (ECHA) Skin - Rabbit Result: slight irritation Remarks: (IUCLID) Drying-out effect resulting in rough and chapped skin.

### Serious eye damage/eye irritation

Eyes - Rabbit Result: Irritating to eyes. Remarks: (ECHA)

### Respiratory or skin sensitisation

Maximisation Test - Guinea pig Result: negative (Regulation (EC) No. 440/2008, Annex, B.6)

# Germ cell mutagenicity

reverse mutation assay

Supelco - 47130-U

Page 7 of 11



Salmonella typhimurium Result: negative reverse mutation assay Escherichia coli Result: negative OECD Test Guideline 474 Rat - male and female - Bone marrow Result: negative OECD Test Guideline 486 Rat - male - Other cell types Result: negative

#### Carcinogenicity

Suspected of causing cancer.

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Chloroform)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

Suspected of damaging the unborn child.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. - Liver, Kidney

### Aspiration hazard

No data available

# **Additional Information**

RTECS: Not available

Vomiting, Cough, irritant effects, Shortness of breath, respiratory arrest, narcosis, Dizziness, Nausea, agitation, spasms, inebriation, Headache, Stomach/intestinal disorders, ataxia (impaired locomotor coordination), cardiovascular disorders Drying-out effect resulting in rough and chapped skin. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **SECTION 12: Ecological information**

#### **12.1 Toxicity**

No data available

Toxicity to fish

flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 18.2 mg/l - 96 h Remarks: (ECHA)

Supelco - 47130-U

Page 8 of 11



Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 79 mg/l  - 48 h Remarks: (ECHA)
Toxicity to algae	static test ErC50 - Chlamydomonas reinhardtii (green algae) - 13.3

mg/l - 72 h Remarks: (ECHA)

### 12.2 Persistence and degradability

No data available

Theoretical oxygen Remarks: No data available demand

**12.3 Bioaccumulative potential** No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### **12.6 Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects. No data available

### **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

### **SECTION 14: Transport information**

#### DOT (US)

UN number: 1888 Class: 6.1 Packing group: III Proper shipping name: ChloroformSOLUTION

Reportable Quantity (RQ): 10 lbs Reportable Quantity (RQ): 10 lbs Poison Inhalation Hazard: No

#### IMDG

UN number: 1888 Class: 6.1 Packing group: III Proper shipping name: CHLOROFORMSOLUTION EMS-No: F-A, S-A

Supelco - 47130-U

Page 9 of 11



### IATA UN number: 1888 Class: 6.1 Packing group: III Proper shipping name: ChloroformSOLUTION

SEC	SECTION 15: Regulatory information					
	SARA 302 Components					
	The following components are subject to reporting level	s established by S	ARA Title III,			
	Section 302:		Dovision Data			
	Chloroform	CAS-No. 67-66-3	Revision Date 2008-11-03			
		07 00 5	2000 11 05			
	SADA 212 Components					
	SARA 313 Components The following components are subject to reporting level	s established by S	ARA Title III			
	Section 313:	s coublished by c				
		CAS-No.	Revision Date			
	Chloroform	67-66-3	2008-11-03			
	SARA 311/312 Hazards					
	Acute Health Hazard, Chronic Health Hazard					
	: Reportable Quantity D022 lbs					
	Reportable Quantity D022 lbs					
	Maaaaahuaatta Diabt Ta Kaawa Campananta					
	Massachusetts Right To Know Components	CAS-No.	Revision Date			
	Chloroform	67-66-3	2008-11-03			
	No componente ave subject to the Macanchusette Dicht	to Know Act				
	No components are subject to the Massachusetts Right	LO KHOW ACL.				
	Pennsylvania Right To Know Components		<b>D</b> · · · <b>D</b> ·			
	Chloroform	CAS-No. 67-66-3	Revision Date 2008-11-03			
		07-00-5	2008-11-05			
	Chloroform	CAS-No.	Revision Date			
		67-66-3	2008-11-03			
	New Jersey Right To Know Components					
	Chloroform	CAS-No.	Revision Date			
		67-66-3	2008-11-03			
	Ergosterol	57-87-4				

Supelco - 47130-U

Page 10 of 11

Millipore Sigma

# **SECTION 16: Other information**

#### Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 1.0

Revision Date: 11/06/2019

Print Date: 11/21/2019

Supelco - 47130-U

Page 11 of 11

