

SAFETY DATA SHEET

Version 6.4
Revision Date 09/15/2021
Print Date 01/15/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Isobutyraldehyde

Product Number : 240788
Brand : Aldrich
CAS-No. : 78-84-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225
Eye irritation (Category 2A), H319
Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Danger

Hazard statement(s)
H225 : Highly flammable liquid and vapor.

H319	Causes serious eye irritation.
H402	Harmful to aquatic life.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Stench.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	: 2-Methylpropionaldehyde
Formula	: C ₄ H ₈ O
Molecular weight	: 72.11 g/mol
CAS-No.	: 78-84-2
EC-No.	: 201-149-6

Component	Classification	Concentration
isobutyraldehyde		
	Flam. Liq. 2; Eye Irrit. 2A; Aquatic Acute 3; H225, H319, H402	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Advice on protection against fire and explosion

Use explosion-proof equipment. **Advice on protection against fire and explosion**
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage stability

Recommended storage temperature
2 - 8 °C

Stench. Air sensitive. Store under inert gas.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
isobutyraldehyde	78-84-2	TWA	25 ppm	USA. Workplace Environmental Exposure Levels (WEEL)

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 30 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: clear, liquid Color: colorless	
b) Odor	unpleasant	
c) Odor Threshold	No data available	
d) pH	No data available	
e) Melting point/freezing point	Melting point/range: -65 °C (-85 °F) - lit.	
f) Initial boiling point and boiling range	63 °C 145 °F - lit.	
g) Flash point	-24 °C (-11 °F) - closed cup - DIN 51755 Part 1	
h) Evaporation rate	No data available	
i) Flammability (solid, gas)	No data available	
j) Upper/lower flammability or explosive limits	Upper explosion limit: 11.0 %(V) Lower explosion limit: 1.6 %(V)	
k) Vapor pressure	88 hPa at 4.4 °C (39.9 °F) 189 hPa at 20 °C(68 °F) 640 hPa at 50 °C(122 °F)	
l) Vapor density	2.49 - (Air = 1.0)	
m) Density	0.79 g/cm ³ at 25 °C (77 °F) - lit.	
	Relative density	No data available
n) Water solubility	60 g/l at 25 °C (77 °F) - OECD Test Guideline 105	
o) Partition coefficient: n-octanol/water	log Pow: 0.77 at 25 °C (77 °F) - Bioaccumulation is not expected.	
p) Autoignition temperature	180 °C (356 °F) at 1,013.25 hPa - ASTM E-659	
q) Decomposition temperature	No data available	
r) Viscosity	No data available	
s) Explosive properties	No data available	
t) Oxidizing properties	none	

9.2 Other safety information

Relative vapor density	2.49 - (Air = 1.0)
------------------------	--------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

Aldrich - 240788

Page 6 of 10

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Oxidizing agents, Strong acids, Strong bases, Strong reducing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - 3,730 mg/kg

(OECD Test Guideline 401)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

LC50 Inhalation - Rat - male - 4 h - > 23.6 mg/l

(OECD Test Guideline 403)

Symptoms: Inhalation may lead to the formation of oedemas in the respiratory tract., Symptoms may be delayed.

LD50 Dermal - Rabbit - male - 5,583 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

After long-term exposure to the chemical: Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation. - 24 h

(OECD Test Guideline 405)

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: NQ4025000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Further hazardous properties cannot be excluded but unlikely when the product is handled appropriately.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish	static test LC50 - Pimephales promelas (fathead minnow) - 23 mg/l - 96 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 277 mg/l - 48 h (Regulation (EC) No. 440/2008, Annex, C.2) Remarks: (above the solubility limit in the test medium)
Toxicity to algae	static test ErC50 - Desmodesmus subspicatus (green algae) - 83.7 mg/l - 72 h (DIN 38412) Remarks: (above the solubility limit in the test medium)
Toxicity to bacteria	static test NOEC - activated sludge - 100 mg/l - 14 Days Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 14 d
Result: 80 - 90 % - Readily biodegradable.
(OECD Test Guideline 301C)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 2045 Class: 3 Packing group: II

Proper shipping name: Isobutyl aldehyde

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 2045 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ISOBUTYL ALDEHYDE

IATA

UN number: 2045 Class: 3 Packing group: II

Proper shipping name: Isobutyl aldehyde

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
isobutyraldehyde	78-84-2	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

isobutyraldehyde

CAS-No.
78-84-2

Revision Date
2007-07-01

SECTION 16: Other information

Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4

Revision Date: 09/15/2021

Print Date: 01/15/2022