

MSDS Material Safety Data SheetFrom: Mallinckrodt Baker, Inc.
222 Red School Lane
Phillipsburg, NJ 0886524 Hour Emergency Telephone: 908-859-2151
CHEMTREC: 1-800-424-9300National Response in Canada
CANUTEC: 619-996-6666Outside U.S. and Canada
Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.

MANGANESE DIOXIDE

1. Product Identification

Synonyms: Manganese black; Manganese peroxide; Manganese (VI) oxide; Cement black**CAS No.:** 1313-13-9**Molecular Weight:** 86.94**Chemical Formula:** MnO₂**Product Codes:**

J.T. Baker: 5308, 8392

Mallinckrodt: 4572

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Manganese Dioxide	1313-13-9	> 98%	Yes

3. Hazards Identification

Emergency Overview

DANGER! OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. HARMFUL IF SWALLOWED OR INHALED. AFFECTS LUNGS, CENTRAL NERVOUS SYSTEM, BLOOD AND KIDNEYS. MAY CAUSE IRRITATION TO EYES AND RESPIRATORY TRACT.**SAF-T-DATA^(tm)** Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Life)

Flammability Rating: 0 - None

Reactivity Rating: 3 - Severe (Oxidizer)

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: Yellow (Reactive)

Potential Health Effects

Inhalation:

Inhalation can cause a flu-like illness (metal fume fever). This 24- to 48-hour illness is characterized by chills, fever, aching muscles, dryness in the mouth and throat and headache. May irritate the respiratory tract. May increase the incidence of upper respiratory infections (pneumonia). Absorption of inorganic manganese salts through the lungs is poor but may occur in chronic poisoning.

Ingestion:

May cause abdominal pain and nausea. Although they are poorly absorbed through the intestines, inorganic manganese salts may produce hypoglycemia and decreased calcium blood levels should absorption occur.

Skin Contact:

No adverse effects expected.

Eye Contact:

May cause irritation, redness and pain.

Chronic Exposure:

Chronic manganese poisoning can result from excessive inhalation and ingestion exposure and involves impairment of the central nervous system. Early symptoms include sluggishness, sleepiness, and weakness in the legs. Advanced cases have shown fixed facial expression, emotional disturbances, spastic gait, and falling. Illness closely resembles Parkinson's Disease. Kidney effects, blood changes and manganese psychosis also may occur as a result of chronic exposure. Chronic inhalation exposure can cause lung damage.

Aggravation of Pre-existing Conditions:

Persons with impaired respiratory function, psychiatric or neurological disturbances, and nutritional deficiencies may be more susceptible to the effect of this substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact:

Not expected to require first aid measures. Wash exposed area with soap and water. Get medical advice if irritation develops.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

5. Fire Fighting Measures

Fire:

Not combustible, but substance is a strong oxidizer and its heat of reaction with reducing agents or combustibles may cause ignition. Increases the flammability of any combustible material.

Explosion:

Contact with oxidizable substances may cause extremely violent combustion.

Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. Keep combustibles (wood, paper, oil, etc.) away from spilled material. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage and moisture. Isolate from any source of heat or ignition. Avoid storage on wood floors. Separate from incompatibles, combustibles, organic or other readily oxidizable materials. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

- OSHA Permissible Exposure Limit (PEL):

5 mg/m³ Ceiling for manganese compounds as Mn

- ACGIH Threshold Limit Value (TLV):

0.2 mg/m³ (TWA) for manganese, elemental and inorganic compounds as Mn

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear protective gloves and clean body-covering clothing.

Eye Protection:

Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

Other Control Measures:

Clothing contaminated with this material may be an increased fire hazard. Wash contaminated clothing as soon as possible.

9. Physical and Chemical Properties

Appearance:

Gray lumps or fine, black to brownish-black powder.

Odor:

Odorless.

Solubility:
Insoluble in water.
Specific Gravity:
5.0
pH:
No information found.
% Volatiles by volume @ 21C (70F):
0
Boiling Point:
Not applicable.
Melting Point:
535C (995F)
Vapor Density (Air=1):
No information found.
Vapor Pressure (mm Hg):
No information found.
Evaporation Rate (BuAc=1):
No information found.

10. Stability and Reactivity

Stability:
Stable under ordinary conditions of use and storage.
Hazardous Decomposition Products:
Toxic metal fumes may form when heated to decomposition.
Hazardous Polymerization:
Will not occur.
Incompatibilities:
Easily oxidizable materials, sulfur, sulfides, phosphids, hypophosphites, chlorates, peroxides, aluminum powder, rubidium acetylide, potassium azide, chlorine trifluoride. Reacts with hydrochloric acid to form corrosive chlorine gas. Heating or rubbing this material with organic materials can cause a fire hazard.
Conditions to Avoid:
Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Toxicological Data:
Manganese Dioxide: LD50 oral rat > 3478 mg/kg. Investigated as a reproductive effector.
Reproductive Toxicity:
For manganese metal:
May damage the reproductive system. Has shown teratogenic effects in laboratory animals.

Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Manganese Dioxide (1313-13-9)	No	No	None

12. Ecological Information

Environmental Fate:
No information found.
Environmental Toxicity:
No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Regulatory Information

Ingredient	-----\Chemical Inventory Status - Part 1\-----			
	TSCA	EC	Japan	Australia
Manganese Dioxide (1313-13-9)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----

Ingredient	--Canada--			
	Korea	DSL	NDSL	Phil.
Manganese Dioxide (1313-13-9)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----

Ingredient	-SARA 302-		-----SARA 313-----	
	RQ	TPQ	List	Chemical Catg.
Manganese Dioxide (1313-13-9)	No	No	No	Manganese co

-----\Federal, State & International Regulations - Part 2\-----

Ingredient	CERCLA	-RCRA-	-TSCA-
		261.33	8(d)
Manganese Dioxide (1313-13-9)	1	No	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
 SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No
 Reactivity: No (Pure / Solid)

Australian Hazchem Code: 1WE

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 1 Other: **Oxidizer**

Label Hazard Warning:

DANGER! OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. HARMFUL IF SWALLOWED OR INHALED. AFFECTS LUNGS, CENTRAL NERVOUS SYSTEM, BLOOD AND KIDNEYS. MAY CAUSE IRRITATION TO EYES AND RESPIRATORY TRACT.

Label Precautions:

- Keep from contact with clothing and other combustible materials.
- Store in a tightly closed container.
- Remove and wash contaminated clothing promptly.
- Avoid contact with eyes.
- Wash thoroughly after handling.
- Avoid breathing dust.
- Use only with adequate ventilation.

Label First Aid:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety
 Phone Number: (314) 654-1600 (U.S.A.)