

SAFETY DATA SHEET

1. Identification

Product identifier HEPTANES

Other means of identification

CAS number 64742-49-0

Recommended use General purpose solvent.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company Name Greenfield Global USA Inc.

Address 1101 Isaac Shelby Drive
Shelbyville, KY 40065
USA

Telephone 502.232.7600

Fax 502.633.6100

Company Name Greenfield Global USA Inc.

Address 58 Vale Road
Brookfield, CT 06804
USA

Telephone 203.740.3471

Fax 203.740.3481

Emergency phone number

USA CHEMTREC: 1.800.424.9300 (CCN 17213)

International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2

Health hazards Skin corrosion/irritation Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2

Hazardous to the aquatic environment, long-term hazard Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary statement**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

None.

3. Composition/information on ingredients**Substances**

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), hydrotreated light		64742-49-0	100

Additional components

Chemical name	CAS number	%
Heptane	142-82-5	30 - 45
3-Methylhexane	589-34-4	≤ 30
Methylcyclohexane	108-87-2	≤ 20
2-Methylhexane	591-76-4	≤ 15
3-Ethyl Pentane	617-78-7	≤ 5
2,3-Dimethyl Pentane	565-59-3	≤ 5
3,3-Dimethyl Pentane	562-49-2	≤ 1

Composition comments

All concentrations are in percent by weight unless otherwise indicated.

4. First-aid measures**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material	Type	Value
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m ³
		100 ppm
Additional components	Type	Value
Heptane (CAS 142-82-5)	PEL	2000 mg/m ³
		500 ppm
3-Methylhexane (CAS 589-34-4)	PEL	2000 mg/m ³
		500 ppm
Methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m ³
		500 ppm

US. ACGIH Threshold Limit Values

Additional components	Type	Value
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
3-Methylhexane (CAS 589-34-4)	STEL	500 ppm
	TWA	400 ppm
Methylcyclohexane (CAS 108-87-2)	TWA	400 ppm
2-Methylhexane (CAS 591-76-4)	STEL	500 ppm
	TWA	400 ppm
3-Ethyl Pentane (CAS 617-78-7)	STEL	500 ppm
	TWA	400 ppm

US. ACGIH Threshold Limit Values

Additional components	Type	Value
2,3-Dimethyl Pentane (CAS 565-59-3)	STEL	500 ppm
	TWA	400 ppm
3,3-Dimethyl Pentane (CAS 562-49-2)	STEL	500 ppm
	TWA	400 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m3
		100 ppm
Additional components	Type	Value
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
	TWA	350 mg/m3
3-Methylhexane (CAS 589-34-4)	Ceiling	85 ppm
		1800 mg/m3
	TWA	440 ppm
Methylcyclohexane (CAS 108-87-2)	TWA	350 mg/m3
		85 ppm
		1600 mg/m3
		400 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical goggles are recommended.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin protection**Other**

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Clear liquid.

Color

Colorless.

Odor	Slight.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	201.2 - 210.2 °F (94 - 99 °C) [ASTM D86]
Flash point	15.8 °F (-9.0 °C) [ASTM D-56]
Evaporation rate	5 (butyl acetate = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 %
Flammability limit - upper (%)	7 %
Vapor pressure	5 kPa Calculated (68 °F (20 °C))
Vapor density	3.5 at 101 kPa [In-house method]
Relative density	0.7 Calculated (at 15.6 °C)
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	> 4 Estimated
Auto-ignition temperature	509 °F (265 °C) Extrapolated
Decomposition temperature	Not available.
Viscosity	0.5 mm ² /s (104 °F (40 °C)) 0.6 mm ² /s (68 °F (20 °C))
Other information	
Coefficient of expansion	0.0009 per °C Calculated
Density	700.00 kg/m ³ Calculated (at 15.6 °C)
Explosive properties	Not explosive.
Molecular weight	101 g/mol
Oxidizing properties	Not oxidizing.
Pour point	-70.6 °F (-57 °C) [ASTM D5950]

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Incomplete combustion may generate carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.
Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.
Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) > 4, [Estimated]

Mobility in soil The product is insoluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1206
UN proper shipping name Heptanes

Transport hazard class(es)

Class 3
Subsidiary risk -
Label(s) 3

Packing group II

Environmental hazards

Marine pollutant Yes.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T4, TP1

Packaging exceptions 150

Packaging non bulk 202

Packaging bulk 242

IATA

UN number UN1206

UN proper shipping name Heptanes

Transport hazard class(es)

Class 3
Subsidiary risk -

Packing group II

Environmental hazards Yes.

ERG Code 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1206

UN proper shipping name HEPTANES

Transport hazard class(es)

Class 3
Subsidiary risk -

Packing group II

Environmental hazards

Marine pollutant Yes.

EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2,3-Dimethyl Pentane (CAS 565-59-3)	Listed.
2-Methylhexane (CAS 591-76-4)	Listed.
3,3-Dimethyl Pentane (CAS 562-49-2)	Listed.
3-Ethyl Pentane (CAS 617-78-7)	Listed.
3-Methylhexane (CAS 589-34-4)	Listed.
Heptane (CAS 142-82-5)	Listed.
Methylcyclohexane (CAS 108-87-2)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Toxic Substances Control Act (TSCA) This substance is on the TSCA 8(b) inventory and is designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Hazard not otherwise classified (HNOC)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

2,3-Dimethyl Pentane (CAS 565-59-3)
2-Methylhexane (CAS 591-76-4)
3-Methylhexane (CAS 589-34-4)
Heptane (CAS 142-82-5)
Methylcyclohexane (CAS 108-87-2)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

US. New Jersey Worker and Community Right-to-Know Act

2,3-Dimethyl Pentane (CAS 565-59-3)
3-Methylhexane (CAS 589-34-4)
Heptane (CAS 142-82-5)
Methylcyclohexane (CAS 108-87-2)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

US. Pennsylvania Worker and Community Right-to-Know Law

2,3-Dimethyl Pentane (CAS 565-59-3)
2-Methylhexane (CAS 591-76-4)
3,3-Dimethyl Pentane (CAS 562-49-2)
3-Ethyl Pentane (CAS 617-78-7)
3-Methylhexane (CAS 589-34-4)
Heptane (CAS 142-82-5)
Methylcyclohexane (CAS 108-87-2)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

US. Rhode Island RTK

3-Methylhexane (CAS 589-34-4)
Heptane (CAS 142-82-5)
Methylcyclohexane (CAS 108-87-2)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Heptane (CAS 142-82-5)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes

HEPTANES

947256 Version #: 01 Revision date: - Issue date: 15-April-2019

SDS US

9 / 10

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 15-April-2019

Revision date -

Version # 01

HMIS® ratings
 Health: 3
 Flammability: 3
 Physical hazard: 0

Disclaimer This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found at <http://www.greenfield.com/tc-po-us/>. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the time of writing.