

PE-11 TRU-TEST ENRICH WOOD STAIN

MSDS Number

BMMNZ

National Stock Number

8010-00F021773

Product Name

PE-11 TRU-TEST ENRICH WOOD STAIN

Manufacturer

TRU TEST MANUFACTURING COMPANY

Product Identification

Product ID:PE-11 TRU-TEST ENRICH WOOD STAIN

MSDS Date:07/25/1990

FSC:8010

NIIN:00F021773

MSDS Number: BMMNZ

Responsible Party

TRU-TEST MANUFACTURING COMPANY

201 JANDUS ROAD

CARY , IL 60013

Emergency Phone: 1-800-228-5635

Info Phone: 1-800-639-5383

Cage: TRUTE

Contractor

TRU-TEST MANUFACTURING CO

CARY, IL 60013

US

708-639-5383

Cage: TRUTE

Ingredients

POTASSIUM ALUMINUM SILICATE (FELDSPAR) *4/91*

CAS: 68476-25-5

Fraction By Weight: 1-5%

KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE,

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 58-63%

RTECS: 9999999VO

7.3-7.6

RTECS: 9999999WG

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DRYING.
INHALATION: HEADACHE, DIZZINESS & NAUSEA.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES: IRRITATION. SKIN: DRYING. INHALATION:
HEADACHE, DIZZINESS & NAUSEA.

First Aid

First Aid:EYES: WASH W/FRESH WATER. SKIN: WASH W/WARM WATER & SOAP.
INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF
NECESSARY. INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM &
QUIET. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:105F
Lower Limits:0.9%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:TREAT AS A VOLATILE LIQUID FIRE. WATER SPRAY
MAY BE INEFFECTIVE. IF WATER SPRAY IS USED, FOG NOZZLES ARE
PREFERABLE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL,
ABSORB W/CLAY, SAND OR FLOOR ABSORBENT.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN
FLAMES. FOR STORAGE CONDITIONS SEE OSHA 1910.106. DON'T TAKE
INTERNALLY. GROUND CONTAINERS WHEN POURING.
Other Precautions:AVOID CONTACT W/SKIN. AVOID FREE FALL OF >2-3 INCHES
WHEN POURING.

Exposure Controls

Respiratory Protection:USE A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED
RESPIRATOR IF >TLV. USE AN APPROVED MECHANICAL FILTER TO REMOVE
SOILD AIRBORNE PARTICLES OF OVERSPRAY DURING APPLICATION.
Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST)
TO KEEP Protective Gloves:RECOMMENDED
Eye Protection:SAFETY EYEWEAR
Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING
BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.
Supplemental Safety and Health
BOILING RANGE: 300-360

Chemical Properties

Boiling Pt:B.P. Text:SEE SUPP
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, OPEN FIRE, SPARKS, OPEN FLAME OR
OTHER SOURCES OF IGNITION.

Disposal

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A
LANDFILL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.
PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.