

MATERIAL SAFETY DATA SHEET

MSDS No.:

SS0090

Revision Date: December 2, 2008 Approved by: James A. Bertsch

www.fisheredu.com

Use in keeping with good laboratory practices. Wash thoroughly after handling.

M909 140" 990090	<u></u>
Section 1	Chemical Rioduct and Company Information
Product	SAND, FINE WHITE (OTTOWA)
Synonyms	Silicon Dioxide; Quartz; Crystalline Silica

CHEMITIES Of House Empression Dhome Number (2001) 404-0000

CHEMITREC 24 Hour Emergency Priorie Number (800) 424-9300			
Section 2: Hazards identification	100	100	
Emergency Overview	0 = Minimal	Health	1
		Fire	0
PROLONGED INHALATION MAY CAUSE IRRITATION.	2 = Moderate		

Contact **HMIS**

Reactivity

O

0

Section 3: Composition // Information or lingredients								
Chemical Name	CAS#	%	TLV Units					
Sand	14808-60-7	>99%	TWA: 0.1 mg/m³ (respirable dust) crystalline quartz (ACGIH 2001)					

Section 4 First Aid Measures

Target organs: Lungs.

INGESTION: Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower evelids occasionally. Get immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5. Fire Fighting Measures

General information: Sand will not burn or support fire.

Extinguishing Media: Use any media suitable for extinguishing supporting fire.

Flash Point: Non flammable. Autoignition temperature: N/A

Explosion Limits: Lower: N/A Upper: N/A

NFPA 0 = Minimal1 = Slight 2 = Modera 3 = Serious

None tisted

Section 6 Accidental Release Measures

Recover for use if not contaminated. Sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling & Storage GENERAL STORAGE CODE GREEN

Read label on container before using. Do not wear contact lenses when working with chemicals. Keep container tightly closed. For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

Handling: Use with adequate ventilation. Do not inhale dusts. Wash thoroughly after handling.

Storage: Avoid contamination with other substances.

Section 8 - Exposure Controls / Personal Protection - -

Engineering controls: Facilities storing or utilizing this material should be equipped with an evewash facility and a safety shower. Personnel should wear safety glasses and appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

Physical state: Solid.

Appearance: White, yellow or tan crystals or granules.

Odor: No odor.

pH: N/A

Vapor pressure (mm Hq): N/A Vapor Density (Air = 1): N/A

Evaporation rate (Butyl acetate = 1): N/A Viscosity: N/A

Boiling point: 2230°C (4046°F)

Freezing / Melting point: 1610°C (3110°F)

Decomposition temperature: N/A

Solubility: Insoluble.

Specific gravity (H₀O = 1): 2.65 Percent volatile (%): N/A Molecular formula: SiO_a

Molecular weight: 60.09

Section 10 Stability & Reactivity

Chemical stability: Stable

Hazardous polymerization: Will not occur.

Conditions to avoid: N/A

Incompatibilities with other materials: Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide and oxygen difluoride may cause fire.

Hazardous decomposition products: Will dissolve in hydrofluoric acid and produce silicon tetrafluoride, a corrosive das.

Section 11 Toxicological information

Effects of overexposure: This product contains crystalline silica (suspect cancer hazard), which is considered a hazard by inhalation. May aggravate pre-existing upper respiratory and lung diseases such as bronchitis. emphysema, asthma, etc. May cause irritation of the eyes, throat and nose. Prolonged inhalation of the dust may cause scarring of the lungs, with cough and shortness of breath. A delayed lung injury, silicosis, may result from breathing free silica. Silicosis is a form of disabling, progressive and sometimes fatal pulmonary fibrosis characterized by the presence of typical modulation in the lungs.

ORL-RAT LD50: N/A IHL-RAT LC50: N/A SKN-RBT LD50: N/A

Section:12 Ecological Information

Data not yet available.

Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local state and federal regulations or contract with a licensed chemical disposal agency.

Section:14

UN/NA number: N/A

Shipping name: Not Regulated.

Hazard class: N/A Packing group: N/A Exceptions: N/A

Section 15

Regulatory Information

EINECS-listed (238-878-4)

Section 16 Additional Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. * Hazardous Materials Industrial Standards.