

SAFETY DATA SHEET

Version 6.8 Revision Date 04/17/2021 Print Date 01/15/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name	Ethyl acetate
Product Number Brand	: 319902 : SIGALD
Index-No.	: 607-022-00-5
CAS-No.	: 141-78-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 SPRUCE ST ST. LOUIS MO 63103
	UNITED STATES
Telephone	: +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone #	: 800-424-9300 CHEMTREC (USA) +1-703-
	527-3887 CHEMTREC (International) 24
	Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

SIGALD - 319902

Page 1 of 11



Hazard statement(s) H225 H319 H336	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement(s) P210	Keen away from heat/ charks/ open flames/ bet surfaces. No
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241 P242	Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools.
P242	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable
	for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.1	Substances Formula Molecular weight CAS-No. EC-No. Index-No.	:	C ₄ H ₈ O ₂ 88.11 g/mol 141-78-6 205-500-4 607-022-00-5		
	Component			Classification	Concentration
	ethyl acetate				
				Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %

SIGALD - 319902

Page 2 of 11



SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SIGALD - 319902

Page 3 of 11



SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
- **6.2 Environmental precautions** Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

SIGALD - 319902

Page 4 of 11



Component	CAS-No.	Value	Control parameters	Basis
ethyl acetate	141-78-6	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	400 ppm 1,400 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm 1,400 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	400 ppm 1,400 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Derived No Effec	t Level (DNEL)		
Application Area	Routes of	Health effect	Value
	exposure		
Workers	Inhalation	Acute systemic effects	1468 mg/m3
Workers	Inhalation	Acute local effects	1468 mg/m3
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	734 mg/m3
Workers	Inhalation	Long-term local effects	734 mg/m3
Consumers	Inhalation	Acute local effects, Acute systemic	734 mg/m3
		effects	
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	367 mg/m3
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d
Consumers	Inhalation	Long-term local effects	367 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.24 mg/kg
Sea water	0.026 mg/l
Fresh water	0.26 mg/l
Sea sediment	0.125 mg/kg
Fresh water sediment	1.25 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact

SIGALD - 319902

Page 5 of 11



Material: butyl-rubber Minimum layer thickness: 0.7 mm Break through time: 120 min Material tested:Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.


SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: clear, liquid Color: colorless
b)	Odor	No data available
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 84 °C (183 °F) - lit.
f)	Initial boiling point and boiling range	76.5 - 77.5 °C 169.7 - 171.5 °F - lit.
g)	Flash point	-4 °C (25 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Lower explosion limit: 2.2 %(V)
k)	Vapor pressure	No data available
I)	Vapor density	No data available
m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n-octanol/water	No data available
p)	Autoignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available

SIGALD - 319902

Page 6 of 11





- s) Explosive properties No data available
- t) Oxidizing properties No data available
- **9.2 Other safety information** No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with: Exothermic reaction with: Fluorine chlorosulfonic acid Strong oxidizing agents fuming sulfuric acid Risk of explosion with: lithium aluminium hydride Alkali metals hydrides Alkaline earth metals Violent reactions possible with: Strong acids and strong bases

10.4 Conditions to avoid

Warming.

- **10.5 Incompatible materials** various plastics
- **10.6 Hazardous decomposition products** In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5,620 mg/kg Remarks: (RTECS) Inhalation: No data available

LD50 Dermal - Rabbit - male - > 20,000 mg/kg Remarks: (ECHA) No data available

Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation

SIGALD - 319902

Page 7 of 11



Remarks: (IUCLID)

Serious eye damage/eye irritation

Eyes - Rabbit Result: slight irritation (OECD Test Guideline 405) Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Maximization Test - Guinea pig Result: negative (OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: UDS (Unscheduled DNA synthesis assay) Test system: Escherichia coli Metabolic activation: with and without metabolic activation Method: US-EPA Result: negative

Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative

Test Type: Micronucleus test Species: Chinese hamster Cell type: Red blood cells (erythrocytes) Application Route: Oral Method: OECD Test Guideline 474 Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

SIGALD - 319902

Page 8 of 11



Specific target organ toxicity - single exposure May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 92 Days - NOAEL (No observed adverse effect level) - 900 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,600 mg/kg RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 230 mg/l - 96 h (US-EPA)
Toxicity to algae	static test NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability

aerobic - Exposure time 20 d Result: ca.69 % - Readily biodegradable. Remarks: (ECHA)

Theoretical oxygen	1,820 mg/g
demand	Remarks: (Lit.)

12.3 Bioaccumulative potential No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

SIGALD - 319902

Page 9 of 11



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

FION 14: Transport information		
DOT (US) UN number: 1173 Class: 3 Proper shipping name: Ethyl acetate Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No	Packing group: II	
IMDG UN number: 1173 Class: 3 Proper shipping name: ETHYL ACETATE	Packing group: II	EMS-No: F-E, S-D
IATA UN number: 1173 Class: 3 Proper shipping name: Ethyl acetate	Packing group: II	

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the

SIGALD - 319902

Page 10 of 11



present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.8

Revision Date: 04/17/2021

Print Date: 01/15/2022

SIGALD - 319902

Page 11 of 11

