

SAFETY DATA SHEET

Version 8.1 Revision Date 03/27/2021 Print Date 03/30/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Acetic acid 30% for analysis EMSURE® Reag.

Ph Eur

Product Number : 1.59166 Catalogue No. : 159166 Brand : Millipore

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis, Chemical production

1.3 Details of the supplier of the safety data sheet

Company : EMD Millipore Corporation

400 Summit Drive

BURLINGTON MA 01803

UNITED STATES

Telephone : +1 800-645-5476

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Skin corrosion (Category 1B), H314 Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H314 Causes severe skin burns and eye damage.

Precautionary statement(s)

P264 Wash skin thoroughly after handling.



P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 +	IF IN EYES: Rinse cautiously with water for several minutes.
P310	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
acetic acid			
CAS-No. EC-No. Index-No. Registration number	64-19-7 200-580-7 607-002-00-6 01-2119475328-30- XXXX	Flam. Liq. 3; Skin Corr. 1A; Eye Dam. 1; H226, H314, H318 Concentration limits: 10 - < 25 %: Eye Irrit. 2, H319; 10 - < 25 %: Skin Irrit. 2, H315; 25 - < 90 %: Skin Corr. 1B, H314; >= 90 %: Skin Corr. 1A, H314; >= 90 %: 3, H226;	>= 30 - < 50 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.



If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Mixture with combustible ingredients.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

Fire may cause evolution of:

Acetic acid vapours

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.

6.2 Environmental precautions

Do not empty into drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® H⁺, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed.

Recommended storage temperature see product label.

Storage class (TRGS 510): 8A: Combustible, corrosive hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters



Component	CAS-No.	Value	Control parameters	Basis
acetic acid	64-19-7	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10 ppm 25 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	15 ppm 37 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	10 ppm 25 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	10 ppm 25 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		PEL	10 ppm 25 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	15 ppm 37 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		С	40 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).



Splash contact

Material: Latex gloves

Minimum layer thickness: 0.6 mm Break through time: 30 min

Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not empty into drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor stinging

c) Odor Threshold No data available
 d) pH No data available
 e) Melting No data available point/freezing point

Initial boiling point

f) Initial boiling point and boiling range No data available

g) Flash point > 100 °C (> 212 °F)
 h) Evaporation rate No data available
 i) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 19.9 %(V) - acetic acid flammability or Lower explosion limit: 4 %(V) - acetic acid

explosive limits

k) Vapor pressure No data availablel) Vapor density No data availablem) Relative density No data available

n) Water solubility soluble

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition No data available temperature

q) Decomposition temperature

No data available

r) Viscosity No data availables) Explosive properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

Risk of explosion with:

chromium(VI) oxide

potassium permanganate

peroxi compounds

perchloric acid

nitrates

phosphorus halides

hydrogen peroxide

chromosulfuric acid

Exothermic reaction with:

Metals

Iron

Zinc

Magnesium

alkali hydroxides

nonmetallic halides

ethanolamine

Acetic anhydride

Aldehydes

Alcohols

halogen-halogen compounds

chlorosulfonic acid

strong alkalis

Nitric acid

fuming sulfuric acid

Strong oxidizing agents

Acetaldehyde

Ethylene glycol

Allylamine

Risk of ignition or formation of inflammable gases or vapours with:

ammonium nitrate

potassium tert-butanolate

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

various metals, (generation of hydrogen)

10.6 Hazardous decomposition products

In the event of fire: see section 5



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - > 5,000 mg/kg (Calculation method)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, Pneumonia, bronchitis, Inhalation may lead to the formation of oedemas in the respiratory tract., Symptoms may be delayed.

Dermal: No data available

No data available

Skin corrosion/irritation

Serious eye damage/eye irritation

Mixture causes serious eye damage. Risk of corneal clouding. Risk of perforation! Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available **Specific target organ toxicity - repeated exposure** No data available

Aspiration hazard

No data available

11.2 Additional Information

Not available



Irritation and corrosion, bronchitis, Shortness of breath, gastric spasms, Nausea, Vomiting, Circulatory collapse, shock Risk of corneal clouding. Risk of blindness!

Systemic effects:

gastric spasms acidosis Circulatory collapse shock

Possible damages:

Damage to:

Kidney

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

acetic acid

Acute toxicity

LD50 Oral - Rat - 3,310 mg/kg

Remarks: (RTECS)

LC50 Inhalation - Mouse - 4 h - 2,819 mg/l

Remarks: (RTECS)

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 4 h (OECD Test Guideline 404)

Remarks: (IUCLID)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes burns. - 4 h (OECD Test Guideline 405)

Remarks: (IUCLID)

Causes serious eye damage.

Respiratory or skin sensitization

No data available



Germ cell mutagenicity

Ames test

Salmonella typhimurium

Result: negative

Mutagenicity (mammal cell test): chromosome aberration.

Chinese hamster ovary cells

Result: negative

Mutagenicity (micronucleus test) Rat - male and female - Bone marrow

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Biological effects:

Harmful effect due to pH shift. Caustic even in diluted form.

Discharge into the environment must be avoided.

No data available

Components

acetic acid

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) -

> 1,000 mg/l - 96 h

(OECD Test Guideline 203)



Toxicity to daphnia static test EC50 - Daphnia magna (Water flea) - > 1,000 mg/l

and other aquatic - 48 h invertebrates (OECD Test Guideline 202)

Toxicity to algae static test EC50 - Skeletonema costatum - > 1,000 mg/l - 72 h

(ISO 10253)

Toxicity to bacteria EC5 - Pseudomonas putida - 2,850 mg/l - 16 h

Remarks: neutral

(maximum permissible toxic concentration)

(Lit.)

microtox test EC50 - Photobacterium phosphoreum - 11 mg/l -

15 min

Remarks: (IUCLID)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 2790 Class: 8 Packing group: III

Proper shipping name: Acetic acid solution

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 2790 Class: 8 Packing group: III EMS-No: F-A, S-B

Proper shipping name: ACETIC ACID, SOLUTION

IATA

UN number: 2790 Class: 8 Packing group: III

Proper shipping name: Acetic acid solution

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components



This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.1 Revision Date: 03/27/2021 Print Date: 03/30/2021

