

R319902 Ethyl acetate Ph-Q 4,00L##

00000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ethyl acetate

Number : 00000020226

Product Use Description : Laboratory chemicals

Manufacturer or supplier's

details

Honeywell International Inc. 1953 South Harvey Street Muskegon, MI 49442

For more information call : 1-800-368-0050

+1-231-726-3171

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid

Color : colourless

Odor : like fruit

Classification of the substance or mixture

Classification of the : Flammable liquids, Category 2 substance or mixture : Eye irritation, Category 2A

Specific target organ toxicity - single exposure, Category 3,

Central nervous system

GHS Label elements, including precautionary statements



R319902 Ethyl acetate Ph-Q 4,00L##

000000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Symbol(s) :





Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness and dizziness.

Precautionary statements : **Prevention**:

Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face

protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.



R319902 Ethyl acetate Ph-Q 4,00L##

000000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C4H8O2

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
Ethyl acetate	141-78-6	>=90.00 - <=100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration.

If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes

immediately. Wash contaminated clothing before re-use. Call a

physician if irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician.

Ingestion : Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. If victim is fully

conscious, give a cupful of water. Call a physician.

Notes to physician

Treatment : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Cool closed containers exposed to fire with water spray.

Page 3 / 12



R319902 Ethyl acetate Ph-Q 4,00L##

000000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Specific hazards during

firefighting

: Flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Avoid breathing vapours, mist or gas.

Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods for cleaning up : Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Page 4 / 12



R319902 Ethyl acetate Ph-Q 4.00L##

00000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Handling Wear personal protective equipment.

> Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and

sources of ignition.

No sparking tools should be used.

No smoking.

Storage

Requirements for storage areas and containers

Store in area designed for storage of flammable liquids.

Protect from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures Ensure that eyewash stations and safety showers are close to

the workstation location.

Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.

Engineering measures Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation

during and after use.

Eye protection Do not wear contact lenses.

Wear as appropriate:

Page 5 / 12



R319902 Ethyl acetate Ph-Q	4,00L##
----------------------------	---------

00000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures : When using do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the

product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Upda te	Basis
Ethyl acetate	141-78-6	TWA: Time weighted average	(400 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values

Ethyl acetate	141-78-6	REL:	1,400 mg/m3	2005	NIOSH/GUIDE:US.
		Recomm	(400 ppm)		NIOSH: Pocket
		ended			Guide to Chemical
		exposure			Hazards
		limit			
		(REL):			



R319902 Ethyl acetate Ph-Q 4,00L##

00000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Ethyl acetate	141-78-6	PEL:	1,400 mg/m3	02	OSHA_TRANS:US.
		Permissi	(400 ppm)	2006	OSHA Table Z-1
		ble			Limits for Air
		exposure			Contaminants (29
İ		limit			CFR 1910.1000)

	444 = 0.0	I = 1 1 1 1	4 400 / 0	1000	744 110 00114
Ethyl acetate	141-78-6	TWA:	1,400 mg/m3	1989	Z1A:US. OSHA
		Time	(400 ppm)		Table Z-1-A (29
		weighted			CFR 1910.1000)
		average			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Color : colourless

Odor : like fruit

pH : Note: no data available

Melting point/range : -84 °C

Boiling point/boiling range : 77 °C at 1,013 hPa

Flash point : 25 °F (-4 °C)

Method: closed cup

Evaporation rate : ca. 5

Lower explosion limit : 2.1 %(V)

Upper explosion limit : 11.5 %(V)

Vapor pressure : 97 hPa

at 20 °C(68 °F)

Vapor density : ca. 3 Note: (Air = 1.0)

Page 7 / 12



R319902 Ethyl acetate Ph-Q 4,00L##

000000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Density : 0.901 g/cm3

Water solubility : ca. 90 g/l

Solubility in other solvents : Note: Soluble in most organic solvents

Ignition temperature : 426 °C

Viscosity, kinematic : Note: not determined

Molecular weight : 88.11 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Conditions to avoid : Heat, flames and sparks.

Keep away from direct sunlight.

Incompatible materials to

avoid

: Strong oxidizing agents

Acids Bases

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: 4,934 mg/kg

Species: Rabbit

Method: OECD Test Guideline 401

Page 8 / 12



R319902 Ethyl acetate Ph-Q 4,00L##

00000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

: LD50: 10,200 mg/kg Species: Rat, female

Acute inhalation toxicity : LC0: > 22.5 mg/l > 6000 ppm

Exposure time: 6 h Species: Rat Note: No deaths

Acute dermal toxicity : LD50: > 18,000 mg/kg

Species: Rabbit

Skin irritation : Species: Rabbit

Result: slight irritation

Method: OECD Test Guideline 404

Eye irritation : Species: Rabbit

Result: slight irritation

Method: OECD Test Guideline 405

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : LC50: 230 mg/l

Exposure time: 96 h Species: Salmo gairdneri

Toxicity to algae : EC50: 3,300 mg/l

Exposure time: 48 h

Species: scenedesmus subspicatus

: Growth inhibition NOEC: > 100 mg/l Exposure time: 72 h Species: Algae

Elimination information (persistence and degradability)

Bioaccumulation : Note: Bioaccumulation is unlikely.

Page 9 / 12



R319902 Ethyl acetate Ph-Q 4,00L##

000000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Further information on ecology

Biochemical Oxygen : Value: 293 mg/g

Demand (BOD)

Chemical Oxygen Demand : Value: 1,816 mg/g

(COD)

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1173

Proper shipping name : ETHYL ACETATE

Class 3
Packing group II
Hazard Labels 3

IATA UN/ID No. : UN 1173

Description of the goods : ETHYL ACETATE

Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

IMDG UN/ID No. : UN 1173

Description of the goods : ETHYL ACETATE

Class : 3
Packaging group : II
Hazard Labels : 3
EmS Number : F-E, S-D

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances : On TSCA Inventory

Page 10 / 12



R319902 Ethyl acetate Ph-Q 4.00L##

00000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

Control Act

Australia, Industrial Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian **Environmental Protection** Act (CEPA), Domestic Substances List (DSL)

: All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea, Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

Act

: On the inventory, or in compliance with the inventory

China. Inventory of Existing

Chemical Substances

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

CERCLA Reportable

Quantity

: 5000 lbs



R319902 Ethyl acetate Ph-Q 4,00L##

000000020226

Version 1.0 Revision Date 09/30/2016 Print Date 03/25/2021

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Ethyl acetate 141-78-6

New Jersey RTK : Ethyl acetate 141-78-6

Pennsylvania RTK : Ethyl acetate 141-78-6

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group