SAFETY DATA SHEET

SUPERIOR

1. Identification

Product identifier Isopropyl Alcohol

Other means of identification

0140006 Product code **CAS** number 67-63-0 Recommended use Solvent **Recommended restrictions** None known.

Manufacturer information Superior Oil Company, Inc.

1402 North Capitol Avenue, Suite #100

Indianapolis, IN 46202 US

(317) 781-4400 (317) 781-4400

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 **Health hazards** Acute toxicity, oral Category 4 Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement

Highly flammable liquid and vapor. H225

Harmful if swallowed. H302 Causes serious eye irritation. H319 May cause drowsiness or dizziness. H336

Precautionary statement

Prevention

Do not get in eyes, on skin, or on clothing. P262

P261 Avoid breathing vapors or mist.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

Keep container tightly closed. P233

Ground/bond container and receiving equipment. P240

Use explosion-proof electrical/ventilating/lighting equipment. P241

Use only non-sparking tools. P242

Take precautionary measures against static discharge. P243

Wash thoroughly after handling. P264

Do not eat, drink or smoke when using this product. P270 Use only outdoors or in a well-ventilated area. P271 Wear protective gloves/eye protection/face protection. P280

Response

Material name: Isopropyl Alcohol

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P311 Call a POISON CENTER or doctor/physician. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P332 + P313 If skin irritation occurs: Get medical advice/attention.

1/7

P304 + P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337 + P313 In case of fire: Use appropriate media to extinguish. P370 + P378

Storage

P235 Keep cool.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Isopropanol		67-63-0	100

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medica

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms

may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipmentand precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Highly flammable liquid and vapor.

Material name: Isopropyl Alcohol SDS US

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material	Туре	Value	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
US. ACGIH Threshold Limit Valu	es		
Material	Туре	Value	
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Material	Туре	Value	
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	

Material name: Isopropyl Alcohol SDS US

0140006 Version #: 04 Revision date: 05-14-2019 Issue date: 07-07-2015

Biological limit values

ACGIH Biological Exposure Indices

Material	Value	Determinant	Specimen	Sampling Time	
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*	

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Skin protection

Face shield is recommended. Wear safety glasses with side shields (or goggles).

Wear appropriate chemical resistant gloves. **Hand protection**

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor

cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking.

Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Clear. **Appearance Physical state** Liquid. Color Colorless. Alcohol. Odor Not available. pН Melting point/freezing point Not determined

Initial boiling point and

179.6 °F (82 °C)

boiling range

Flash point 53.6 °F (12.0 °C) Tag Closed Cup (ASTM D-56)

Upper/lower flammability or explosive limits

Flammability limit - lower 2 %

(%)

Flammability limit -

upper (%)

13 %

Vapor pressure 30 mmHg @ 20 °C (68 °F)

Vapor density > 1 (Air = 1)

Solubility(ies)

Solubility (water) **Appreciable**

750.2 °F (399 °C) (ASTM E-659) **Auto-ignition temperature**

Other information

Pounds per gallon 6.608 lb/gal Specific gravity 0.793 VOC 100 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions. Stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Material name: Isopropyl Alcohol 4/7

0140006 Version #: 04 Revision date: 05-14-2019 Issue date: 07-07-2015

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Suitable

precautions should be utilized if using this product at temperatures above the flash point. Contact

with incompatible materials.

Incompatible materials

Acids. Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eve contact Causes serious eye irritation. Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms

may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatique, dizziness and

central nervous system effects. Harmful if swallowed.

Product Species Test Results

Isopropanol (CAS 67-63-0)

Acute **Dermal**

Rabbit **LD50** 12800 mg/kg

Oral

LD50 Rat 4.7 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: Isopropyl Alcohol

Product Species Test Results

Isopropanol (CAS 67-63-0)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this substance.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

0.05

Mobility in soil No data available.

Other adverse effectsThe product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT NON-BULK / BULK:

UN number 1219 Proper shipping name Isopropanol

Hazard class 3 Packing group II ERG code 129

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categoriesAcute toxicity (any route of exposure)
Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Material name: Isopropyl Alcohol sps us

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Isopropanol (CAS 67-63-0) Low priority

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information, go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Isopropanol (CAS 67-63-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

07-07-2015 **Issue date** 05-14-2019 **Revision date**

Version # 04

Disclaimer Superior Oil Company, Inc. cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is based on data available to us and is accurate and reliable to the best of our knowledge at the time of printing. However, no warranty is expressed or implied regarding the accuracy or completeness of the information contained herein. Final determination of the suitability of this material for the use contemplated is the sole responsibility of the user. Buyer assumes all risk and liabilities. Buyer

accepts and uses this material on these conditions.

Material name: Isopropyl Alcohol SDS US 0140006 Version #: 04 Revision date: 05-14-2019 Issue date: 07-07-2015