

National Laboratories
 Lehn & Fink Products Company
 225 Summit Avenue
 Montvale, New Jersey 07645

Telephone Number: (201) 573-5700 (24 hrs)

Emergency Contact: CHEMIREC
 Emergency Phone Number: (800) 424-9300

SECTION #1 - IDENTIFICATION

Product: DECOAT (R) BASEBOARD CLEANER & WAX STRIPPER

CAS Number: Not Applicable
 EPA Reg No.: Not Applicable
 Product Code: EC-182
 Formula No.: V-2881-4

NFPA Hazard Rating - Health: 1 Slight
 - Fire: Level 1 Aerosol
 - Reactivity: 1 Slight

Special Hazards: Contents under pressure

Product Description: Aerosol Wax Stripper

SECTION #2 - CHEMICAL COMPONENTS

Component: ISOBUTANE (AS PROPELLANT) CAS Number: 75-28-5 Simple asphyxiant. Keep oxygen Levels above 19.5%	Percent of Mixture: 7.0 Isobutane is a flammable hydrocarbon propellant in this product.
---------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------

Component: ETHYLENE GLYCOL MONOBUTYL ETHER CAS NUMBER: 111-76-2 OSHA PEL-TWA: 25 ppm ACGIH TLV-TWA: 25 ppm	Percent of Mixture: 5.57 OSHA PEL-STEL: Not Applicable ACGIH TLV-STEL: Not Applicable
---------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------

SECTION #3 - PHYSICAL DATA

Boiling Point: Not Applicable
Vapor Pressure: Not Applicable
Vapor Density (Air=1): >1
Evaporation Rate (Butyl Acetate=1): >1
Specific Gravity: 1.01 @ 25°C
Solubility (H₂O): Soluble
pH 12.0 (concentrate)

Appearance:
Aerosol container.

SECTION #4 - FIRE FIGHTING & EXPLOSION DATA

Flash Point: >200°F TOC (concentrate)

Flammability Class: Level 1 Aerosol

Lower Explosive Limit (%): Not Determined
Upper Explosive Limit (%): Not Determined

Fire and Explosion Hazards:

Contents under pressure. Do not use near fire, sparks or flame. Do not puncture or incinerate container, exposure to temperatures above 120°F may cause bursting.

Extinguishing Media:

Use water spray, foam, dry chemical or carbon dioxide, as suitable for the surrounding fire.

Special Fire Fighting Instructions:

Wear self-contained breathing apparatus and protective equipment appropriate for fighting a typical chemical fire. Move containers away from fire if possible and safe to do so. Use water spray to cool fire-exposed container.

SECTION #5 - EXPOSURE and EFFECTS - INHALATION

Routes of Exposure - Inhalation:
None expected.

SECTION #5 - EXPOSURE and EFFECTS - SKIN

Routes of Exposure - Skin:

Prolonged and/or repeated contact may cause irritation.

First Aid - Skin:

Wash thoroughly with soap and water.

SECTION #5 - EXPOSURE and EFFECTS - EYES

Routes of Exposure - Eyes:

Will cause eye irritation.

First Aid - Eyes:

Immediately flush eyes with plenty of low pressure water. Remove contact lenses to insure a thorough flush and continue to flush with water for at least 15 minutes. If irritation persists, get medical attention.

SECTION #5 - EXPOSURE and EFFECTS - INGESTION

Routes of Exposure - Ingestion:

May cause GI tract irritation.

First Aid - Ingestion:

Drink several glasses of water to dilute the ingested material. Do not induce vomiting. Do not give liquids to an unconscious person. Consult a physician.

SECTION #5 - MISCELLANEOUS TOXICOLOGICAL INFORMATION

CARCINOGENICITY:

NTP - No

IARC - No

OSHA - No

SECTION #6 - REACTIVITY & POLYMERIZATION

Stability: Stable

Conditions to Avoid: Temperatures above 120°F

Incompatible Materials: None known

Hazardous Decomposition Products: None known

Hazardous Polymerization: Will not occur

SECTION #7 - SPILL, LEAK & DISPOSAL PROCEDURES

Steps to be Taken in the Event of Spills, Leaks or Release:

Spills may be flushed to sewer with large quantities of water.

Waste Removal Methods:

Dispose of in accordance with local, state and federal regulations.

Other Environmental Information:

This product contains the following chemicals subject to the reporting requirements Section 313 of the Emergency Planning and Community Right-to-Know Act (EPCRA) of 1986 and of 40 CFR 372:

CAS#	Chemical Name	Percent of Mixture
111-76-2	ETHYLENE GLYCOL MONOBUTYL ETHER	5.57

This information must be included on all MSDSs that are copied and distributed for this material.

SECTION #8 - SPECIAL PROTECTIVE MEASURES

Ventilation:

None required

Protective Clothing:

None required

Respiratory Protection:

None required

SECTION #9 - SPECIAL PRECAUTIONS - STORAGE & HANDLING

Storage & Handling Conditions:

Store in cool, dry location away from heat, sparks or open flames.

SECTION #10 - SHIPPING INFORMATION

Proper Shipping Name: Compressed Gas, N.O.S.

Hazard Class: Non-flammable Gas

Identification Number: UN1956

Labels Required: None

A D D E N D U M

NEW JERSEY WORKER AND COMMUNITY RIGHT TO KNOW ACT:

DECOAT (R) BASEBOARD CLEANER & WAX STRIPPER

<u>NAME</u>	<u>CAS #</u>
WATER	77732-18-5
ISOBUTANE (AS PROPELLANT)	75-28-5
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2
SODIUM LAUROYL SARCOGINATE	137-16-6

DIRECTIONS FOR USE

Shake Well Before Use

Baseboards and Cove Moldings

Hold can 6 to 8 inches from surface. Press button and cover area with foam. Allow 3 to 5 minutes for Decoat™ to penetrate and loosen built-up wax finish. Scrub with an NL® Green or Wine Scrubber Dubber to remove loosened soils. Rinse with clear water.

Dry Stripping—To remove the dirty, marked layer of finish prior to recoating floors.

- Decoat™ can be used manually or attaches to machine-mounted spray units.
- Dust mop floor to remove loose dirt.
- Apply a mist in front of floor machine containing an NL® Blue or Black Stripping Pad.
- Apply enough foam so the first pass of the machine wets the floor.
- Do a 4' x 6' area at a time.
- Continue to scrub area until floor is dry.
- For extremely marked or built-up areas, repeat as necessary.
- Damp mop entire area to remove any dust and heavy residue.
- Recoat floor as needed.

NATIONAL LABORATORIES
LEWIS & FINK INDUSTRIAL PRODUCTS
DIVISION OF STEARNS DRUMS INC.
775 SUMMIT AVENUE
MONTVALE, NEW JERSEY 08054

NATIONAL

DECOAT™

Baseboard Cleaner & Wax Stripper

Removes old wax buildup on baseboards and cove moldings

- Removes old wax buildup on baseboards and cove moldings
- Dry strips dirty floors
- Cleans floor equipment and tools fast
- Sprays in any position—even upside down

KEEP OUT OF REACH OF CHILDREN.

WARNING: CONTENTS UNDER PRESSURE.
Read additional precautions on right side panel.

NET WEIGHT 24 OZ. (1 lb. 8 oz.)

For easy cleaning and stripping of baseboards, mop buckets, wringers, floor machine housings and floor pads. Decoat™ clings to vertical surfaces to provide extended contact time in removal of dirt, oil, grime and heavy wax buildup. Leaves no gritty residue. Contains detergents, grease and wax stripping agents and does not contain phosphates.

Floor Equipment—Apply foam—let soak for 5 minutes—scrub with NL® Green Scrubber Dubber and rinse. For floor machines, DO NOT spray on electrical connections or motors.

Floor Pads—Apply foam on both sides as soon as possible after pad use. Let soak for 5 minutes and rinse using high pressure hose.

WARNING:

Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Never throw container into fire or incinerator. Avoid contact with eyes. Avoid contamination of food.