

# **SAFETY DATA SHEET**

Revision Date 24-Feb-2020 Revision Number 2

## 1. Identification

Product Name Methyl Red, 0.1% w/v solution in ethanol

Cat No.: 38698

Synonyms No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

### Company

Alfa Aesar Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757 **Email:** tech@alfa.com

www.alfa.com

#### **Emergency Telephone Number**

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660.

After normal business hours, call Carechem 24 at (866) 928-0789.

## 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 2
Acute oral toxicity
Category 4
Acute Inhalation Toxicity - Vapors
Category 3
Serious Eye Damage/Eye Irritation
Category 2
Specific target organ toxicity (single exposure)
Category 1

Target Organs - Optic nerve, Central nervous system (CNS).

#### **Label Elements**

## **Signal Word**

Danger

### **Hazard Statements**

Highly flammable liquid and vapor Harmful if swallowed Causes serious eye irritation Toxic if inhaled

#### Causes damage to organs



#### **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

### Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

## Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS.

WARNING. Cancer and Reproductive Harm - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethyl alcohol	64-17-5	86
Methyl alcohol	67-56-1	13
Methylisobutyl ketone	108-10-1	0.9
Methyl red	493-52-7	0.1

### 4. First-aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

**Eve Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

> method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

## 5. Fire-fighting measures

**Suitable Extinguishing Media** Carbon dioxide (CO<sub>2</sub>). Powder, Water spray, In case of major fire and large quantities:

Evacuate area. Fight fire remotely due to the risk of explosion. Water mist may be used to

cool closed containers.

No information available **Unsuitable Extinguishing Media** 

Flash Point 11 °C / 51.8 °F

Method -No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available No data available Lower Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

None known.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability **Physical hazards** 3 3

### Accidental release measures

**Personal Precautions** Ensure adequate ventilation. Use personal protective equipment as required. Keep people

away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources

of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** 

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on Handling

> clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Take precautionary measures against static discharges.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, Storage

sparks and flame.

### 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm	IDLH: 3300 ppm	STEL: 1000 ppm
		(Vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm	
		TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>	
		TWA: 1900 mg/m <sup>3</sup>	_	
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm	STEL: 250 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>	
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm	
		Skin	STEL: 325 mg/m <sup>3</sup>	
		TWA: 200 ppm	_	
		TWA: 260 mg/m <sup>3</sup>		
Methylisobutyl ketone	TWA: 20 ppm	(Vacated) TWA: 50 ppm	IDLH: 500 ppm	TWA: 20 ppm
	STEL: 75 ppm	(Vacated) TWA: 205 mg/m <sup>3</sup>	TWA: 50 ppm	STEL: 75 ppm
		(Vacated) STEL: 75 ppm	TWA: 205 mg/m <sup>3</sup>	
		(Vacated) STEL: 300 mg/m <sup>3</sup>	STEL: 75 ppm	
		TWA: 100 ppm	STEL: 300 mg/m <sup>3</sup>	
		TWA: 410 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures** Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

**Personal Protective Equipment** 

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection** 

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection** 

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

Physical State Liquid

Appearance
Odor
No information available

Melting Point/RangeNo data availableBoiling Point/RangeNo information availableFlash Point11 °C / 51.8 °FEvaporation RateNo information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available
Lower No data available
Vapor Pressure No information available
Vapor Density No information available
Specific Gravity No information available
Solubility No information available
Partition coefficient; n-octanol/water No data available

Autoignition Temperature

Autoignition Temperature

No information available

No information available

No information available

No information available

Viscosity

No information available

(CH3)2 NC6 H4 N=NC6 H4 CO2H

Molecular Weight 269.30

## 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

**Conditions to Avoid** Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Oxidizing agent

Hazardous Decomposition Products None under normal use conditions

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

**Oral LD50** Category 4. ATE = 300 - 2000 mg/kg.

**Dermal LD50**Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

**Vapor LC50** Category 3. ATE = 2 - 10 mg/l.

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg	Not listed	LC50 = 117-125 mg/l (4h)
	OCED 401 (Rat)		OECD 403 (rat)
	3450 mg/kg ( Mouse )		20000 ppm/10H (rat)
Methyl alcohol	LD50 > 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h
Methylisobutyl ketone	LD50 = 2080 mg/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 2000 - 4000 ppm (Rat) 4 h

**Toxicologically Synergistic** 

**Products** 

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No information available Irritation Sensitization No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Group 1	Known	A3	X	A3
Methyl alcohol	67-56-1	Not listed				
Methylisobutyl ketone	108-10-1	Group 2B	Not listed	A3	X	A3
Methyl red	493-52-7	Not listed				

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program) NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

A1 - Known Human Carcinogen ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

No information available. **Teratogenicity** 

STOT - single exposure Optic nerve Central nervous system (CNS)

None known STOT - repeated exposure

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800 mg/L/24h
		LC50 = 14200 mg/l/96h	mg/L/30 min	
			Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	
			EC50 = 43000 mg/L 5 min	

	Methylisobutyl ketone	EC50: 400 mg/L/96h	LC50: 496 - 514 mg/L, 96h	EC50 = 79.6 mg/L 5 min	EC50: 4280.0 mg/L/24h
		_	flow-through (Pimephales	_	EC50: 170 mg/L/48h
1			promelas)		EC50: 4280.0 mg/L/24h
-					

Persistence and Degradability Persistence is unlikely

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Methylisobutyl ketone	1.19
Methyl red	3.83

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component		RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67	-56-1	U154	-
Methylisobutyl ketone -	108-10-1	U161	-

## 14. Transport information

DOT

UN-No UN1170
Proper Shipping Name Ethanol solution

Hazard Class 3
Packing Group ||

TDG

UN-No UN1170

Proper Shipping Name Ethanol solution

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN1170

Proper Shipping Name Ethanol solution

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1170

Proper Shipping Name Ethanol solution

Hazard Class 3 Packing Group II

# 15. Regulatory information

### **United States of America Inventory**

Component	CAS-No	TSCA	TSCA Inventory notification - Active/Inactive	TSCA - EPA Regulatory Flags
Ethyl alcohol	64-17-5	X	ACTIVE	-
Methyl alcohol	67-56-1	Χ	ACTIVE	-
Methylisobutyl ketone	108-10-1	X	ACTIVE	-
Methyl red	493-52-7	X	ACTIVE	-

#### Legend:

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

Component	CAS-No	DSL	NDSL	EINECS	PICCS	ENCS	AICS	IECSC	KECL
Ethyl alcohol	64-17-5	X	-	200-578-6	X	X	Χ	Χ	KE-13217
Methyl alcohol	67-56-1	Х	-	200-659-6	X	X	Х	Χ	KE-23193
Methylisobutyl ketone	108-10-1	Х	-	203-550-1	Х	X	Χ	Χ	KE-24725
Methyl red	493-52-7	X	-	207-776-1	Χ		X	Х	KE-06693

## U.S. Federal Regulations

### **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	13	1.0
Methylisobutyl ketone	108-10-1	0.9	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-
Methylisobutyl ketone	X		-

**OSHA** - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-
Methylisobutyl ketone	5000 lb	-

### California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic	-	Developmental
		beverages only)		Carcinogen
		Carcinogen		
Methyl alcohol	67-56-1	Developmental	-	Developmental
Methylisobutyl ketone	108-10-1	Carcinogen	-	Developmental
		Developmental		Carcinogen

## U.S. State Right-to-Know

Regulations

· · · · · · · · · · · · · · · · · · ·									
Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island				
Ethyl alcohol	X	X	Х	X	X				
Methyl alcohol	X	X	X	X	X				
Methylisobutyl ketone	X	X	X	X	Х				

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

**U.S.** Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Health, Safety and Environmental Department

Email: tech@alfa.com

www.alfa.com

Revision Date 24-Feb-2020 Print Date 24-Feb-2020

Revision Summary SDS authoring systems update, replaces ChemGes SDS No. 2,884.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**