

## SAFETY DATA SHEET

Version 8.5 Revision Date 07/01/2021 Print Date 10/04/2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifiers

Product name : Ethyl Alcohol 200 Proof GR ACS

Product Number : EX0276
Brand : Millipore
Index-No. : 603-002-00-5
CAS-No. : 64-17-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.

Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula : C2H6O

Molecular weight : 46.07 g/mol

CAS-No. : 64-17-5

EC-No. : 200-578-6

Index-No. : 603-002-00-5

Component	Classification	Concentration
ethanol		
	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first-aid measures

### **General advice**

Show this material safety data sheet to the doctor in attendance.

## If inhaled

After inhalation: fresh air.



#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

### Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### **5.3** Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### **6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.



### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

#### 6.4 Reference to other sections

For disposal see section 13.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

### **Hygiene measures**

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

### **Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

**Ingredients with workplace control parameters** 

Component	CAS-No.	Value	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	1,000 ppm 1,900 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		



TWA	1,000 ppm	USA. NIOSH Recommended
	1,900 mg/m3	Exposure Limits
PEL	1,000 ppm	California permissible exposure
	1,900 mg/m3	limits for chemical
		contaminants (Title 8, Article
		107)

### 8.2 Exposure controls

### **Appropriate engineering controls**

Change contaminated clothing. Wash hands after working with substance.

### Personal protective equipment

### **Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

#### **Body Protection**

Flame retardant antistatic protective clothing.

### Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

## **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid Color: colorless

Millipore - EX0276

Millipore

b) Odor pungentc) Odor Threshold 0.1 ppm

d) pH 7.0 at 10 g/l at 20 °C (68 °F)

e) Melting point/freezing point: -144.0 °C (-227.2 °F) at 1,013.25

point/freezing point hPa

f) Initial boiling point 78.29 °C 172.92 °F at 1,013 hPa and boiling range

g) Flash point 13 °C (55 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 13.5 %(V) flammability or explosive limits Upper explosion limit: 2.5 %(V)

k) Vapor pressure 0.57 hPa at 19.6 °C (67.3 °F)

I) Vapor density 1.6

m) Relative density No data available

n) Water solubility 1,000 g/l at 20 °C (68 °F) - completely miscible

o) Partition coefficient: log Pow: -0.35 at 24 °C (75 °F) - Bioaccumulation is not expected.

p) Autoignition 455 °C (851 °F) at 1,013 hPa - DIN 51794

temperature

q) Decomposition Distillable in an undecomposed state at normal pressure. temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

Conductivity  $< 1 \mu S/cm$ 

Surface tension 72.75 mN/m at 20 °C (68 °F)

Relative vapor 1.6

density

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Vapors may form explosive mixture with air.

#### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with: hydrogen peroxide



perchlorates perchloric acid Nitric acid

mercury(II) nitrate permanganic acid

**Nitriles** 

peroxi compounds

Strong oxidizing agents

nitrosyl compounds

Peroxides

sodium

Potassium

halogen oxides

calcium hypochlorite

nitrogen dioxide

metallic oxides

uranium hexafluoride

iodides

Chlorine

Alkali metals

Alkaline earth metals

alkali oxides

Ethylene oxide

silver

with

Nitric acid

silver compounds

with

Ammonia

potassium permanganate

with

conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapours with:

halogen-halogen compounds

chromium(VI) oxide

chromyl chloride

Fluorine

hydrides

Oxides of phosphorus

platinum

Nitric acid

with

potassium permanganate

## 10.4 Conditions to avoid

Warming.

Warming.

## 10.5 Incompatible materials

rubber, various plastics

### 10.6 Hazardous decomposition products

In the event of fire: see section 5

#### **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

### **Acute toxicity**

LD50 Oral - Rat - male and female - 10,470 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l

(OECD Test Guideline 403) Dermal: No data available

No data available

### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h (OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

### Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Methanol

## Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: dominant lethal test

Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 478

Result: Positive results were obtained in some in vivo tests.

### Carcinogenicity

No data available

IARC: 1 - Group 1: Carcinogenic to humans (ethanol)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

### Reproductive toxicity

No data available

### Specific target organ toxicity - single exposure

No data available

### Specific target organ toxicity - repeated exposure

No data available

#### **Aspiration hazard**

No data available

#### 11.2 Additional Information

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) -1,730 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,200 mg/kg

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

static test LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48

15,300 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

and other aquatic

invertebrates Remarks: (ECHA)

static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l Toxicity to algae

- 72 h

(OECD Test Guideline 201)

static test IC50 - activated sludge - > 1,000 mg/l - 3 h Toxicity to bacteria

(OECD Test Guideline 209)

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 15 d

Result: ca.95 % - Readily biodegradable.

(OECD Test Guideline 301E)

Biochemical Oxygen 930 - 1,670 mg/g Demand (BOD) Remarks: (Lit.)

Theoretical oxygen 2,100 mg/g demand Remarks: (Lit.)

### 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No interference with wastewater treatment plants are to be expected when used properly. Discharge into the environment must be avoided.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

### **SECTION 14: Transport information**

DOT (US)

UN number: 1170 Class: 3 Packing group: II

Proper shipping name: Ethanol Reportable Quantity (RQ): Poison Inhalation Hazard: No

**IMDG** 

UN number: 1170 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ETHANOL

**IATA** 

UN number: 1170 Class: 3 Packing group: II

Proper shipping name: Ethanol

### **SECTION 15: Regulatory information**

#### **SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

#### **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313

### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

Millipore

### **SECTION 16: Other information**

#### **Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.5 Revision Date: 07/01/2021 Print Date: 10/04/2021



