

ITEM: 4TH64 - Spray Paint Gloss Equipment Orange

CLICK & FIND

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: B0784

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - B0784

Associated Grainger Item: 4TH64 - Spray Paint Gloss Equipment Orange

MATERIAL SAFETY DATA SHEET

24 HOUR ASSISTANCE:

1-847-367-7700 RUST-OLEUM CORP.

WWW.RUSTOLEUM.COM

----- SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION -----

PRODUCT NAME:
RUST-OLEUM HIGH PERFORMANCE INDUSTRIAL
ENAMEL AEROSOL TOPCOATS (HARD HAT)

IDENTIFICATION NUMBER:
V2123838, V2134838, V2147838,
V2155838, V2156838, V2167838,
V2170838, V2171838, V2174838,
V2175838, V2178838, V2179838,
V2183838, V2184838, V2188838,
V2124838, V2125838, V2133838,
V2137838, V2138838, V2143838,
V2148838, V2163838, V2164838,
V2177838, V2187838, V2190838,
V2192838, V2196838, 209567

REVISION DATE: 04/05/2006

PRODUCT USE/CLASS: TOPCOATS/AEROSOL

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

MANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

----- SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS -----

CHEMICAL NAME	CAS NUMBER	WEIGHT %	ACGIH TLV-TWA LESS THAN
ACETONE	67-64-1	30.0	500 PPM
LIQUEFIED PETROLEUM GAS	68476-86-8	30.0	1000 PPM
TITANIUM DIOXIDE	13463-67-7	15.0	10 MG/M3
MAGNESIUM SILICATE	14807-96-6	15.0	10 MG/M3
n-BUTYL ACETATE	123-86-4	10.0	150 PPM
XYLENE	1330-20-7	10.0	100 PPM
METHYL ETHYL KETONE	78-93-3	10.0	200 PPM
STODDARD SOLVENTS	8052-41-3	5.0	100 PPM
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	5.0	20 PPM
TOLUENE	108-88-3	5.0	50 PPM
ETHYLBENZENE	100-41-4	5.0	100 PPM
AROMATIC HYDROCARBON	64742-95-6	5.0	N.E.
1,2,4-TRIMETHYLBENZENE	95-63-6	5.0	25 PPM
PIGMENT BLACK 7	1333-86-4	5.0	3.5 MG/M3
PIGMENT YELLOW 17	4531-49-1	5.0	2 MG/M3
PIGMENT VIOLET 32	12225-08-0	1.0	N.E.
PIGMENT RED 122	980-26-7	1.0	15 MG/M3

CHEMICAL NAME	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
ACETONE	750 PPM	750 PPM	N.E.
LIQUEFIED PETROLEUM GAS	N.E.	1000 PPM	N.E.
TITANIUM DIOXIDE	N.E.	10 MG/M3	N.E.
MAGNESIUM SILICATE	N.E.	15 MG/M3	N.E.
n-BUTYL ACETATE	200 PPM	150 PPM	N.E.
XYLENE	150 PPM	100 PPM	N.E.
METHYL ETHYL KETONE	300 PPM	200 PPM	N.E.
STODDARD SOLVENTS	N.E.	500 PPM	N.E.

ETHYLENE GLYCOL MONOBUTYL ETHER	N.E.	50 PPM	N.E.
TOLUENE	150 PPM	200 PPM	300 PPM
ETHYLBENZENE	125 PPM	100 PPM	N.E.
AROMATIC HYDROCARBON	N.E.	N.E.	N.E.
1,2,4-TRIMETHYLBENZENE	N.E.	N.E.	N.E.
PIGMENT BLACK 7	N.E.	3.5 MG/M3	N.E.
PIGMENT YELLOW 17	N.E.	5 MG/M3	N.E.
PIGMENT VIOLET 32	N.E.	N.E.	N.E.
PIGMENT RED 122	N.E.	5 MG/M3	N.E.

----- SECTION 3 - HAZARDS IDENTIFICATION -----

EMERGENCY OVERVIEW:
HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. EXTREMELY FLAMMABLE LIQUID AND VAPOR. CONTENTS UNDER PRESSURE. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
MAY BE HARMFUL IF ABSORBED THROUGH SKIN. PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION.

EFFECTS OF OVEREXPOSURE - INHALATION:
HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. HARMFUL IF INHALED.

EFFECTS OF OVEREXPOSURE - INGESTION:
ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. SUBSTANCE MAY BE HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:
IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES. OVEREXPOSURE TO METHYL ETHYL KETONE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY AND LUNG DAMAGE. FETOTOXIC/EMBRYOTOXIC EFFECTS FROM INHALATION HAVE BEEN SEEN IN RATS EXPOSED TO >1000PPM DURING GESTATION.

CONTAINS CARBON BLACK. CHRONIC INFLAMMATION, LUNG FIBROSIS, AND LUNG TUMORS HAVE BEEN OBSERVED IN SOME RATS EXPERIMENTALLY EXPOSED FOR LONG PERIODS OF TIME TO EXCESSIVE CONCENTRATIONS OF CARBON BLACK AND SEVERAL INSOLUBLE FINE DUST PARTICLES. TUMORS HAVE NOT BEEN OBSERVED IN OTHER ANIMAL SPECIES (I.E., MOUSE AND HAMSTER) UNDER SIMILAR CIRCUMSTANCES AND STUDY CONDITIONS. EPIDEMIOLOGICAL STUDIES OF NORTH AMERICAN WORKERS SHOW NO EVIDENCE OF CLINICALLY SIGNIFICANT ADVERSE HEALTH EFFECTS DUE TO OCCUPATIONAL EXPOSURE TO CARBON BLACK.

CARBON BLACK IS LISTED AS A GROUP 2B - "POSSIBLY CARCINOGENIC TO HUMANS" BY IARC AND IS PROPOSED TO BE LISTED AS A4 - "NOT CLASSIFIED AS A HUMAN CARCINOGEN" BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF CARBON BLACK IN THE FORMULA.

PRIMARY ROUTE(S) OF ENTRY:
SKIN CONTACT
SKIN ABSORPTION
INHALATION
EYE CONTACT

----- SECTION 4 - FIRST AID MEASURES -----


FIRST AID - EYE CONTACT:
HOLD EYELIDS APART AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT:
WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:
IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:
ASPIRATION HAZARD:
DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

----- SECTION 5 - FIRE FIGHTING MEASURES -----



FLASH POINT: -156 F (SETAFLASH)
LOWER EXPLOSIVE LIMIT: 0.7 %
UPPER EXPLOSIVE LIMIT: 32.5 %

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

- a. POINT IS LESS THAN 20 DEG. F.:
- b. HIGHLY FLAMMABLE LIQUID AND VAPOR!

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.

SPECIAL FIREFIGHTING PROCEDURES:
EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

SECTION 7 - HANDLING AND STORAGE

HANDLING:
USE ONLY IN A WELL-VENTILATED AREA. AVOID BREATHING VAPOR OR MIST. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING.

STORAGE:
CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:
USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

RESPIRATORY PROTECTION:
A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A FAVORABLE USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

SKIN PROTECTION:
NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION. USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN.

EYE PROTECTION:
USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:
REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

HYGIENIC PRACTICES:
WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: -34 - 900 F

ODOR: SOLVENT-LIKE

APPEARANCE: LIQUID

SOLUBILITY IN H2O: SLIGHT

FREEZE POINT: ND

VAPOR PRESSURE: ND

PHYSICAL STATE: LIQUID

VAPOR DENSITY: HEAVIER THAN AIR

ODOR THRESHOLD: ND

EVAPORATION RATE: FASTER THAN ETHER

SPECIFIC GRAVITY: 0.8660

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:
AVOID TEMPERATURES ABOVE 120 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:
BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

SECTION 11 - TOXICOLOGICAL INFORMATION

PRODUCT LD50: ND

PRODUCT LC50: ND

CHEMICAL NAME	LD50	LC50
ACETONE	N.D.	N.D.
LIQUEFIED PETROLEUM GAS	N.D.	N.D.
TITANIUM DIOXIDE	>7500 MG/KG (ORAL, RAT)	N.D.
MAGNESIUM SILICATE	N.D.	TCLO: 11 MG/M3 INH.
n-BUTYL ACETATE	13100 MG/KG (ORAL, RAT)	2000 PPM (INH 4 HR, RAT)
XYLENE	N.D.	N.D.
METHYL ETHYL KETONE	N.D.	N.D.
STODDARD SOLVENTS	N.D.	N.D.
ETHYLENE GLYCOL MONOBUTYL ETHER	1519 MG/KG (ORAL, MOUSE)	700 PPM (INH 7 HR, RAT)
TOLUENE	N.D.	N.D.
ETHYLBENZENE	3500 MG/KG (ORAL, RAT)	N.D.
AROMATIC HYDROCARBON	N.D.	N.D.
1,2,4-TRIMETHYLBENZENE	N.D.	18000 MG/M3 (RAT, 4 HR)
PIGMENT BLACK 7	>8000 MG/KG (ORAL, RAT)	N.D.
PIGMENT YELLOW 17	N.D.	N.D.
PIGMENT VIOLET 32	>10000 MG/KG (ORAL, RAT)	N.D.
PIGMENT RED 122	N.D.	N.D.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION:
DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2.1

DOT UN/NA NUMBER: UN1950

PACKING GROUP:

HAZARD SUBCLASS:

RESP. GUIDE PAGE: 126

SECTION 15 - REGULATORY INFORMATION

CERCLA - SARA HAZARD CATEGORY:
THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:


IMMEDIATE HEALTH HAZARD
CHRONIC HEALTH HAZARD
FIRE HAZARD

SARA SECTION 313:
LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER
XYLENE	1330-20-7
METHYL ETHYL KETONE	78-93-3
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2
TOLUENE	108-88-3
ETHYLBENZENE	100-41-4
1,2,4-TRIMETHYLBENZENE	95-63-6

TOXIC SUBSTANCES CONTROL ACT:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE



UNITED STATES: NONE KNOWN

U.S. STATE REGULATIONS: AS FOLLOWS

NEW JERSEY RIGHT-TO-KNOW:
THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE
COMPONENTS IN THIS PRODUCT.

CHEMICAL NAME	CAS NUMBER
ALKYD RESIN	MIXTURE

PENNSYLVANIA RIGHT-TO-KNOW:
THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT
GREATER THAN 3%.

CHEMICAL NAME	CAS NUMBER
ALKYD RESIN	MIXTURE
BARIUM SULFATE	7727-43-7
CALCIUM CARBONATE	1317-65-3
YELLOW IRON OXIDE	51274-00-1

CALIFORNIA PROPOSITION 65:

WARNING!

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO
CAUSE CANCER.

WARNING!

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO
CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INTERNATIONAL REGULATIONS: AS FOLLOWS

CANADIAN WHMIS:
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT
REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS:

AB5
D2A
D2B

SECTION 16 - OTHER INFORMATION

HMS RATINGS:
HEALTH 2
FLAMMABILITY 4
REACTIVITY 0
PERSONAL PROTECTION X

INERT ORGANIC COMPOUNDS, G/L:

REASON FOR REVISION:

LEGEND:

N.A.: NOT APPLICABLE
N.E.: NOT ESTABLISHED
N.D.: NOT DETERMINED

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE
ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL
FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

