

Safety Data Sheet

Product: Coleman Camp Fuel

Page: 1 of 6

Issued: 30-June-2014

SECTION 1 - IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

The Coleman Company, Inc.
3600 N Hydraulic
Wichita, Kansas 67219
Phone: 1 800 835 3278 (bus hours)



Chemical Nature: Petroleum Distillates, n.o.s.
Trade Name: Coleman Camp Fuel
Product Use: Fuel for lanterns and camp stoves
Creation Date: 13-August-2012
Revision Date: 30-June-2014



SECTION 2 - HAZARD IDENTIFICATION

UN Number: 1268, Petroleum Distillates, n.o.s.
Classification: Class 3 Flammable Liquid, Category 2
SUSDP Classification: S6



Hazard Statements: DANGER
Highly flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
Causes eye irritation.

Precautionary Statements: Keep out of the reach of children.
Keep away from heat and ignition sources - No Smoking.
Keep in a cool place.
In case of fire, use dry chemical, water fog or foam.
Use only in well ventilated areas.
Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco.
In case of insufficient ventilation, wear suitable respiratory equipment.
Remove to fresh air immediately. Get medical attention immediately.
Do NOT induce vomiting. Get immediate medical attention.
Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.
After contact with skin, take off immediately all contaminated clothing and wash immediately with plenty of soap and water. Get medical attention.
Avoid run off to waterways and sewers.

SECTION 3 - COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical	CAS Number	EC Number	Conc. %	OSHA	Australia	Canada	EU
Light Hydrotreated Distillate	68410-97-9	270-093-2	100%	---	---	---	---
Cyclohexane	110-82-7	203-806-2		300 ppm	100 ppm	100 ppm	200 ppm
Nonane	111-84-2	203-913-4		not set	200 ppm	200 ppm	not set
Octane	111-65-9	203-892-1		500 ppm	300 ppm	300 ppm	not set

Safety Data Sheet

Product: Coleman Camp Fuel

Page: 2 of 6

Issued: 30-June-2014

Heptane	142-82-5	205-563-8	500 ppm	400 ppm	400 ppm	500 ppm
Pentane	109-66-0	203-692-4	1000 ppm	600 ppm	600 ppm	1000 ppm

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

SECTION 4 - FIRST AID MEASURES

Inhalation	Remove person to fresh air and seek immediate medical assistance. Give oxygen if breathing is difficult, give artificial resuscitation if not breathing.
Eye Contact	Irrigate with water for 15 minutes. Hold eyelids open to ensure adequate flushing. Seek immediate medical assistance.
Ingestion	Do NOT induce vomiting. Seek immediate medical assistance.
Skin Contact	Remove contaminated clothing, jewelry and shoes. Wash skin thoroughly with soap and water. Seek immediate medical assistance.

SECTION 5 - FIRE FIGHTING MEASURES

May form flammable mixtures with air and flash at room temperature or upon slight application of heat. Vapors are heavier than air and may travel considerable distance. Explosion hazard in confined spaces if exposed to ignition source. Mists or sprays may be flammable below fuel's normal flash point. Keep away from heat or open flame.

Extinguishing Media:	Use Carbon Dioxide, Dry Chemical or Foam extinguishers.
Fire Fighting:	Fire fighters to wear respiratory protection (positive pressure if available). Do not enter enclosed or confined spaces without proper protective equipment. If leak or spill has not ignited, use water spray to disperse vapors. Water, fog and foam may cause frothing and spattering. Water stream may spread fire. Use water to cool containers exposed to flames.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use personal safety equipment at all times as detailed in Section 8. Evacuate area and shut off all sources of ignition. Contain spill and keep from entering waterways or sewers. Absorb with inert material. Shovel or sweep spill and place in closed container for disposal. Advise EPA or state agency if required.

SECTION 7 - HANDLING AND STORAGE

Handling:	Keep product away from high energy ignition sources, heat, sparks, pilot lights, static electricity and open flame. Avoid contact with skin and inhalation of vapors or mists. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Remove fuel soaked clothing, shoes and gloves and launder before reuse or discard.
Storage:	Store fuel in a cool area with adequate containment in the event of spills. Check containers periodically for leaks.
Special Precautions:	To prevent and minimize fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system. Electrical equipment and fittings must comply with local fire prevention regulations for this class of product. EMPTY CONTAINER WARNING: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY OR OTHER

Safety Data Sheet

Product: Coleman Camp Fuel

Page: 3 of 6

Issued: 30-June-2014

SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Engineering Controls:** Use only in a well ventilated area to keep fuel mists below applicable standards. See Section 3 for exposure limits. Use non-sparking equipment and lighting in areas where explosive vapors may form. Loading, unloading, tank gauging, etc., remain upwind. Keep containers closed when not in use.
- Personal Protection:**
- Eye / Face Protection** Safety glasses, splash goggles or face shield as appropriate. Have suitable eye wash water available.
- Skin Protection** Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective gloves (neoprene, nitrile, viton) and clothing.
If there is a likelihood of splashing oil resistance clothing should be worn.
- Respiratory Protection** Up to 1000 ppm - half mask organic vapor respirator. Up to 5000 ppm - full face organic vapor respirator or full face supplied air respirator. Greater than 5000 ppm, fire fighting or unknown concentration - self contained breathing apparatus with positive pressure should be used.
- Environmental Controls:** Keep fuel from entering waterways and sewers.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Appearance:** Clear, green liquid
- Odor:** Petroleum Naphtha
- Boiling Point:** > 38°C
- Melting Point:** No data available
- Flashpoint:** < -18°C Tag Closed Cup
- Evaporation Rate:** No data available
- Flammability Limits:** No data available
- Flammability Class:** 1B
- Vapor Pressure:** 5.3 psi @ 38°C
- Vapor Density:** 3
- Specific Gravity:** 0.69
- Solubility in Water:** Negligible
- Autoignition**
- Temperature:** No data available

SECTION 10 - STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions of use.
- Conditions to Avoid:** Avoid heat, sparks, open flames and other ignition sources.

Safety Data Sheet

Product: Coleman Camp Fuel

Page: 4 of 6

Issued: 30-June-2014

Materials to Avoid: Avoid contact with strong oxidizing agents.

Hazardous Decomposition: Incomplete combustion may produce fumes, smoke, carbon monoxide and other asphyxiants. HAZARDOUS POLYMERIZATION will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Health Effects: Acute

Ingestion Tests on similar materials indicate an order of acute oral toxicity.

Inhalation Acute toxicity expected on inhalation.

Skin Exposure May cause irritation or dermatitis with prolonged and repeated exposure.

Eye Exposure Irritation on contact.

Medical Conditions Aggravated By Overexposure: Dermatitis and sensitive skin.

This product is not listed as carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs or by OSHA.

SECTION 12 - ECOLOGICAL INFORMATION

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

This product is rapidly biodegradable. Biodegradation is possible within 90 to 120 days in aerobic environments at temperatures above 21°C.

SECTION 13 - DISPOSAL CONSIDERATION

Dispose of in accordance with all local, state and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

Proper Shipping Name: Petroleum Distillates, n.o.s.

UN Number: 1268

Hazard Class 3

Packing Group: II

Marine Pollutant: No

International Maritime Organization (IMDG)

Proper Shipping Name: Petroleum Distillates, n.o.s.

UN Number: 1268

Hazard Class 3

Packing Group: II

Marine Pollutant: No

Safety Data Sheet

Product: Coleman Camp Fuel

Page: 5 of 6

Issued: 30-June-2014

Transport of Dangerous Goods by Road (ADR)

Proper Shipping Name: Petroleum Distillates, n.o.s.

UN Number: 1268

Hazard Class 3

Packing Group: II

Marine Pollutant: No

Transport of Dangerous Goods by Rail (RID)

Proper Shipping Name: Petroleum Distillates, n.o.s.

UN Number: 1268

Hazard Class 3

Packing Group: II

Marine Pollutant: No

International Air Transport Association (IATA)

Proper Shipping Name: Petroleum Distillates, n.o.s.

UN Number: 1268

Hazard Class 3

Packing Group: II

Marine Pollutant: No

SECTION 15 - REGULATORY INFORMATION

SECTION 16 - ANY OTHER RELEVANT INFORMATION

This SDS contains only safety-related information. For other data see product literature.

PLEASE READ ALL LABELS CAREFULLY BEFORE USING PRODUCT.

Manufacturer Disclaimer:

The information contained herein is based upon data available to us and reflects our best professional judgment. However no warranty of merchantability, fitness for any use, or other warranty is expressed or implied regarding the accuracy of such data, the results to be obtained from the use thereof, or that any such use does not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Within the US:

The Coleman Company, Inc.

3600 N Hydraulic

Wichita, Kansas 67219

Phone: 1 800 835 3278 (bus hours)

American Association of Poison Control Centers: 1 800 222 1222

Chemical Emergencies CHEMTREC: 1 800 424 9300 within US, 703 527 3887 outside US

Safety Data Sheet

Product: Coleman Camp Fuel

Page: 6 of 6

Issued: 30-June-2014

Within Australia:

Coleman Brands Pty Limited

Suite W2C1, 75-85 O'Riordan St

Sydney Corporate Park, Alexandria, NSW 2015

Phone: 1 800 224 350 (bus hours)

Poisons Information Centre: 13 1126 within Australia, 0800 764 766 in New Zealand

Within Canada:

Sunbeam Corporation (Canada) Limited

20B Hereford Street

Brampton, Ontario L6Y 0M1

Phone: 1 800 387 6161 (bus hours)

Poison and Drug Information Services: 1 866 454 1212

Within United Kingdom:

Coleman UK Ltd

Kestrel Court, Harbour Road - Portishead

Bristol, BS20 7AN - England

Phone: 44 (0)1275 845024 (bus hours)

National Poisons Information Service: 0845 4647 in England & Wales, 08454 24 24 24 in Scotland,
01 809 2166 in Republic of Ireland

Revisions:

6/30/2014 Added Environmental Control information to Section 8, Marine Pollutant information to Section 14 and
Campingaz United Kingdom contact information.

